


(No Model.)

R. A. STEWART.  
FRUIT CLIPPER.


No. 457,679.

Patented Aug. 11, 1891.


*Fig. 1.*



*Fig. 2.*



*Fig. 3.*



WITNESSES:  
*John H. Deemore*  
*C. Sedgwick*

INVENTOR:  
*R. A. Stewart*  
BY *Munn & Co.*  
ATTORNEYS



# UNITED STATES PATENT OFFICE.

RIPLEY ALSBERRY STEWART, OF LEESBURG, FLORIDA.

## FRUIT-CLIPPER.

SPECIFICATION forming part of Letters Patent No. 457,679, dated August 11, 1891.

Application filed November 21, 1890. Serial No. 372,147. (No model.)

*To all whom it may concern:*

Be it known that I, RIPLEY ALSBERRY STEWART, of Leesburg, in the county of Lake and State of Florida, have invented a new and  
5 Improved Fruit-Clipper, of which the following is a specification, reference being had to the annexed drawings, forming a part thereof, in which—

Figure 1 is a perspective view of my improved fruit-clipper, showing the manner of applying it to the hand. Fig. 2 is a plan view of the clipper as adapted to the left hand, and Fig. 3 is a transverse section taken on line *xx* in Fig. 2.

15 Similar letters of reference indicate corresponding parts in all the views.

My invention relates to certain improvements in that class of clippers in which the clipper is held by loops between the forefinger  
20 and thumb of the hand which grasps the fruit; and the invention consists in the construction and arrangement of parts, as will be hereinafter fully described and claimed.

The shear-blades *A A'* are connected together by the rivet or screw *a*. The blades  
25 are rounded at their pivoted end and curved slightly and pointed at their free ends. To the inner face of the blade *A* is attached a guard-plate *B*, which extends over the blade  
30 *A'* and receives the rivet *a*.

To the edges of the blades *A A'* are attached the double flanges *C C'* for receiving the thumb and forefinger. To the two parts  
35 of the flange *C* are attached loops *b b'*, of flexible material, for holding the forefinger, and to the parts of the flange *C'* are attached straps *c c'* for holding the thumb. To the outer flange *C* is attached an elastic strap *D*,  
40 which extends along the side of the hand and is attached to a strap *E*, which surrounds the wrist.

My improved fruit-clipper is held on the hand, as shown in Fig. 1, and is used by opening and closing the blades by means of the

forefinger and thumb, the fruit being grasped 45 by the hand while the stem is cut by the shears. The stem is supported during the cutting operation by the guard *B*—that is to say, the inner edge of the guard *B* will engage the stem a short distance from where it is engaged by the cutting-edge of blade *A*, and  
50 therefore when the blades *A A'* are moved toward each other the fruit-stem will cross the blades at right angles and be evenly cut. The guard being parallel with and spaced 55 from the blade *A* a distance equal to the thickness of the blade *A'* will prevent the blades from spreading apart laterally when their pivot gets somewhat loose, for the blade *A'* works in the space between said guard and  
60 blade *A'*. The guard has nothing in common with a stem-retaining device secured to one blade of certain shears and lying in the path of the opposing blade to grasp a severed stem and hold it with the attached fruit or flower. 65 In fruit-pickers of the class to which mine belongs there is a tendency for them to fall from the thumb and forefinger; but the elastic strap *D* exerts sufficient strain to draw the clippers rearward into the proper position. 70

Having thus described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. In a fruit-clipper, the combination of the blades *A A'*, provided with the double flanges 75 *C C'*, the spaced parallel guard-plate *B*, the rivet *a*, and the finger, thumb, and wrist straps, substantially as specified.

2. In a fruit-clipper, the combination of the curved blades *A A'*, provided with flanges *C* 80 *C'*, the spaced parallel guard-plate *B*, the rivet *a*, the finger-straps *b b'*, the thumb-straps *c c'*, the elastic strap *D*, and the wrist-strap *E*, substantially as specified.

RIPLEY ALSBERRY STEWART.

Witnesses:

P. W. BUTLER,  
THOS. W. SPICER.