

(No Model.)

R. B. McKAY.
PLOW.

No. 457,893.

Patented Aug. 18, 1891.




Fig. 1.




Fig. 2.

Witnesses

Arthur Ashley
J. Paul

Inventor

By his Attorneys, Robert B. McKay

C. Snow & Co.

UNITED STATES PATENT OFFICE.

ROBERT B. MCKAY, OF LOGANSFORT, LOUISIANA, ASSIGNOR OF ONE-HALF
TO BAILEY A. ROPER, OF TENAHA, TEXAS.

PLOW.

SPECIFICATION forming part of Letters Patent No. 457,893, dated August 18, 1891.

Application filed April 21, 1891. Serial No. 389,862. (No model.)

To all whom it may concern:

Be it known that I, ROBERT B. MCKAY, a citizen of the United States, residing at Logansfort, in the parish of De Soto and State of Louisiana, have invented a new and useful Plow, of which the following is a specification.

The invention relates to improvements in reversible plows.

The object of the present invention is to simplify and improve the construction of reversible plows and enable them to be adjusted to any desired depth.

The invention consists in the construction and novel combination and arrangement of parts, hereinafter fully described, illustrated in the accompanying drawings, and pointed out in the claims hereto appended.

In the drawings, Figure 1 is a perspective view of a reversible plow embodying the invention. Fig. 2 is a longitudinal sectional view.

Referring to the accompanying drawings, 1 designate handle-bars having their front portions parallel and their rear portions diverging, and the front ends of the handle-bars are secured to the axle 2 of a wheel 3. The shares or blades 4 and 5 are secured to the outer ends of diverging standards 6, and are preferably different in construction and are of the forms desired. The standards 6 have their inner ends connected and secured to a curved rack-bar 7, and are connected to the ends of a cross-bar 8, which is pivoted intermediate its ends by a bolt 9 to the handle-bars 1, whereby the standards are secured to the handle-bars. Both the standards and the cross-bar 8 are arranged between the parallel portions of the handle-bars, and the bolt 9 serves as a pivot on which the frame formed by the standards and the cross-bar turns to carry the shares or blades 4 and 5 to and from the wheel to regulate the depth of the blades or shares.

The shares or blades are adjusted by means of a cog-wheel 10, mounted on a shaft 11 and arranged to engage the segmental rack-bar 7, and one end of the shaft 11 is provided with a handle 12, by which the cog-wheel is rotated. The parts are secured at the desired adjust-

ment by a double pawl 13, pivoted intermediate its ends, and being substantially U-shaped, with inwardly-bent ends adapted to engage the upper edge of the cog-wheel.

It will readily be seen that the adjustable and reversible plow is simple and inexpensive in construction and is adapted to be readily secured at any desired adjustment.

In Fig. 1 of the accompanying drawings I have illustrated in dotted lines the relative position, swing, and line of adjustment of the shares or blades. The line *a a* shows the relative position of the blades, and the curved line *b b* illustrates the line of adjustment of the blades made by turning the share-carrying frame on its pivot, and the circle C shows the swing of the shares or blades and illustrates that the handles may be raised or lowered without materially affecting the depth of the share or blade.

What I claim is—

1. In a reversible plow, the combination of the wheel, the handle-bars, the share-carrying frame pivoted to the handle-bars, the shares secured to the frame and arranged on opposite sides of the wheel, the curved rack-bar secured to the frame, a cog-wheel arranged to engage the rack-bar, and means for securing the parts at any desired adjustment, substantially as described.

2. In a reversible plow, the combination of the wheel, the handle-bars, the share-carrying frame comprising the diverging standards and the cross-bars connecting the standards and pivoted intermediate its ends to the handle-bars, the shares secured to the standards, the curved rack-bar attached to the inner ends of the standards, a cog-wheel arranged to engage the rack-bar, and a pawl pivoted to the handle-bars and arranged to engage the cog-wheel, whereby the parts are secured at any desired adjustment, substantially as described.

3. In a reversible plow, the combination of the wheel, the handle-bars, the share-carrying frame pivoted to the handle-bars, the shares secured to the frame and arranged on opposite sides of the wheel, the curved rack-bar secured to the frame, a shaft journaled

in suitable bearings and provided at one end
with a handle, a cog-wheel mounted on the
shaft and arranged to engage the rack-bar,
and the double pawl approximately U-shaped
5 and having inwardly-bent ends arranged to
engage the cog-wheel, substantially as de-
scribed.

In testimony that I claim the foregoing as
my own I have hereto affixed my signature in
presence of two witnesses.

ROBERT B. MCKAY.

Witnesses:

D. MIDDLETON,
W. C. HARDY.