(No Model.)

S. SMITH. SHEARS SHARPENER.

No. 458,004.

Patented Aug. 18, 1891.




Fig. 2.

C
A
A
A

Witnesses:

Fred F. Amold. E. F. Dowling Inventor:

Sylvester Smith, H. H. Mornison, Attorney.

United States Patent Office.

SYLVESTER SMITH, OF GUILFORD, ILLINOIS.

SHEARS-SHARPENER.

SPECIFICATION forming part of Letters Patent No. 458,004, dated August 18, 1891.

Application filed May 5, 1891. Serial No. 391,662. (No model.)

To all whom it may concern:

Be it known that I, SYLVESTER SMITH, of Guilford, in the county of Winnebago and State of Illinois, have invented certain new and useful Improvements in Sharpeners for Shears, of which the following is a specification.

My invention relates to sharpeners for shears, composed of a slotted block, a file, and means for operatively securing said parts together; and it consists of certain new and useful features of construction and combinations of parts hereinafter described, and pointed out in the claim.

Referring to the accompanying drawings, which form a part of this specification, Figure 1 is an isometric view of a shears-sharpener embodying my invention. Fig. 2 is a longitudinal section at the dotted line X X in Fig. 1 of the parts there shown.

Like letters of reference indicate corresponding parts throughout the several views.

A is a file-block having a laterally-inclined passage A' extending longitudinally therethrough and a vertical longitudinal slot A² in the top thereof, opening into the passage A', one side whereof, as A³, being inclined, as shown, and being provided with a tapering key-seat A⁴, located in the longitudinal cen-

30 ter of the bottom of the passage A' therein. B is a flat file narrower than the passage A' to allow the former to be laterally adjusted in the latter.

C is a key adapted to be slid longitudinally in the key-seat A⁴ in the block A to secure

the file B in operative position therein. The inclined side A³ of the slot A² serves to give the proper inclination to the shear-blades while they are being sharpened, which is done by placing the outside of the same against the 40 inclined side A³ of the slot A² and drawing them from heel to point across the file B, at the same time pressing evenly upon the blades, repeating the operation until the requisite degree of sharpness is obtained. When-45 ever the operative portion of the file becomes dull from use, the key C may be loosened and the former moved the requisite distance to either side and again secured in place by tightening the key C.

In combination, in a sharpener for shears, the file-block having the laterally-inclined passage A' extending therethrough and the vertical longitudinal slot A² in the top there- 55 of, the side A³ whereof is inclined, as shown, and being provided with a tapering key-seat A⁴, located in the longitudinal center of the bottom of the passage A', the file narrower than the passage A' in the block A to admit 60 of lateral adjustment therein, and the key C, adapted to be slid longitudinally in the key-seat A⁴, all of said parts being constructed, arranged, and combined substantially as and

SYLVESTER SMITH.

Witnesses:

L. L. Morrison, E. F. Dowling.

for the purpose specified.