


(No Model.)

G. HIPWOOD.
CAN OPENER.

No. 458,703.

Patented Sept. 1, 1891.



WITNESSES=
W. J. Coyn
A. Dwyer

INVENTOR=
George Hipwood,
PER Chas. Shaw,
ATTY.

UNITED STATES PATENT OFFICE.

GEORGE HIPWOOD, OF BOSTON, MASSACHUSETTS, ASSIGNOR OF ONE-FOURTH
TO FRANCIS F. BIBBER, OF SAME PLACE.

CAN-OPENER.

SPECIFICATION forming part of Letters Patent No. 458,703, dated September 1, 1891.

Application filed June 1, 1891. Serial No. 394,641. (No model.)

To all whom it may concern:

Be it known that I, GEORGE HIPWOOD, of Boston, in the county of Suffolk, State of Massachusetts, have invented certain new and
5 useful Improvements in Can - Openers, of which the following is a description sufficiently full, clear, and exact to enable any person skilled in the art or science to which said invention appertains to make and use the
10 same, reference being had to the accompanying drawings, forming part of this specification, in which—

Figure 1 is an elevation showing my improved can-opener in use, the body of the can
15 being represented as broken away; Fig. 2, an end elevation of the same, looking from the left in Fig. 1; Fig. 3, a bottom plan view of the guard, and Figs. 4 and 5 views of the guards, illustrating modifications in the ad-
20 justing mechanism.

Like letters of reference indicate corresponding parts in the different figures of the drawings.

My invention relates, especially, to a de-
25 vice for opening tin cans and is designed as an improvement on the implement shown and described in United States Letters Patent numbered 450,810, dated April 23, 1891, and granted to me for new and useful improve-
30 ments in can-openers.

In the drawings, A represents the can, and B the guard, of the can-opener considered as a whole, and C the handle.

The guard B comprises a semi-disk *d*, from
35 the periphery of which lugs *f* are pendent. The disk *d* is adapted to rest upon the top of the can and is provided with a longitudinal knife-slot *g*, which is arranged out of parallelism with a line tangent to the central ra-
40 dial line of said semi-disk or segment. A plate *h* is fitted to slide horizontally in suitable ways formed in the lugs *f* and is provided on its inner end with a curved head *i*, which is adapted to engage and conform to
45 the curve of the side wall of the can. An adjusting-screw *j*, passing centrally through the lug *f*, engages the slide-head *i* or is fitted

to turn loosely therein, forcing said slide against the can.

A curved or hook-shaped cutting-blade *k* is 50
secured in the handle C and is pivoted at *m* in the knife-slot *g* of the segment *d* eccentrically of the center of said segment or semi-disk. The handle C projects at *p* in front of the pivot of said knife, to afford a bearing 55
for the hand in obtaining sufficient leverage to force the point of the blade through the can-top *q*.

In the use of my improvement the semi-disk *d* is disposed on the top of the can, as 60
shown best in Fig. 2, and the gage-plate *h* adjusted by means of the screw *j* so as to bring the knife-point at a desired distance from the side of the can. The parts being in the posi- 65
tion shown by dotted lines in Fig. 1, the operator, by forcing the toe *p* of the handle downward, readily drives the point of the curved blade *k* through the can-top, said blade being provided, in the ordinary manner of 70
blades of this class, with a cutting-edge on both sides. By moving the handle vertically the knife is caused to cut its way through the can-top, the guard-plate *h*, bearing against the side of the can, readily directing the 75
movement of said knife as it is fed along by the operator. The slot *t* cut by the knife being on a circle with the same center as the can-side, to prevent liability of the blade *k* binding and tending to work in straight line 80
toward the outer edge of the can-side, the diagonal slot *g* is provided. The inner end of said slot, being farther from the periphery of the can than the pivot *m*, slants the knife sufficiently in relation to the guide to enable 85
it to feed readily without binding.

In Fig. 4 the lugs *f* are substituted by a segment *v*, through which two screws *w* are 90
turned to engage the side of the can and perform the same function as the guide-plate *h*.

In Fig. 5 the guide-plate *h* is fitted to slide 90
in the bottom of the segment *v*. A rod *x*, secured to the head *i* of said plate, passes centrally through said segment and is provided with notches *y*, in which a rod *z*, pivoted to

outer face of said segment, is fitted to take and lock the guide-plate in position.

Having thus explained my invention, what I claim is—

- 5 In a can-opener, a guard comprising a segmental plate adapted to engage the can-top and provided with a pendent lug, a guide adjustable horizontally in said lug and adapted

to engage the side of the can, and a curved cutting-blade pivoted to swing vertically in said segment, substantially as described.

GEORGE HIPWOOD.

Witnesses:

K. DURFEE,
O. M. SHAW.