


(No Model.)

C. T. SEGAR.
FOLDING COT.

No. 464,524.

Patented Dec. 8, 1891.



WITNESSES.

Rich. George.
Elwin H. Riley

INVENTOR.

Chas T Segar.
By Riley Elwin H. Riley
attys

UNITED STATES PATENT OFFICE.

CHARLES T. SEGAR, OF UTICA, NEW YORK, ASSIGNOR TO ERASTUS Z. WRIGHT, RECEIVER.

FOLDING COT.

SPECIFICATION forming part of Letters Patent No. 464,524, dated December 8, 1891.

Application filed January 31, 1887. Serial No. 226,094. (No model.)

To all whom it may concern:

Be it known that I, CHARLES T. SEGAR, of Utica, in the county of Oneida and State of New York, have invented certain new and
5 useful Improvements in Folding Beds or Cots; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it appertains to make and use the
10 same, reference being had to the accompanying drawings, and to the figures of reference marked thereon, which form part of this specification.

My invention relates to a folding bed or
15 cot; and it consists in the mechanism herein-after more fully described and pointed out.

In the accompanying drawings, Figure 1 represents a perspective view of my improved bed or cot. Fig. 2 represents a side view of a
20 one-end section of my improved bed or cot, showing the side bar and posts in the position in which they are when in use. Fig. 3 represents a side view of Fig. 2, showing the position of the parts when partly folded. Fig.
25 4 represents a side view of Figs. 2 and 3, showing the same folded into a compact space to be stowed away or shipped. Fig. 5 shows a portion of my improved folding bed or cot, as shown in Fig. 3, provided with a stop for en-
30 gaging the side bar.

In constructing folding beds or cots, whether constructed of iron, brass, or any other suitable material, it is desirable, for convenience in storing or shipping, that the legs and ends
35 forming the head and foot of the bed be folded into the same space occupied by the bed-bottom. I attain these beneficial results by the use of a system of braces and stops, whereby the ends forming the head and foot of the
40 bed or cot may be folded into a compact space substantially of the same size as the bed frame or bottom proper. I attain these beneficial results by the use of side bars 1 1 and end bars 2 2, which are preferably secured at
45 3 3 3 3, Fig. 1, in suitable manner, so as to be rigidly held together, the side and end bars being of the required size. I then provide legs 4 4 4 4 with suitable rounds 5 5 5 for holding the legs in proper position.

50 It will readily be seen that any other device

for holding the legs may be used without departing from the spirit of my invention. The legs and side bars are held in position by means of braces 6 6 6 6, one end of each brace being pivoted to the side bars at 7 7 on each
55 side bar and the opposite end of the braces are pivoted to the legs at 8 8. In constructing and pivoting these braces they should be of sufficient length to carry the legs substantially parallel with the bed-bottom when the
60 same are moved forward and folded into a compact space, as shown in Fig. 4. The length of the braces determines the location of the legs when folded under the bottom. In the drawings additional braces are shown in Fig. 65
3, and are pivoted to each leg and side bar on the inside of the frame in such manner as to form a connection between the legs and the side bars, the braces 9 being pivoted to side
70 bars and legs at 10 10 on each side and end of the bed-frame. These braces, when the bed is extended as shown in Fig. 1, are substantially parallel with the side bars. The side bars in the drawings being constructed of angle-iron, the upper angle rests at each end
75 on braces 9, forming a reliable means of holding the bed-frame when extended. It is quite obvious that if the side bars are made of round or square form a stop may be used on the inner side of the side rails for engaging
80 braces 9.

It is quite obvious that a stop or hook may be provided for engaging the ends of the side bars and legs when the legs are extended, as shown in Fig. 1. The stop consists of projec-
85 tions 11 11 and hooks 11^a 11^a, Fig. 5, or any other suitable means for engaging the extremes of the side bars and legs when extended.

What I claim as new, and desire to secure
90 by Letters Patent, is—

The combination, in a folding cot-bed, of a bed-bottom consisting of a frame composed of cross-bars and side rails rigidly secured together and a fabric stretched thereon, sup-
95 porting-legs in pairs, each leg at the end of a side rail, two braces 6 and 9, of unequal length, for each leg on the same side, pivoted at their respective ends to the side rail and leg, the legs passing by the end of the side rail and
100

having for each pair of legs an upward extension forming a head and foot board, the leg being adapted to fold from its vertical supporting position to a parallel position with
5 the side rails, and the frame supported in extended position by resting on brace 9, substantially as set forth.

In witness whereof I have affixed my signature in presence of two witnesses.

CHARLES T. SEGAR.

Witnesses:

EDWIN H. RISLEY,
MILTON E. ROBINSON.