
(No Model.)

H. M. CLARK. COMBINED WAIST AND SUSPENDERS.

No. 477,648.

Patented June 28, 1892.



UNITED STATES PATENT OFFICE.

HARRIET M. CLARK, OF FLUSHING, NEW YORK.

COMBINED WAIST AND SUSPENDERS.

SPECIFICATION forming part of Letters Patent No. 477,648, dated June 28, 1892.

Application filed April 4, 1892. Serial No. 427,611. (No model.)

To all whom it may concern:

Be it known that I, HARRIET MERRELL CLARK, residing at Flushing, in the county of Queens and State of New York, have in-5 vented certain new and useful Improvements in Waists and Supporters, of which the following is a specification, reference being had therein to the accompanying drawings.

This invention relates to suspenders or garro ment-supports and waists especially for chil-

dren's wear.

The object of the invention is to produce a suspender connected to a waist in such manner that the nether garments may be sup-15 ported at the back by an elastic support extending to the shoulder-band of the waist or shirt; also, to produce a combined waist and elastic suspender in which the weight supported from the shoulders shall be distributed: 20 at the waistband; also, to make a washable garment having elastic suspenders removable therefrom; also, to improve various details in the construction of garment-supports.

Figure 1 is a front view of a shirt-waist 25 thrown open at the front to show the connection of the suspenders at the back thereof. Fig. 2 is a rear elevation of the same, the suspenders indicated in dotted lines. Fig. 3 is a rear elevation of an underwaist with sus-30 pender and stocking-support attachments. Figs. 4 and 5 are sectional details of the part connecting the suspenders to the shoulderstrap. Fig. 6 is an enlarged detail of the suspender detached.

The letter A indicates a shirt or washable waist, such as is worn by small boys, and having buttons B B for the attachment of trous-

ers or knickerbockers to the waist.

In the present invention the buttons at the 40 back of the waist areomitted, and instead of atteching the trousers directly to the waist at the back the trousers are there attached to buttons or other common fastenings B, which are attached to elastic suspenders C.

The body of the elastic suspenders C is formed from a single piece of elastic webbing, which is folded back and forth upon itself nearly in form of the Roman capital M or like an inverted W. The middle fold is se-50 cured permanently by stitching or similar fastening, and a tab c is preferably attached. The webbing at the fold or the tab, or both,

should have an attaching device, such as a button or buttons B. The reverse folds of the webbing pass through links D D of metal 55 or other strong material, and the webbing is secured by stitching to retain the links permanently. The ends of the webbing are preferably reinforced by tabs e e of inelastic material, and the buttons B are attached to said 60 tabs.

The waist, whether a shirt-waist or underwaist, has shoulder-straps F extending from the shoulder-seam down the back of the garment and preferably stitched to the garment, 65 These straps incline from the shoulders toward the middle of the back. The ends of straps F are free, or the straps have continuations F' sewed to the straps and garmont and provided with buttonholes. A button B' is 70 sewed to each strap a little above the end, and the free ends of these straps F or their continuations F' are passed through rings D and then buttoned over buttons B'. The upper folds of the suspenders are thus connected 75 to the shoulder-straps of the garment, and the central fold of the suspenders is in such position as to draw from both shoulder-straps, while the end pieces of the webbing draw separately on the straps and garment con- 80 nected thereto.

Holes H in the shirt-waist similar to buttonholes are provided at the back, through which holes the tabs cee pass, and the trousers are buttoned to the buttons on these tabs. 85 The suspenders C permit the movement of the body in bending without drawing on the material of the shirt-waist below the points of attachment of the suspenders, and as the waist above these points is strengthened by 90 the shoulder-straps the pull on the back of the collar-band and the tearing off of buttons is avoided.

In attaching the same suspenders to underwaists, as A', the connection is made at the 95 outside instead of inside of the garmout, and thus the holes II are avoided. The shoulderstraps F2 extend over the shoulders as far as may be necessary to insure the required strength. At the back of the garment these 100 straps are attached to the textile material of the garment by stitching, and the tab F3 is attached by stitching between the fabric of the garment and the shoulder-strap and buttoned back on the buttons B', as has been described.

For washing the waists the straps F' or F2 are unbuttoned and the suspenders C are then 5 removed from the waist, which can then be washed with no more difficulty than pertains to washing buttoned garments of similar character.

The shoulder-straps F2 are preferably atro tached to the body of the waist along the lines of greatest strength. Straps S may be connected to the waist between the shoulderstraps and body portion and extend down at the side of the wearer for attachment of 15 the stocking-supporters. The stocking-supporters may then extend down between the trousers and drawers of the wearer instead of passing inside the drawers, as is generally the case with garments of this character. In 20 this instance, as with the suspenders, the weight is supported from the shoulder-straps.

From the foregoing description, covering modifications, it will not be difficult to deduce other modifications, bearing in mind that the 25 salient features of the invention are the suspenders in their peculiar form and the connection of the same to the shoulders of the garment by straps extending in such direction as to secure great strength in the garment

30 and comfort to the wearer

What I claim is— 1. The garment having straps attached thereto at the shoulders and extending down the back, where they are provided with attach-35 ing means, in combination with the elastic M-

shaped suspenders having means for attaching one of the upwardly-extending folds to the strap extending from one shoulder only and the other fold to the other shoulder-strap and means for attaching the two downwardly-ex- 40 tending ends and the middle fold to the nether garment, substantially as described.

2. The garment having shoulder-straps attached and extending down the back, as described, and provided at the lower ends with 45 tabs and buttons, in combination with the Mshaped elastic suspenders having loops at the two upper folds, through which the said tabs extend, said suspenders having means for attaching the two pendent ends and the pend- 50 ent middle fold to the netwer garment, sub-

stantially as described.

3. The shirt-waist described, having attached inside shoulder-straps extending down the back, provided with tabs, as described, and 55 having holes below said shoulder-straps for the passage of the suspenders, in combination with the M-shaped suspenders connected at their upper folds to said tabs and having their lower ends and folds extending through the 60 holes in the shirt and provided with means for attachment to a nether garment, substantially as described.

In testimony whereof I affix my signature in

presence of two witnesses

HARRIET M. CLARK.

Witnesses: FRANKIE M. HITCHINS WM. H. MERRELL.