

J. J. COCHRAN. WRAPPER.

No. 481,846.

Patented Aug. 30, 1892.





Witnesses:

United States Patent Office.

JOHN J. COCHRAN, OF ST. LOUIS, MISSOURI, ASSIGNOR OF TWO-THIRDS TO ALFRED T. GERRANS AND HIRAM A. BRIDGES, OF SAME PLACE.

WRAPPER.

SPECIFICATION forming part of Letters Patent No. 481,846, dated August 30, 1892.

Application filed December 14, 1891. Serial No. 415,074. (No model.)

To all whom it may concern:

Be it known that I, JOHN J. COCHRAN, of St. Louis, Missouri, have made a new and useful Improvement in Wrappers, of which the fol-5 lowing is a full, clear, and exact description.

By means of the present improvement a wrapper for newspapers, magazines, pamphlets, and other articles is not only adapted to be readily opened, but is also materially

strengthened. It consists, substantially, in a thread, cord, band, ribbon, tie, ligature, fiber, or analogous article secured to the inner side of the wrapper, with an end projecting beyond the 15 edge of the wrapper. The person opening a bundle inclosed with the improved wrapper grasps the projecting end referred to and draws it away from the bundle, thereby ripping the wrapper and readily removing it

20 from the bundle.

when the cord is applied to the wrapper in such a manner as to cause it when the wrapper is attached to the bundle to extend more 25 or less around the bundle, so as to serve as a tie or to strengthen the wrapper in the direction of its length, all substantially as is hereinafter described and claimed, aided by the annexed drawings, making part of this speci-30 fication, in which—

Figure 1 is a view of the inner side of the improved wrapper, and Fig. 2 a view in perspective of the wrapper applied to a bundle.

The same letters of reference denote the

35 same parts.

The wrapper A is usually a piece of paper

and of suitable size and shape.

B represents the cord, tie, or fiber, &c. It is preferably secured to the inner side a of 40 the wrapper, and preferably by gluing or cementing it thereto—that is, the improvement in a measure may be carried out by embodying the fiber, &c., in the wrapper, either at the time of the manufacture of the paper 45 from which the wrapper is ultimately formed or by making the wrapper in two or more folds and inclosing the fiber, &c., between them, in either of which cases the fiber, &c., should be so attached to the wrapper as to 50 enable it when drawn as described to carry the underlying portion of the wrapper with

it, so as to practically accomplish the opening of the wrapper; or the cord, &c., may be and in practice preferably is attached, as shown, to the inner side of the wrapper. The cord 55 should be secured throughout its length substantially to the wrapper, as thereby the object of the improvement is more fully attained. The cord is preferably arranged so that its projecting end b shall not come upon 60 the customary gummed portion a' of the wrapper. While the cord, &c., may be otherwise extended upon the wrapper and some of the purposes of the improvement accomplished, I prefer to arrange it substantially 65 diagonally upon the wrapper, substantially as shown, as thereby when the wrapper is applied to the bundle C the part B is caused to wind around the bundle, and thus to serve, also, as an auxiliary to the wrapper, as a 70 means for inclosing the bundle, and as a The improvement is more fully carried out | means for strengthening the wrapper. A lighter paper with the part B thus arranged may suffice for the wrapper. For some of the purposes herein named it is not essential that 75 an end of the cord, &c., shall project from the wrapper.

I claim—

1. A wrapper provided with a flexible tearing device secured diagonally thereto, where- 80 by the tearing device will encompass the article in a spiral manner, substantially as set forth.

2. A wrapper provided with a cord secured diagonally to one side thereof, said cord be- 85 ing upon the inside of the wrapper and encompassing the article in a spiral manner when in place upon an article, substantially as set forth.

3. A wrapper provided with an adhesive 90 substance across one end and provided with a cord secured diagonally across the inner surface of the wrapper, one end of the cord projecting beyond the edge of the wrapper adjacent to the adhesive substance, substan- 95 tially as set forth.

Witness my hand this 11th day of December, 1891.

JOHN J. COCHRAN.

Witnesses:

C. D. Moody, A. BONVILLE.