



(No Model.)

2 Sheets—Sheet 1.

F. H. PARKER.  
COMBINED COTTON CHOPPER AND PLANTER.

No. 484,337.

Patented Oct. 11, 1892.



Witnesses:

*E. H. Hurdman*  
*M. S. Duval*

Inventor

*Francis H. Parker*  
By *his* Attorneys,

*C. A. Snow & Co.*

(No Model.)



2 Sheets—Sheet 2.

F. H. PARKER.

## COMBINED COTTON CHOPPER AND PLANTER.

No. 484,337.

Patented Oct. 11, 1892.



Witnesses

Inventor

E. W. Lurman,  
W. S. Duval.

*Francis H. Parker.*

By *his* Attorneys,

Chas. Snow & Co.



# UNITED STATES PATENT OFFICE.

FRANCIS H. PARKER, OF GRAPELAND, TEXAS.

## COMBINED COTTON CHOPPER AND PLANTER.

SPECIFICATION forming part of Letters Patent No. 484,337, dated October 11, 1892.

Application filed October 21, 1891. Serial No. 409,381. (No model.)

*To all whom it may concern:*

Be it known that I, FRANCIS H. PARKER, a citizen of the United States, residing at Grape-land, in the county of Houston and State of Texas, have invented a new and useful Com-  
5 Combined Cotton Chopper and Planter, of which the following is a specification.

This invention relates to machines for chopping, cultivating, and planting cotton; and the objects in view are to provide a ma-  
10 chine of such construction as will be adapted to perform the above operations.

A further object of the invention is to provide a machine of cheap and simple construc-  
15 tion and readily convertible for the practice of its various functions.

Other objects and advantages of the inven-  
20 tion will appear in the following description, and the novel features thereof will be particularly pointed out in the claims.

Referring to the drawings, Figure 1 is a plan of a machine constructed in accordance with my invention. Fig. 2 is a vertical lon-  
25 gitudinal section. Fig. 3 is a transverse section, the hopper removed and taken through the space the hopper would, if present, occupy. Fig. 4 is a rear elevation.

Like numerals of reference indicate like parts in all the figures of the drawings.

30 1 designates the opposite longitudinal side bars of the frame, and journaled in the rear ends of the same is a transverse axle 2, upon the ends of which, outside of the side bars, ground-wheels 3 are rigidly mounted, where-  
35 by the axle and wheels rotate in unison.

4 designates a beam, provided with an open-  
40 ing 5 in its front end, which loosely receives a reduced cylindrical bearing 6, formed on the axle. To opposite sides of the beam, near its rear end, are secured a pair of plow-stand-  
ards 7, the lower ends of which support shov-  
els 8 and are provided with L-shaped fenders 9, through which, the shovels, and the stand-  
ards heel-bolts 10 are passed. Through the  
45 standards and beam an adjusting-rod 11 passes, and upon the same said standards may be adjusted through the medium of nuts 12, so that their distances apart may be varied. A similar rod 13 passes through the up-  
50 per ends of the standards above the beam, and through the medium of nuts 14 said rod

may be adjusted to give the standards a proper space. Upon this rod handles 15 are mounted, the lower ends of the handles being loosely connected with the opposite sides of  
55 the beam.

In a pair of cross-bars 16, secured to the under side of the opposite side bars 1, bear-  
ings 17 are formed, and mounted for rotation in the bearings and removable therefrom is a  
60 chopping-shaft 18. This shaft extends at its rear end beyond the rear bar and engages loosely with a socket 19, formed in the front end of the beam 4, and carries in front of  
65 said end a beveled gear 20. The teeth of the gear are engaged and operated by teeth formed upon one side of a pulley 21, which is rigidly mounted upon and moves with the axle, so  
70 that the rotation of the axle is imparted by the two gears to the chopping-shaft. The chopping-shaft is rectangular in cross-section and has mounted thereon one or a pair of  
choppers 22<sup>a</sup>. These choppers have their han-  
dles or shanks provided with square slots 23,  
75 which receive the shaft 18, and are secured in position upon the shaft by bolts 25, which  
pass through perforations in the shanks and serve to adjust the choppers upon the shaft.

26 designates a hopper that is removably  
80 mounted in position upon the framework and between the transverse bars 16. The hopper has journaled in its opposite side walls an agitator-shaft 27, the ends of the shaft being removably journaled in boxes 28, located upon  
85 the upper sides of the bars 1. Within the hopper the shaft is provided with agitating-fingers, while outside of the same, and between it and one of the bars 1, the shaft carries a pulley 29, which is connected by the  
90 endless belt 30 with the pulley 21.

In the front ends of the side bars 1 a trans-  
verse bar 31 is mounted, the same having its ends tenoned to fit mortises formed in the bars  
1. The draft-pole 32 is passed through the bar  
31 and into the bar 16, and is thus held rigid.  
95

33 designates a front plow-standard carry-  
ing a shovel 34 at its lower end for opening a furrow. The standard 33 has one of its sides  
recessed, as at 35, and receives that portion of  
the draft-beam that lies between the trans-  
verse bars 31 and 16, and through the draft-  
100 beam and standard a pin 36 is passed.



To the under side of the transverse bar 16, at opposite sides of the center thereof, guiding-arms 38 are secured and the same at their free ends project in front of the machine.

5 In operation the machine may be used either as a planter or as a cotton chopper and scraper. When used as a planter, the fenders to the rear shovels, which then serve as covering-shovels, are removed, as are also the chop-  
10 pers or hoes, and as the machine progresses the front shovel opens the furrow, while the seed is dropped in the usual manner from the hopper and covered by the covering-shovels following thereafter. When, however, the ma-  
15 chine is used as a combined chopper and scraper, the hopper is removed, as is also the front furrow-opening standard, and as the machine progresses the hoes, which have been previously adjusted, are successively and intermit-  
20 tingly brought in contact with the row of cotton, so that the stands are formed, and the fenders being at the sides of the covering-shovels prevent the shovels from throwing dirt upon the young plants and simply scrape along the  
25 edges of the furrow which they straddle. By extending the rear end of the shaft 18 into the socket at the front end of the beam 4 the said shaft is greatly strengthened, and, furthermore, where it is not desired to dirt up  
30 the rows, the cultivators being removed, the beam 4, when depressed at its rear end by a manipulation of the handles, will serve to raise the hoes over large stones, stumps, and other obstructions.

35 From the foregoing description it will be seen that I have provided in a single machine one calculated to perform the functions of a planter and a combined cotton-chopper and scraper, and that by such combination neither  
40 is lessened in its operativeness. The machine is simple in its construction and may be readily converted to its different forms without the employment of any special hand-tools or skilled labor.

Having described my invention, what I 45 claim is—

1. In a machine of the class described, the combination, with the opposite side bars, of the wheel-carrying axle journaled therein, having a bearing portion near its center, a master- 50 pulley mounted on the axle and adapted to turn therewith, the rearwardly-extending beam having an opening for the reception of the axle and at its front end a socket, the opposite plow-standards secured to the sides of 55 the beam; the rotatable chopping-shaft journaled in the framework and having its rear end terminating in the socket of the beam, the chopping-hoes mounted upon the shaft, and the gear mounted on the shaft and en- 60 gaging the teeth of the main pulley, substantially as specified.

2. In a machine of the class described, the combination, with the framework and a loosely-pivoted beam at the rear end of the same, 65 terminating in handles and provided at its front end with a socket, of the rotatable hoe-carrying chopper-shaft rotatably and loosely connected at its front end to the framework, and having its rear end terminating in the 70 socket of the beam, substantially as specified.

3. In a machine of the class described, the combination, with the framework, the loosely-fulcrumed beam, and the handles at the rear end of the same, of the rotatable chopping- 75 shaft, choppers mounted thereon, said shaft being pivotally journaled at its front end, and loose connections between the rear end of the same and the front end of the beam, substantially as specified. 80

In testimony that I claim the foregoing as my own I have hereto affixed my signature in the presence of two witnesses.

FRANCIS H. PARKER.

Witnesses:

J. L. BROWNING,  
J. E. BEAN.