


3 Sheets—Sheet 1.

No. 487,750.

Patented Dec. 13, 1892.



Witnesses;

*Inventor,*

G. B. Hope.  
 Jas. L. Condon

W. P. Kimbrell,

By - Nigam & Nigam  
Attys.

(No Model.)

3 Sheets—Sheet 2.

W. P. KIMBRELL.  
WINDMILL.

No. 487,750.

Patented Dec. 13, 1892.

Fig. 2.




Fig. 4.





Fig. 7

Witnesses:  
*G. S. Hodge*  
*John L. Condon*

Inventor,  
*W. P. Kimbrell*  
By *H. H. Hagan & H. H. Hagan*  
attys:


(No Model.)

3 Sheets—Sheet 3.

W. P. KIMBRELL.  
WINDMILL.

No. 487,750.

Patented Dec. 13, 1892.



Witnesses:

*W. P. Kimbrell*  
*John L. Condon*

Inventor:

*W. P. Kimbrell*

By *Hyman & Lipman*  
attys:

# UNITED STATES PATENT OFFICE.

WILLIAM P. KIMBRELL, OF BEAVER CITY, NEBRASKA.

## WINDMILL.

SPECIFICATION forming part of Letters Patent No. 487,750, dated December 13, 1892.

Application filed December 7, 1891. Serial No. 414,217. (No model.)

### *To all whom it may concern:*

Be it known that I, WILLIAM P. KIMBRELL, of Beaver City, Furnas county, Nebraska, have invented certain new and useful Improvements in Windmills, of which the following is a full, clear, and exact description, reference being had to the accompanying drawings, forming a part hereof.

My invention relates to that class of machines which are designed to utilize the force or power of atmospheric currents for operating pumps and various other types of machinery; and its objects are to produce a windmill which shall be, simple, durable, and inexpensive and also very light in construction and which shall be entirely uniform and automatic in its operation, and, furthermore, the parts of which can be readily connected together and disconnected from each other whenever necessary in setting up, taking down, or shipping the machine.

A still further object of my invention is to produce a windmill the wheel of which can be quickly and easily turned whenever necessary and to provide means for quickly and easily throwing the windmill into and out of action, as required.

To the above purposes my invention consists in certain peculiar and novel features of construction and arrangement, as hereinafter described and claimed.

In order that my invention may be fully understood, I will proceed to describe it with reference to the accompanying drawings, in which—

Figure 1 is a front elevation of a windmill constructed in accordance with my invention, the vanes being set open, so as to stop the rotation of the wind-wheel. Fig. 2 is a transverse vertical section of the same on the line 2 2 of Fig. 1. Fig. 3 is a horizontal cross-section of the same on the line 3 3 of Fig. 1, the vanes being, however, set in their normal oblique operative positions. Fig. 4 is a transverse vertical section of the same on the line 4 4 of Fig. 3. Fig. 5 is a perspective view of the central portion of the wind-wheel and its immediate operate connections, the vanes of the wheel being in this figure also set in their normal oblique operative positions. Fig. 6 is a transverse sectional view of the hub and two of the opposite spokes of the wind-wheel

on the line 6 6 of Fig. 1. Fig. 7 is a transverse sectional view of the rim and an outer end of one of the spokes of the wind-wheel on the line 7 7 of Fig. 1. Fig. 8 is a perspective view of the upper parts of the tower-uprights and the annular cap supported thereby. Fig. 9 is a view, partly in side elevation and partly in central transverse vertical section, of the upper parts of the lower uprights and the cap and head.

In the drawings, 1 designates four uprights, which constitute the principal supports of the framework or tower of the windmill, the said supports being of any desired length to accord with the required elevation of the wind-wheel. These uprights converge upwardly and are braced together by any suitable number of horizontal cross-braces 2 and also by any suitable number of interposed oblique braces 3, which are arranged in X form. Upon the upper ends of these supports 1 is supported an annular cap 4, which is preferably in the form of a metal casting and which is provided with a short pendent cylindrical flange 5, which is also preferably in the form of a metal casting integral with the cap 4 just described. Upon its outer sides this flange is formed with four pairs of vertical ribs 6, each pair of said ribs thus inclosing a vertical space which constitutes a socket for the reception of the upper end of one of the uprights 1. These uprights are retained in said sockets by any suitable number of through-bolts 7, which pass transversely through the upper ends of the uprights 1 and also similarly through the two companion ribs 6.

8 designates a vertical cylinder, which is also preferably in the form of a metal casting and which extends downward within the short cylinder 5 and which is also of such length as to extend above the annular cap 4, as is clearly shown in Figs. 2, 4, and 9. The upper portion of this cylinder is surrounded by a horizontal head 9, which rests directly upon the annular cap 4 and turns horizontally thereon, the said head being preferably also in the form of a metal casting, but being permissibly of wood or other suitable material, and said cylinder is secured to the head by any number of bolts 11, which are passed horizontally through the upper part of the cylinder and likewise through the body of the head, as

shown. Upon the upper side of this head 9 are secured two oppositely-disposed vertical standards or pillow-blocks 12, upon the upper sides of which are secured two journal-bearings 13 for the main shaft 14 of the wind-wheel.

From the lower end of the cylinder 8 depend two lugs or ears 15, transversely through which extend two bolts or similar stub-axles 16. Upon the inner ends of these bolts or stub-axles are mounted rollers 17, the peripheries of which come into contact with the under or lower end of the cylinder 8. The purpose of these rollers will be more clearly understood from the ensuing description of the wind-wheel itself; but it is to be understood that said rollers counteract the friction which might result from uneven balancing of the parts connected to the main shaft 14, which might otherwise cause the cylinder 8 to bind within the flange 5. The main shaft 14 of the windmill is prevented from longitudinal movement (while yet being permitted to freely rotate) by two collars 18, which embrace opposite sides of the rear bearing 13.

Upon the shaft 14, at a point midway between the bearings 13, is secured an eccentric 19, which is surrounded by the usual divided eccentric-strap, 20.

To the eccentric-strap 20 is connected, either by an eye 22 or in other suitable manner, the main operating-rod 21 of the windmill, said rod extending downward and having its lower end bifurcated, preferably, as at 23, to embrace the rod 24 of a suitable pump 25. It is to be understood, of course, that I propose to connect the windmill either to any type of pump or to any other machine or machinery capable of being driven by a windmill, and it will therefore be seen that the precise described form of connection at the lower end of the rod 21 may be varied, as circumstances may suggest. The main shaft 14 of the windmill is extended rearwardly as far as desired, and at its rear end or portion said shaft carries a balance-wheel 26, the arrangement being such that the extended portion of the main shaft and its balance-wheel shall about counterbalance the front portion of the main shaft and the wind-wheel mounted thereon in order to reduce the friction between the pendant flange 5 and the cylinder 8 to the minimum. This balance-wheel 27 is provided near its periphery with a counterweight or enlargement 27, which extends precisely opposite from the outer end of the longer axis of the eccentric 19, as is clearly shown in Fig. 2. Thus the counterweight or the enlargement 27 of the wheel 26 counterbalances the eccentric and renders it impossible for the windmill to stop on a dead-center.

The wind-wheel itself is constructed as follows:

28 designates the hub of the wheel, which is preferably in the form of a solid metal casting of disk-like form and having its front side formed with a forwardly-projecting extension

29 of less diameter than the hub itself. The front end of the main shaft 14 passes entirely through the hub and its extension, and said hub is retained removably upon the shaft by a set-bolt 30, which extends radially through the extension 29 and impinges upon the shaft, or by equivalent means, such as a key.

31 designates the rim of the wind-wheel, the said rim being in the form of a broad circular band which is of suitable diameter and which is preferably of thin steel, so as to combine the maximum degrees of strength with lightness.

Between the rim and the hub of the wind-wheel is interposed a circular band 32, which is also of metal and which is of much less width and diameter than the rim 31, while of considerably-greater diameter than the hub 28, as indicated in the drawings.

33 designates the spokes of the wheel, the said spokes being preferably of hollow tubular material—such as gas-pipe—and having their inner ends 34 externally screw-threaded to enter correspondingly internally-screw-threaded radial sockets 35 in the hub 28. (See Fig. 6.) These spokes extend radially outward from the hub 28, and their outer extremities pass through the rim 31 and also through a circular strengthening-rib 36, which is formed upon or suitably secured to the inner surface of the rim 31 midway of its width. The outer extremities of these spokes are internally screw-threaded for a suitable distance, as shown at 37, (see Fig. 7,) and into these ends of the spokes are inserted the externally-screw-threaded stems of a corresponding number of the set-bolts 38, the heads 39 of said bolts abutting against the outer surface of the rim. It will thus be seen that by turning the set-bolts 38 in one or the opposite direction the rim 31 can be readily and effectually trued whenever for any cause it has sprung out of the true, or, in other words, out of exact concentric position relative to the hub 28. It is to be observed that these spokes 33 also pass through the intermediate band 32 and that between each two adjacent spokes 33 is interposed a radial arm 40. These radial arms are of similar hollow character to the spokes 33, and their outer ends are secured to the rim 31 in the same manner—that is, by set-bolts like the set-bolts 38—as are the outer ends of the spokes 33; but the arms 40 are of less length than the spokes 33, so that the inner ends of said arms merely pass through the band 32 and are secured in position by nuts 41, which are screwed upon the inner ends of the arms 40 and which abut against the inner surface of the band 32. Upon these arms 40 and the outer portions of the spokes 33 are pivotally mounted the wind-wheel vanes 42, each of which is of substantially-triangular form and of such length as to extend from the inner surface of the rim 31 to the outer surface of the band 32. These vanes are preferably in the form of steel plates, each of which is provided with a

longitudinal central strengthening-rib 43, formed upon or suitably secured to one side of the vane, and the outer and inner ends of which are turned at right angles to form  
 5 flanges 44, through which extend the spokes 33, so that said vanes can be turned pivotally upon said arms and spokes. The inner ends of the vanes 42 are also turned outwardly, as shown at 45, and to each of these out-  
 10 wardly-turned portions is connected, by a pivot 46, the front end of a link 47, to be hereinafter more fully described.

Upon the front portion of the main shaft 14, just back of the hub 28, is mounted a  
 15 sleeve 48, which is preferably in the form of a single disk-like metal casting and which is arranged to rotate with and also to slide longitudinally upon said main shaft.

Immediately surrounding and concentric  
 20 with the hub 48 is a band 49, which is similar in respect to material, width, and diameter to the band 32, above described, and which is connected to said hub by a number of radial arms 50. These arms 50 are preferably of hol-  
 25 low tubular form, similarly as are the arms 40 and the spokes 33, and the inner ends of said arms 50 are screwed into radial sockets in the margin of said sleeve, while the outer ends of said arms are riveted or otherwise secured to  
 30 the band 49. The rear ends of the links 47 are secured to the band 49 by rivets 51 or equivalent means.

Upon the front side of the front standard or pillow-block 12 is bolted a standard or ver-  
 35 tical bracket 52, while upon the rear side of the rear standard or pillow-block is bolted or otherwise secured a second vertical standard 53, bolts 54 serving as the means for thus se-  
 40 curing said standards or brackets to the standards or pillow-block, and said vertical standards or brackets being of such length as to extend downward along the sides of the head 9, as well as those of the pillow-block, and the  
 45 bolts 54 and the standards 52 and 53 serving, therefore, to assist in securing the pillow-blocks to the head. The upper part of the standard 53 is, moreover, of U form trans-  
 50 versely, and its sides are formed at their lower ends with oppositely and outwardly extending flanges 55, which are secured to the upper side of the corresponding pillow-block by bolts 56. At its rear side the sleeve 48 is formed  
 55 with an integral externally-grooved extension 57, in which works loosely a ring 58, said ring being embraced by a bifurcated arm or fork 59, the ends of which are pivotally connected, as at 61, to the ring. The fork 59 is formed  
 60 upon or secured to the lower end of the vertical front arm of an L-shaped bar 60, the upper arm of which extends rearwardly and hori-  
 65 zontally through the upper ends of the brackets 52 and 53, so as to be movable longitudinally therein. The rear end of this arm projects considerably beyond the rear bracket 53 and is surrounded by a spiral spring 62, which is confined between the rear side of the rear bracket 53 and a cross-pin 63 or a suitable

head, which is carried by the rear extremity of the arm. It is to be understood that the  
 spring 62 is an expansively-acting spring, its  
 70 expansion tending to draw the bar 60 rearward and through the described connections to retain the vanes in closed position. It will thus be seen that any increased wind-pressure will cause the vanes to open, compressing the  
 75 spring, and that any diminution of the wind-pressure will permit the spring to expand and thus correspondingly move the vanes more or less toward their closed position. Hence it  
 80 will be understood that the wheel is automatic or self-governing in its action by virtue of the spring 62 and that consequently it will maintain a uniform rotative movement under widely-varying conditions of wind-pressure without racing and will, if subjected to ex-  
 85 cessive wind-pressure, automatically stop its rotation.

In order to provide for the voluntary stop-  
 ping of the wheel when desired, a bell-crank lever 64 is pivoted, as at 65, upon the upper  
 90 part of the rear bracket 53, and to the upper end of this lever is pivotally connected the rear end of a link 65, the front end of which is pivoted, as at 66, to the bar 60 at a point about midway between the brackets 52 and 53.  
 95

To the outer end of the lower arm of the bell-crank lever 64 is connected the upper  
 end of a rod 67<sup>a</sup>, to the lower end of which is also connected a cord 67, the lower end of  
 said cord extending within convenient reach  
 100 of a person standing upon the ground. It will thus be seen that by pulling downward upon the rod or cord 67 the bar 60 will be moved forward longitudinally, compressing  
 the spring 62, and thus throwing the vanes  
 105 into open position and stopping the revolution of the wind-wheel. The lower end of the rod or cord 67 is shown as provided with a loop 68, which is to be engaged with a suit-  
 110 able peg or pin to retain the wheel in inoperative position as long as desired.

In order to lessen the friction resulting from the horizontal movement of the head 9 as the wind-wheel turns into and out of the wind,  
 four or more or less rollers 69 are journaled  
 115 in the under side of the head 9, as shown, and travel upon the circular casting 4 in the top of the windmill-tower.

From the above description it will be seen  
 that I have produced a windmill which is of  
 120 simple, durable, and inexpensive construction, effective and automatic in its operation, and easily managed by an attendant.

Having thus described my invention, what I claim as new therein, and desire to secure  
 125 by Letters Patent, is—

A windmill comprising a wind-wheel hav-  
 ing a central hub, a circular rim concentric  
 with the hub, and a circular band interme-  
 130 diate of the hub and rim and concentric therewith, a number of shorter hollow radial spokes interposed between the rim and band and internally screw-threaded at their inner and  
 outer ends, a number of bolts having exter-

nally-screw-threaded stems and inserted  
through the rim and band and also into the  
inner and outer ends of the spokes, a number  
of longer radial spokes interposed between the  
5 shorter spokes and having externally-screw-  
threaded inner ends to enter the hub and  
passing through the band and rim and also  
externally screw-threaded at their outer ends,  
a number of bolts having externally-screw-  
10 threaded stems and passing through the rim  
and into the outer ends of the longer spokes,

and a number of radial and triangular vanes  
pivotaly connected to the longer and shorter  
spokes and interposed between the band and  
rim, substantially as set forth. 15

In testimony whereof I affix my signature in  
the presence of two witnesses.

WILLIAM P. KIMBRELL.

Witnesses:

JAMES BURCHARD,  
FRED. H. BROWN.