

(No Model.)

## T. J. KELLEY. PORTABLE HAY OR GRAIN SHED.

No. 487,927.

Patented Dec. 13, 1892.





Witnesses H. N. Jenkins

Inventor Ihomas J. Kelley By Attorney Eugene Ayres

## United States Patent Office.

THOMAS J. KELLEY, OF AVENUE CITY, MISSOURI.

## PORTABLE HAY OR GRAIN SHED.

SPECIFICATION forming part of Letters Patent No. 487,927, dated December 13, 1892.

Application filed June 20, 1892. Serial No. 437,415. (No model.)

To all whom it may concern:

Be it known that I, THOMAS J. KELLEY, a citizen of the United States, residing at Avenue City, in the county of Andrew and State 5 of Missouri, have invented certain new and useful Improvements in Portable or Knockdown Hay and Grain Sheds; and I do declare the following to be a full, clear, and exact description of the invention, such as will enable to others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

The object of my improvements is to provide a cheap, easily-constructed, and strong portable device for protecting hay or grain in stack or rick. It may also be used to advantage while the hay or grain is on a wagon 20 when a storm approaches suddenly; also, as a temporary shed for a variety of purposes. I attain these objects by the mechanism illustrated in the accompanying drawings, in which-

Figure 1 is a perspective view of my improved hay and grain shed. Fig. 2 shows the roof as it appears when closed. Fig. 3 is one of four tie-bars used in each frame. Fig. 4 is one of the four corner-posts of the shed.

Similar letters refer to similar parts through-

out the several views.

In the construction of my device the rafters A B and C D are hinged at top joint, as shown at EF. Stirrups H are secured to the lower 35 ends of the rafters for engaging the upper ends of the corner-posts I I I I. The tie-bars K (shown in detail at Fig. 3) are provided with stirrups b at each end thereof for slipping over the posts I. These bars are pre-40 vented from working or sliding down to the ground by pins in posts I, as shown at M M !

M M, and the roof is securely protected from being lifted by cyclones or high winds by pins O O O in posts I. The roof-boards are made to overlap and project over each end of 45 the shed. They are secured to the rafters by nails, screws, or pins, as shown at P. Provision being made for the insertion of pins at several corresponding points in upper ends of posts, the roof may be adjusted to height 50 desired.

The device is preferably constructed of lumber, and of any length, width, and height desired, the stirrups only being of metal.

It will be seen from the foregoing descrip- 55 tion that by simply withdrawing the pins the structure can be easily and quickly taken apart, transported from place to place, and easily again set up.

What I claim, and desire to secure by Let- 60

ters Patent, is—

1. A portable structure consisting of a hinged folding roof with rafters having stirrups at lower ends for engaging four vertical posts and four tie-bars with similar stirrups to 65 engage posts, and pins to hold stirrups in place and for the purpose of adjusting height of roof, substantially as described, and for the purposes specified.

2. A portable frame structure with folding 70 roof having hinged rafters with stirrups at lower ends engaging upper ends of vertical posts, and horizontal tie-bars having stirrups also engaging posts, with pins for holding tiebars and roof in place and adjusting height of 75

roof, substantially as described.

In testimony whereof I affix my signature in presence of two witnesses.

THOMAS J. KELLEY.

Witnesses:

EUGENE B. AYRES, EMMA HECKEL.