


(No Model.)

M. BADONI.
BOX FASTENER.

No. 493,203.

Patented Mar. 7, 1893.



Witness
Chas. H. Smith
J. Staib

Fig. 3

Inventor
M. Badoni
per Lemuel W. Serrell
Att'y

UNITED STATES PATENT OFFICE.

MASSIMILIANO BADONI, OF GENEVA, SWITZERLAND, ASSIGNOR TO ALOYS
REVILLIOD DE MURALT, OF SAME PLACE.

BOX-FASTENER.

SPECIFICATION forming part of Letters Patent No. 493,203, dated March 7, 1893.

Application filed June 20, 1892. Serial No. 437,412. (No model.)

To all whom it may concern:

Be it known that I, MASSIMILIANO BADONI, mechanician, of Geneva, Switzerland, have invented certain new and useful Improvements
5 in Spring-Clasp Devices for Caskets, Jewel-Boxes, and Similar Articles, of which the following is a specification.

This invention consists of a simple and cheap spring clasp for caskets, jewel boxes
10 and the like.

In the accompanying drawings I have shown how my said invention may be conveniently and advantageously carried into practice.

Figure 1 is a cross section of part of a casket
15 and its cover provided with my improved spring clasp showing the said cover partly shut. Fig. 2 is a similar section of the said casket showing the cover shut. Fig. 3 is a section on the line xy of Fig. 2. Fig. 4 is a
20 perspective view of a half open casket provided with the improved clasp. Fig. 5 is a similar view of the same when shut. Figs. 6 to 10 inclusive show details of the different parts of the device detached.

25 Similar letters of reference indicate corresponding parts in the several figures of the drawings.

The clasp proper is formed as a spring as shown in Figs. 6 and 8 and consists of a foot-
30 piece A' intended to be fixed to the box or casket, a spring portion or blade A^2 of suitable elasticity, a V-shaped part $A^3 A^4$, the portion A^4 of which is provided with a hole a having sharp edges a' and a^2 ; and a finger
35 piece A^5 at the end to project out of the box or casket and to be acted upon by hand when the cover is to be opened. The hole or mortise a of said clasp A may be square, round, elliptical or of any other suitable form, the
40 edges of said hole being left sharp, as shown at $a' a^2$, so as to firmly grasp the pin B. The said pin may be cylindrical, square or of other

shape and is fixed to the casket D when the clasp A is fixed to the cover E and vice versa. The said pin B may consist of a simple nail or
45 screw and the clasp A is suitably formed and fixed to the cover E (or box D) so as to engage with its hole a over the said pin B, as shown in Figs. 1, 2 and 3 when the cover E is shut. The sharp edges a' , a^2 of the hole a
50 grip the pin B and the clasp A being pressed toward said pin B so as to produce such gripping (see Fig. 2) the cover E will be firmly closed. Any attempt to open the cover will
55 produce a pressure upon the spring clasp A in the direction of the arrow 1 (Fig. 2) and this pressure will augment the gripping action of the clasp A on the pin B.

To open the casket or box it is only necessary to press the end of the clasp A in the di-
60 rection indicated by the arrow 2 in Fig. 2, this pressure disengaging the said clasp A from the pin B. The pin or stop C is intended to limit the down-stroke of the clasp A.

Having thus fully described my invention,
65 I claim—

A fastening device for boxes, composed of a pin and a spring blade rigidly attached at one end and having a finger piece or lifter at the other end, and a V shaped bend adjacent
70 to the finger piece, there being a mortise through one part of the bend to receive the stationary pin, whereby the edges of the metal at the mortise engage the pin for holding the lid in position, or such edges are released
75 when the finger piece is lifted, substantially as set forth.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

MASSIMILIANO BADONI.

Witnesses:

E. IMER-SCHNEIDER,
A. REVILLIOD DE MURALT.