






(Model.)

L. SCHEIMBERG.
COAT.

No. 497,928.

Patented May 23, 1893.



Attest:
H. Schott
A. J. Birney

Inventor
L. Scheimberg
by: W. H. Engle
Att'y.

UNITED STATES PATENT OFFICE.

LOUIS SCHEIMBERG, OF NEW YORK, N. Y.

COAT.

SPECIFICATION forming part of Letters Patent No. 497,928, dated May 23, 1893.

Application filed May 25, 1892. Serial No. 434,335. (Model.)

To all whom it may concern:

Be it known that I, LOUIS SCHEIMBERG, a citizen of the United States, residing at the city of New York, county and State of New York, have invented a new and useful Improvement in Coats, of which the following is a specification.

My invention relates to an improved-combined coat and shawl.

10 The object of my invention is to produce a garment which may be quickly arranged to fit any size of person, within the usual limits, and which may be hastily put on in case of fire to protect the wearer from the flames and
15 smoke.

Another object of my invention is to provide means for allowing the wearer of my improved garment to safely carry a child out from a burning building.

20 With these objects in view my invention consists of such a combination of parts and details of construction as will be fully described in connection with the accompanying drawings, and then pointed out in the claims.

25 In the drawings—Figure 1 is a side view of my improved garment as it appears when in use. Fig. 2 is a view of the back of the same garment extended. Fig. 3 is a detail view of the skirt-flaps. Fig. 4 shows the manner of
30 attaching the skirt-flaps to the coat. Fig. 5 is a front view of the garment.

Referring to the drawings, A is a coat constructed with a pair of folds, *a*, extending toward the center of the back of the coat, the
35 amount of cloth folded in being regulated to suit the size of the wearer by means of a strap, B, provided with a series of button-holes, *b*, arranged to receive the buttons, *b'*, one secured to each fold.

40 C are sleeves constructed in the usual manner, and arranged to have the cuffs, *c*, tucked up or not, as may be necessary in fitting the garment to the wearer.

45 D is a hood secured to the shoulder and back of the coat along the line, *d*, being made large enough so that when turned up over the head it will completely cover the face of the wearer, except on a line with the eyes, where it is open, as at *e*, being also provided with a
50 peak or visor, *d'*, above the opening. The hood may be fastened by buttons, *e'*, as shown

in Fig. 2 or buckles, catches, pins, or other fastening devices may be used.

A cord or strap, F, passing through a tube, *f*, and loops, *f'*, secured to the back of the
55 coat serves to draw the garment tightly about the neck of the wearer.

G is a skirt-flap having four buttons, *g*, near its upper edge, one at one end and three
60 in a row near the other end.

G' is another skirt-flap having two buttons, *g'*, and two button-holes, *g''*, by means of which the flap, G', may be buttoned to the flap, G.

H is a skirt-lining secured along its upper
65 edge to the inside of the skirt of the coat and provided with a series of horizontal rows of button-holes, *h*, into which may be inserted the buttons on the skirt-flaps, G, G'. By having a series of rows of button-holes, as de-
70 scribed, the skirt-flaps may be buttoned either to the upper, lower, or intermediate horizontal row of button-holes, thus exposing more or less of the skirt-flaps below the bottom edge
75 of the coat and enabling the coat to be adjusted to any length as may be necessary to make it fit the wearer.

K is a shawl buttoned to the coat by one row of buttons, *k*, and arranged to be folded inwardly and held against the breast of the
80 coat by a second row of buttons, *k'*, secured to the outside of the shawl on the part that is folded inward, these buttons, *k'*, being arranged to enter button-holes, *k''*, in the edge
85 of the coat. This shawl may be used to wrap around a child and permit the wearer of the coat to carry it through the flames and smoke with safety.

L are slipper pockets which are constructed with a space above and below the pocket-
90 opening, *l*, as clearly shown in dotted lines, by which construction a pair of slippers, if inserted in the pockets, cannot work upward and out.

The manner of using my improved garment
95 is so obvious from what has been said as to need no further description.

Having thus fully described my invention, what I claim as new, and desire to secure by
100 Letters Patent, is—

1. As an article of manufacture, a coat having a skirt-lining, a pair of skirt-flaps, and

means for securing the flaps to the lining at varying heights, whereby the skirt-flaps may be adjusted to shorten or lengthen the coat, substantially as set forth.

5 2. As an article of manufacture, a coat having a skirt-lining provided with a series of horizontal rows of button-holes and a pair of skirt-flaps each provided with a series of buttons for engagement with any desired row of
10 button-holes in the skirt-lining, whereby the length of the coat may be adjusted, substantially as set forth.

3. In a garment, the combination, with a coat, of a shawl-device secured to the coat
15 near one of its front edges and arranged to be

folded up, and means for securing the shawl to the coat in its folded position, substantially as described and for the purpose set forth.

4. In a garment, the combination, with a coat having a series of button-holes, of a shawl device secured to the coat near one of its front edges and arranged to be folded within itself, and a series of buttons secured to the outside of the shawl for engagement with the button-holes in the coat, substantially
25 as described and for the purpose set forth.

LOUIS SCHEIMBERG.

Witnesses:

GREGORY WEINSTEIN,
WILLIAM LARKINS.