(No Model.)

P. G. H. DOP.

PROTECTIVE COVERING FOR THE SEATS OF WATER CLOSETS.

No. 498,159.

Patented May 23, 1893.





Fig. 2.



United States Patent Office.

PHILIP GERHARD HENDRIK DOP, OF UTRECHT, NETHERLANDS.

PROTECTIVE COVERING FOR THE SEATS OF WATER-CLOSETS,

SPECIFICATION forming part of Letters Patent No. 498,159, dated May 23, 1893.

Application filed November 28, 1892. Serial No. 453, 405. (No model.)

To all whom it may concern:

Be it known that I, Philip Gerhard Hendrik Dop, a subject of the Queen of The Netherlands, residing at Utrecht, Holland, have inthe Seats of Water-Closets and the Like, of which the following is a specification.

This invention has reference to a simple and inexpensive protective covering for the 10 seats of water closets and the like. A protective covering for this purpose according to this invention consists of suitable sheet material such as paper formed with a hole or perforation to correspond with the hole in 15 the seat to which it is to be applied, and the edge portion of which is made of two or more thicknesses of material cut or slit in such a manner as to form a number of flaps each of which is opposite to the cut or slit between 20 two of the flaps of the adjacent sheet of material, the arrangement being such that when the covering is applied to a seat, the flap portions can be turned downward so as to completely cover the edge of the hole in the seat.

In the accompanying drawings:—Figure 1 is a plan, and Fig. 2 a cross section on the line A B Fig. 1, of a protective covering according to this invention.

This covering consists of a thin sheet 1 of 30 paper formed with a hole 2 therethrough of smaller size than the hole in the seat to which it is to be applied. To this sheet and around the hole therein is secured by suitable means such as gum or paste a second sheet or strip 35 3 of paper formed with a hole corresponding approximately with that in the sheet 1 so that around the edge of the hole in the combined sheets there will be two strips or layers of paper one of which, namely that forming 40 part of the sheet 1, is cut or slit as at 1a, while the other forming part of the sheet or strip 3, is similarly cut or slit as at 3a, the cuts or slits in the latter being out of line with those in the former. These cuts or slits serve to divide the material around the hole into two annular or approximately annular series of flaps, those in one series covering the cuts or slits between those in the other

series. By this means when the covering is

50 in use and the flaps are bent downward as

indicated in dotted lines, they will effectually and completely cover the edge 4 of the hole in the seat 5 to which the protective covering is applied.

My improved protective covering can be 55 treated with any suitable disinfectant, or perfume, and may advantageously be made of such a size that a portion thereof can when the covering is in use, hang over the front or outer edge of the seat to which it is applied 60 as indicated at 1^b in Fig. 2.

What I claim is—

1. A protective covering for the seats of water closets and the like, consisting of sheet material formed with a hole therethrough to 65 correspond with the hole in the seat to which said covering is to be applied and the edge of which is provided with a number of overlapping flaps or parts substantially as herein described for the purpose specified.

2. A protective covering for the seats of water closets and the like consisting of perforated sheet material made of two or more thicknesses around the hole therein, these thicknesses being slit or cut in such a man-75 ner as to form two or more series of flaps that extend completely around the edge of the hole, the flaps in one series being arranged to overlap those in the other series in a lateral direction substantially as herein described for 8c the purpose specified.

3. The improved protective covering for the seats of water closets and the like consisting of a sheet 1 of paper formed with a hole 2 the edge portion of which is slit or cut at a number of 85 points 1^a and a strip 3 of paper secured to the first sheet around the hole therein and formed with a number of slits or cuts 3^a arranged out of line with those in the said sheet 1 substantially as herein described for the purpose specified.

In testimony whereof I have signed my name to this specification in the presence of two subscribing witnesses.

PHILIP GERHARD HENDRIK DOP.

Witnesses:

F. O. HENNY,

Henerstraat, 12bis, Utrecht.

St. van Emmerik,

A B C Straat A, 29bis, Utrecht.