

(No Model.)

2 Sheets—Sheet 1.

W. P. WINNER.
HEATING FURNACE.

No. 501,034.

Patented July 4, 1893.

FIG. 1.





FIG. 4.



Witnesses:
H. D. Goodwin
William A. Penn.

Inventor:
William P. Winner
by his Attorneys
Hamm & Hamm

(No Model.)

2 Sheets—Sheet 2.

W. P. WINNER.
HEATING FURNACE.

No. 501,034.

Patented July 4, 1893.

FIG. 2.





FIG. 3.



Witnesses:

F. D. Goodwin
William A. Goss

Inventor:

William P. Winner
by his Attorneys
Hornum & Hornum

UNITED STATES PATENT OFFICE.

WILLIAM P. WINNER, OF QUAKERTOWN, PENNSYLVANIA, ASSIGNOR TO HIMSELF, WILLIAM P. ROBERTS, FRANK CAVANAUGH, OLIVER R. SCHEETZ, AND CHARLES A. KLUMP, OF SAME PLACE.

HEATING-FURNACE.

SPECIFICATION forming part of Letters Patent No. 501,034, dated July 4, 1893.

Application filed March 27, 1893. Serial No. 467,770. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM P. WINNER, a citizen of the United States, and a resident of Quakertown, Bucks county, Pennsylvania, have invented certain Improvements in Heating-Furnaces, of which the following is a specification.

The object of my invention is to so construct a hot air heating furnace that the products of combustion will pass away from the fire pot toward the front of the furnace and to the smoke flue in a circuitous path, heating the air more thoroughly than in the old method of allowing the products of combustion to pass away from the combustion chamber at the rear.

In the accompanying drawings:—Figure 1, is a view in elevation, partly in section, illustrating my improved hot air furnace. Fig. 2, is a section on the line 1—2, Fig. 1. Fig. 3, is a section on the line 3—4, Fig. 1; and Fig. 4, is a detached perspective view of the “crab” or flue section.

The furnace shown in the accompanying drawings is what is termed a portable heater, but it will be understood that my invention can be applied to brick set heaters as well.

A is the casing, B the fire pot section, D the flue section mounted upon the fire pot section, and mounted upon this flue section are the drums a , a' and a^2 , having suitable caps b and b' , so that the space c within the inner drum a and the space c' between the drums a' and a^2 connect directly with the combustion chamber d of the flue section, while the space e between the drums a and a' , and the space e' between the drum a^2 and the casing A are air spaces for the passage of the air to be heated.

The fire door opening d' is provided with a suitable door d^2 . This fire door opening communicates with the space c' through an opening d^3 in the top plate D' of the flue section. On each side of this fire door opening d' are extensions D^2 in which are formed flues or passages f communicating with the combustion chamber d , and in the top plate D' are openings f' which form a communication between the said flues f and the space c' . Thus it will be seen that there are three openings

into the space or passage c' for the products of combustion, all at the front of the furnace, and the flues f can be made of such a size that the products of combustion will readily pass into the space c' , so that the fire will not choke, and a better combustion will be effected.

The smoke flue g is formed in the rear of the flue section G, and can be made to communicate directly with the combustion chamber d on operating a damper g' , as clearly shown in Fig. 1, by turning the handle g^2 . This damper, however, is only turned down when the fire is being made or when it is wished to reduce considerably, the heat of the furnace, as the products of combustion will then pass directly out through the smoke flue, but when the damper is turned up all communication with the passage at the rear of the furnace is cut off except through the front flues f and d' .

In order to prevent the too rapid passage of the products of combustion through the smoke flue, I mount within the space c' on each side of the furnace, a deflecting plate c^2 , so that the products of combustion will have to pass as shown by the arrows in Fig. 1, in a circuitous path, thoroughly heating the drums a' and a^2 and consequently heating the air to a greater degree as it passes through the furnace. The top plate D' has an opening d^4 at the rear, which communicates with the flue g^2 formed in a tubular section mounted between the top plate and the flue section. This passage communicates with the smoke flue g .

The flue section D is preferably made of cast metal, the extensions D^2 being part of the structure, and are so formed that they receive the greater proportion of the products of combustion which is naturally carried away from the fire door, so that when the said door is opened there will not be an escape of gas; at the same time the advantage of a complete circulation is obtained.

The flue section D has a bottom plate D^3 and bolts extend from the top and bottom plate tying the structure together.

I claim as my invention—

1. The combination in a heating furnace, of

the fire pot, the flue section mounted above the fire pot, a smoke flue opening at the rear, a damper therefor, the fire door, extensions on each side of the fire door opening, flues
5 formed in said extensions, drums mounted above the flue section and forming a passage for the products of combustion, substantially as described.

2. The combination in a heating furnace of
10 the fire pot, the flue section mounted above the fire pot, fire door opening in the front of said section, extensions on each side of said opening, passages in said extensions communicating with the combustion chamber,
15 drums mounted above the flue section forming a passage for the products of combustion and communicating only with the passages at the front of the furnace, deflecting plates in said passage, and a passage at the rear
20 forming a communication between the space

between the drums and the smoke flue, substantially as described.

3. The combination in a heating furnace, of the fire pot section and drums, a flue section
25 mounted between the fire pot section and the drums, said flue section composed of three parts, a center piece in which the flues are formed, and top and bottom plates, with bolts securing the said parts together, each part
30 having side extensions at the front forming the flues between the combustion chamber and the space between the drums, substantially as described.

In testimony whereof I have signed my name to this specification in the presence of
35 two subscribing witnesses.

WILLIAM P. WINNER.

Witnesses:

WILLIAM D. CONNER,
JOSEPH H. KLEIN.