


(No Model.)

B. L. FLETCHER.
FIRE MAT.

No. 504,156.

Patented Aug. 29, 1893.



Witnesses,
J. Thomson Cross
E. A. Strehli

Inventor:
Benjamin L. Fletcher
for *John W. Trubli*
Attorney.

UNITED STATES PATENT OFFICE.

BENJAMIN L. FLETCHER, OF CINCINNATI, OHIO, ASSIGNOR TO THE FLETCHER
FIRE MAT COMPANY, OF NEWPORT, KENTUCKY.

FIRE-MAT.

SPECIFICATION forming part of Letters Patent No. 504,156, dated August 29, 1893.

Application filed January 11, 1893. Serial No. 458,016. (No model.)

To all whom it may concern:

Be it known that I, BENJAMIN L. FLETCHER, a citizen of the United States, residing at the city of Cincinnati, in Hamilton county and State of Ohio, have invented certain new and useful Improvements in Fire-Mats, of which the following is a specification.

My improved mat is simple in construction, cheap of manufacture and efficient in use. It is made of a non heat conducting substance such as asbestos covered on one or both sides by a heat conducting substance, such as sheet iron filled with small holes or slots.

In the accompanying drawings forming part of this specification Figure 1 is a view in elevation of my improved fire mat; Fig. 2 a central cross section of the mat shown in Fig. 1. Figs. 3 and 4 are central cross sections of fire mats showing modified forms of the mat.

The mat is preferably made annular in form. It is composed of an asbestos disk A, covered on one or both sides by a punctured metal disk B. The disks A and B. are firmly held together and in juxtaposition by a rim or band C.

D represents a ring attached to the rim C as shown, by which the mat can be taken off the stove or fire and hung up. This rim or band C. can be made separate or be a part of the disk as shown in the modified form in Fig. 3. In Fig. 4 two punctured disks are shown one on each side of the asbestos disk A held together by a rim C.

I prefer to make the mat as shown in Fig. 1. Any kind of non heat conducting substance may be used to form the disk A.

The mat is placed on the fire of a gasoline or gas stove or the holes of an ordinary stove or range, the perforated disk being placed next to the fire. The utensil holding the matter to be cooked or boiled is placed on the asbestos disk and the asbestos being a non conductor of heat only enough heat is transmitted to properly boil or cook the contents of the vessel or utensil resting upon the mat. Consequently it is not necessary to stir the contents to prevent burning. Burning is therefore prevented.

I can make the mat hexagon, rectangular, square, or in any other form or contour. I may use any kind of non-heat conducting substance.

The punctured disk may be attached to the asbestos in any desired manner.

What I claim as new and of my invention, and desire to secure by Letters Patent, is—

1. A fire mat composed of a disk of asbestos covered with a perforated disk of heat conducting substance as set forth.

2. In a fire mat, the combination of asbestos A, sheet metal B, rim C, the metal disk B, being perforated as shown and described.

BENJ. L. FLETCHER.

Attest:

ED. STREHLI,
W. T. JONES, Jr.