

(No Model.)

J. T. REED.
TAG ATTACHING IMPLEMENT.

No. 504,280.

Patented Aug. 29, 1893.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.





Fig. 5.



WITNESSES.

Geo. E. Truch.
Poland A. Fitzgerald.

INVENTOR-

J. I. Reed,
Lehman Patterson & Washburn
attys.

UNITED STATES PATENT OFFICE.

JAMES T. REED, OF CORRECTIONVILLE, IOWA.

TAG-ATTACHING IMPLEMENT.

SPECIFICATION forming part of Letters Patent No. 504,280, dated August 29, 1893.

Application filed December 13, 1892. Serial No. 455,058. (No model.)

To all whom it may concern:

Be it known that I, JAMES T. REED, of Correctionville, in the county of Woodbury and State of Iowa, have invented certain new and
5 useful Improvements in Tag-Attaching Implements; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it pertains to make
10 and use it, reference being had to the accompanying drawings, which form part of this specification.

My invention relates to an improvement in tag attaching implements; and it consists in
15 the novel combination and arrangement of parts which will be fully described hereinafter, and more particularly referred to in the claims.

The object of my invention is to provide
20 an improved implement for attaching tags to the ears of cattle for the purpose of marking them.

Referring to the accompanying drawings,—
25 Figure 1 is a perspective view of my improved implement when open. Fig. 2 is a front elevation of the same when closed. Figs. 3 and 4 are perspective views of the jaws detached. Fig. 5 is a detached view of the rivet splitting
30 knife.

A, designates the upper jaw of the implement and B, the lower jaw, the same being secured together in the usual manner by a rivet or pin C, acting as a pivot. The jaw B,
35 is formed with a depression D, so that in attaching the tag to the animal's ear in the manner presently to be explained the latter may be drawn into the implement by occupying this depression thus securing for the tag a firm hold on the thicker and more solid
40 portion of the ear and at a place where it will not be liable to tear out.

Secured to the under face of the jaw A, is the forked spring plate F, adapted to receive a rivet and hold the same with its head
45 clamped between the said plate and the jaw. As will be seen it may be easily slipped into place and the plate being formed of spring metal serves to hold it there.

The lower jaw B, is formed with a recess G,

at its center and secured to the surface of the
said jaw is the forked plate H, and on top of
this plate is the cap holding spring I, which
is adapted to hold the cap of the rivet as
shown so that when the latter approaches by
the contraction of the jaws it will enter the
said cap. The space between the forks of
plate H is wider than recess G, see Figs. 1
and 2, so that cap K rests directly on the upper
surface of jaw B, being held thereon from
lateral movement by the forks of plate H, and
confined thereon from vertical displacement
by plate I. The cap is thus fixedly held so
as to take the rivet E when brought thereto.

Within the recess G, is the removable knife
J against which the end of the rivet strikes
after passing through the cap K, splitting its
end so that when the implement is removed
the cap will be held in place and only a little
further flattening of the rivet will be required
to make the hold of the cap very secure.

When it is desired to place a tag the rivet
E, is put in position in the implement with a
tag penetrated or held in any suitable manner
thereby, after which the device is adjusted
to the ear to be tagged and the operation
completed as above described. If desired
the rivet head may be suitably marked
thus constituting it a distinguishing mark
and disposing entirely with the tag.

The implement is most simple in construction
and the splitting of the rivet end and
separating the split portions is of decided
advantage in that the tool may be removed
after placing the rivet without danger of the
latter dropping off before the permanent
clenching of the same is effected.

Having thus fully described my invention,
what I claim as new, and desire to secure by
Letters Patent, is—

1. An implement of the class described
comprising two pivotally connected jaws, the
lower jaw being formed with a recess in its
upper face, forked plate H secured to said
face with its forks arranged adjacent said recess,
the space between the forks being wider
than the recess for the purpose stated, a means
for holding a rivet cap located between said
forks from vertical displacement, a rivet split-

ting mechanism carried by the lower jaw, and a rivet carrying mechanism on the upper jaw, substantially as shown and described.

2. A tag attaching implement comprising
5 two jaws pivotally connected, one of which being adapted to carry a rivet, a forked plate secured to the other jaw for confining in place a rivet cap, cap holding spring I arranged over the forked plate, and a rivet splitting

mechanism, substantially as shown and described.

In testimony whereof I affix my signature in presence of two witnesses.

JAMES T. REED.

Witnesses:

LUKE HEATH,
BANCROFT ERWIN.