


(No Model.)


**J. A. GIBBONS.**  
**ADVERTISING DEVICE.**

No. 504,919.

Patented Sept. 12, 1893.



*Fig. 2*



*Fig. 1*

*Witnesses*

L. Edw. Maybee  
H. J. McMillan

*Inventor*

J. A. Gibbons  
by J. Donald C. Ridout & Co.  
attys



# UNITED STATES PATENT OFFICE.

JOHN A. GIBBONS, OF TORONTO, CANADA.

## ADVERTISING DEVICE.

SPECIFICATION forming part of Letters Patent No. 504,919, dated September 12, 1893.

Application filed May 6, 1893. Serial No. 474,168. (No model.)

*To all whom it may concern:*

Be it known that I, JOHN AUGUSTUS GIBBONS, of the city of Toronto, in the county of York and Province of Ontario, Canada, have  
5 invented a certain new and Improved Advertising Device, of which the following is a specification.

The object of the invention is to provide a device for advertising a specific article, and  
10 it consists, of a dummy representing the article being advertised, behind which dummy is placed a magazine or receptacle containing a number of articles with mechanism arranged to move the dummy and discharge a  
15 single article at a time, substantially as hereinafter more particularly explained and then definitely claimed.

In the accompanying drawings Figure 1, is a front view of my improved advertising device. Fig. 2, is a rear view of the same.

A, is a stiff plate of card-board or other suitable material on which is printed an advertisement of the article to be sold. This plate is intended to be placed on the counter  
25 or other suitable point, and is supported by a frame B, the bottom of which frame is preferably provided with rubber feet C, or in any other way to prevent it scratching the counter.

D, is a dummy representing a package of  
30 tooth-ache gum or other article advertised. This dummy is hinged in front of an opening E, made through the plate A, immediately at the bottom of a magazine or receptacle F, designed to contain a number of packages G,  
35 containing the tooth ache gum or other article. The dummy D, is pivoted at a, and has a crank extension H, formed on it. When the dummy is thrown open, as indicated in Fig. 1, the upper portion of the extension H,  
40 forms a bottom to the magazine F, and when the dummy is closed a portion of the extension H, nearest to the dummy forms a bottom which is lowered to a point opposite to the opening E. In opening the dummy D, the  
45 package lying on the portion of the extension H, nearest to it, is thrown forward in its position shown in Fig. 2, the other portion of the extension H being raised so as to act as a button to the magazine F, above the opening  
50 E, thus holding the bulk of the packages G,

above the opening E, so that only one package is thrown out at a time.

I, is a pivoted latch provided with a button J, and designed when in a vertical position to come in contact with a hasp K, extending  
55 from the tail L, formed on the back of the extension H, as indicated. When in this position, the dummy D, is held closed and cannot be removed until the clerk in charge of the device draws the latch I, clear of the hasp  
60 K, which action pulls upon the cord M, attached at one end to the latch I, and at the other end to the hasp K of the tail L, tilting the dummy D, on its pivot, thus throwing out the package lying on the extension H, as indicated in Fig. 1. The extension H, is either  
65 weighted or provided with a spring to throw it back and close the dummy D, immediately that the package is removed from it, which action brings the latch I, again into contact  
70 with the hasp K, thereby locking the dummy in a closed position. A bell N, is hung by a light spring O, on the extension H, so that any movement of the dummy will immediately be announced by the ringing of the bell.  
75 Several boxes P, of packages G, may be held onto the back of the plate A.

What I claim as my invention is—

1. A plate A, suitably supported on one edge and having an opening E, through it at  
80 the bottom of the magazine F, in combination with a dummy D, pivoted in front of the opening E, and provided with an extension H, forming a bottom for the magazine F, and mechanism for holding the dummy  
85 closed, substantially as and for the purpose specified.

2. A plate A, suitably supported on one edge and having an opening E, through it at  
90 the bottom of the magazine F, a dummy D, pivoted in front of the opening E, and provided with an extension H, forming a bottom for the magazine F, in combination with the hasp K on said extension H, a pivoted latch I, acting on said hasp K, and cord M, forming a connection between said latch I and extension H substantially as and for the purpose  
95 specified.

3. A plate A, suitably supported on one edge and having an opening E, through it at  
100

the bottom of the magazine F, a dummy D,  
pivoted in front of the opening E, and pro-  
vided with an extension H, forming a bottom  
for the magazine F, in combination with the  
5 hasp K on said extension H, a pivoted latch  
I, acting on said hasp K, cord M, forming  
connection between said latch I and exten-

sion H bell N, and spring J, substantially as  
and for the purpose specified.

Toronto, April 14, 1893.

JOHN A. GIBBONS.

In presence of—

A. M. NEFF,

J. EDW. MAYBEE.