
(No Model.)

H. I. BLITS.

HYGIENIC VAPOR AND HOT AIR RENOVATOR.

No. 510,235.

Patented Dec. 5, 1893.



J. M. Copenhaver.

_tuventor.

United States Patent Office.

HARRY I. BLITS, OF NEW YORK, N. Y.

HYGIENIC VAPOR AND HOT-AIR RENOVATOR.

SPECIFICATION forming part of Letters Patent No. 510,235, dated December 5, 1893.

Application filed July 5, 1893. Serial No. 479,617. (No model.)

To all whom it may concern:

Be it known that I, IIARRY I. BLITS, of New York, in the county of New York, and State of New York, have invented certain new and useful Improvements in Hygienic Vapor and Hot-Air Renovators; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention relates to portable hygiene, vapor and hot air renovators and has particular reference to an inhaler and vapor spray for catarrh, colds and headache, and also for renovating the hair and scalp and cleansing the head and face.

My invention consists in an apparatus for this purpose as hereinafter set forth and claimed.

o In the accompanying drawings, Figure 1 is an elevation of the invention. Fig. 2 represents details of the wire head screen and Fig. 3 is a longitudinal section of an inhaler spray nozzle.

other stove can be attached to generate hot air and steam. To the cylinder 1 is removably secured the receptacle 2, by means of the flange 3 on the lower periphery, which embraces the top of the said cylinder as shown. The top of the cylinder is closed by means of the lid 6, which is provided with the pipe nipples 8 and 9 and escapement 6'. The nipple 9 is provided with a removable cap 9' and may be used for the attachment of a pipe for hygienic purposes.

To the nipple 8 is secured the pipe 20, suitably braced by the rods 21. To the pipe 20 is adjustably attached a conveyer 22 provided with a damper 23 for regulating the flow of steam and hot air. The upper end of the conveyer is provided with a suitable nozzle 24. To the conveyer 22 is rigidly secured the wire screen 25 which is provided with a hinged cover 26, to obtain access to the inte-

rior of the wire screen, and is provided with

cotton or other fabric on its inside, and with I

the toweling 27, which completely covers the head and hair screen and protrudes out about seven inches from the end thereof, so that the 50 head can be properly adjusted without coming in contact with the wire screen. When it is desired to treat the face, the same is placed partly in the toweling and steamed the same as the cap.

To dry the hair, the steam is cut off and the hot air is substituted.

The band-spring 28 is secured to the pipe 20 and is provided with the thumb screw 29 adapted to engage the slots 30 formed in the 60 conveyer 22. The screen 25 is braced and secured to the conveyer and chair by means of the hooks 31. A spray 37 is attached to pipe 20 when it may be used as an inhaler for catarrh, cold in the head, headache, earache, 65 and other head troubles.

When head, scalp, or hair cleaning is desired, the pipe 20 is adjusted to the nipple 8, the spray is connected to the conveyer. The vapor is then generated until the scalp and 70 hair have received the proper treatment. Then the head and hair are well washed and again placed in toweling. The boiler is then taken out and only the hot air is allowed to circulate, which quickly dries the hair.

Having described my invention, what I claim is—

In a hygiene, vapor and hot air renovator, the combination with a cylinder having a lid provided with pipe openings and removable 80 caps, a pipe secured to one of said openings, a conveyer adjustably secured to said pipe, a spray mouth piece secured to the conveyer and a wire frame having a hinged opening, substantially as shown and for the purposes 85 set forth.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

II. I. BLITS.

Witnesses:
Thos. S. Hopkins,
W. II. Ruff.