

(No Model.)

W. SHOYER, Dec'd.

F. J. SHOYER, Administrator.

HAT CURLER'S IRON STAND.

No. 522,858.

Patented July 10, 1894.





Fig. 2.



WITNESSES:

P. F. Chagel.
Wm. C. Wiedersheim.

INVENTOR
William Shoyer.
Deceased
BY Frederick J. Shoyer.
Administrator.
John A. Wiedersheim.
ATTORNEY.

UNITED STATES PATENT OFFICE.

FREDERICK J. SHOYER, OF PHILADELPHIA, PENNSYLVANIA, ADMINISTRATOR OF WILLIAM SHOYER, DECEASED.

HAT-CURLER'S IRON-STAND.

SPECIFICATION forming part of Letters Patent No. 522,858, dated July 10, 1894.

Application filed July 29, 1893. Serial No. 481,820. (No model.)

To all whom it may concern:

Be it known that WILLIAM SHOYER, formerly residing in the city and county of Philadelphia, State of Pennsylvania, (FREDERICK J. SHOYER administrator of said WILLIAM SHOYER,) hath invented a new and useful Improvement in Hat-Curlers' Iron-Stands, which improvement is fully set forth in the following specification and accompanying
10 drawings.

This invention consists of improvements in hat curlers' iron stands, as will be hereinafter set forth and pointed out in the claims which follow the specification.

15 Figure 1 represents a perspective view of a hat curler's iron stand embodying the invention. Fig. 2 represents a bottom plan view thereof. Fig. 3 represents a vertical section on line *x, x*, Fig. 1, on an enlarged scale.

20 Similar letters of reference indicate corresponding parts in the several figures.

Referring to the drawings: A designates a stand or base having openings B, C, and D therein.

25 E and F designate peaks or elevated supports which are secured to the stand over the openings B and C, the same being provided with flanges G on their lower ends.

Below the peaks are gas pipes H, J, and K, 30 the pipes H and K being perforated so that gas may be burned under said peaks in order to heat the latter. The pipe J is extended as at J' so as to reach the opening D, it being seen that the walls of the latter have the ridge
35 L around the same for supporting a hatter's iron, which is heated by the flame from the perforated portion J' of the gas pipe J. The said ridge L is detachable from said base A, and is secured thereto by means of screws
40 which pass through the eyes L' thereon. It is also provided with a flange A' to hold the iron in place on the ridge.

Air may be admitted to the gas pipes by suitable openings *a* or collars *b*, or both, and
45 to the flames by openings in the stand and the peaks.

On the side edge of the stand are ledges M

and N, which are heated by a flame or flames from the extension P of the gas pipe B, the upper ledge supporting a curved bar or iron 50 Q, which is held in place by the catches R, and adapted to be heated by said ledge.

The peaks E and F are designed for supporting the hatters' tools, known as shackles, while the same are being heated. 55

The iron or bar Q receives between it and the upper ledge N, the brim of a hat for softening the same.

The ledge M is designed for softening the front and rear of the brim, which is placed 60 upon the same.

As the peaks E and F are slanting, the shackles may rest therein in oblique directions, see dotted lines, Fig. 1, thus removing the handles thereof from direct action of the 65 heat, and allowing the same to be kept comparatively cool.

While the bar Q is freely held in place by the catches R, so as to be raised above the ledge in order to permit of the introduction 70 of the brim between the same and the ledge N, especially when brims are of different sizes, said bar may be removed in order to be cleaned of shellac and other matter that may adhere to the same. 75

Having thus described the invention of WILLIAM SHOYER, deceased, what is claimed as new, and desired to be secured by Letters Patent, is—

1. A hat curler's iron stand having the 80 ledges M and N, the catches R, and the bar Q, substantially as and for the purpose set forth.

2. A hat curler's iron stand having a base with openings B, C, D, therein, the supports 85 E and F on the base over the openings B and C, the gas burners H and K beneath said supports, the gas pipe J below the base with the extension J' beneath the opening D, and the extension P of the pipe B of the burner K, 90 said parts being combined substantially as described.

3. A hat curler's iron stand having a base with a ledge on the edge thereof, and a re-

movable bar on said ledge, substantially as described.

4. A hat curler's iron stand having a base with openings B, C, D, therein, and a ledge or
5 ledges on the edge, the supports E and F on the base over the openings B and C, the gas burner H and K beneath said supports, the gas pipe J below the base with the extension J' beneath the opening D and the extension

P of the pipe B of the burner K adjacent to said ledge, substantially as described.

FREDERICK J. SHOYER,
Administrator of the estate of William Shoyer,
deceased.

Witnesses:

JOHN A. WIEDERSHEIM,
R. H. GRAESER.