

(No Model.)

D. B. MARTIN.
STOPPER FOR HOT WATER BAGS.

No. 525,853.

Patented Sept. 11, 1894.

Fig. 1.




Fig. 3.



Fig. 4.





Fig. 2.



Witnesses
J. H. Shugart
William D. Kellogg

Dennis B. Martin.
Inventor
By atty
Earle & Seymour

UNITED STATES PATENT OFFICE.

DENNIS B. MARTIN, OF NEW HAVEN, CONNECTICUT, ASSIGNOR TO THE SEAMLESS RUBBER COMPANY, OF SAME PLACE.

STOPPER FOR HOT-WATER BAGS.

SPECIFICATION forming part of Letters Patent No. 525,853, dated September 11, 1894.

Application filed June 11, 1894. Serial No. 514,229. (No model.)

To all whom it may concern:

Be it known that I, DENNIS B. MARTIN, of New Haven, in the county of New Haven and State of Connecticut, have invented a new
5 Improvement in Stoppers for Hot-Water Bags; and I do hereby declare the following, when taken in connection with the accompanying drawings and the letters of reference marked thereon, to be a full, clear, and exact
10 description of the same, and which said drawings constitute part of this specification, and represent, in—

Figure 1, a view in side elevation of a screw-stopper constructed in accordance with my
15 invention; Fig. 2, a view thereof in vertical central section; Fig. 3, a detached view of the washer; Fig. 4, a view thereof in transverse section.

My invention relates to an improvement in
20 that class of screw-stoppers for water-bags which comprise a sheet-metal body, a wire handle, and a rubber packing or washer, the object of my invention being to produce at a comparatively low cost for manufacture, a
25 simple and strong stopper, of superior appearance and effectiveness.

With these ends in view, my invention consists in a screw-stopper having a spun body, which is recessed to receive an annular pack-
30 ing-washer and in certain details of construction and combinations of parts as will be hereinafter described, and pointed out in the claim.

As herein shown, the stopper consists of a
35 sheet-metal spun body A, a disk-shaped sheet-metal cap B applied to the open outer end thereof, a wire handle C secured to the center of the said cap, and an annular packing washer D, preferably formed of soft rubber,
40 and located in an annular recess A', formed in the body just within, and located in the plane of, the closed inner end thereof. The body is also formed with screw-threads A², adapting it to be screwed into a suitable
45 screw-threaded socket or collar E, which is mounted in the mouth of the water-bag in any approved manner, and constructed at its inner end with an inwardly projecting annular flange E', against which the packing-

washer D is impinged when the stopper is 50 screwed home in the collar. It will be understood, of course, that both the annular recess A' and the screw-threads A², are spun into the body during its formation, and before its
55 assemblance with the cap B, the edge of which is clasped over the outwardly turned upper edge of the body, in the usual manner. The annular recess extends inward sufficiently below the bottoms of the screw-threads
60 so that when the washer is in place, its outer edge will be flush, or substantially flush, with the surface of the body.

By adapting the body of the stopper to itself receive the packing-washer in a recess
65 formed in it, I secure a construction which is at once extremely simple, cheap, attractive, convenient and cleanly. The washer may be readily removed and replaced when worn, or for the purpose of washing it and the stopper. Furthermore, when the stopper is screwed
70 home in its socket or collar, the washer is subjected not merely to direct flatwise compression, but also to pressure tending to force it outward and expand it into the bottom of the socket, whereby its effectiveness as a
75 packing is greatly enhanced, the washer being forced outward by the inclination of the inner or outer wall of the recess in which it is located.

I would have it understood that I do not
80 limit myself to the exact construction herein shown and described, but hold myself at liberty to make such changes and alterations therein as fairly fall within the spirit and
85 scope of my invention.

I am aware, however, that a bottle-stopper, constructed with an annular recess to receive a packing-washer, is old. I am also aware that a hollow stopper for hot-water
90 bags, formed in part of spun sheet-metal, is old. I do not, therefore, claim either of those constructions broadly.

Having fully described my invention, what I claim as new, and desire to secure by Letters
95 Patent, is—

A screw-stopper for water-bags, consisting of a spun sheet-metal body having its inner end closed, and its outer end open, and formed

with screw threads, and with an annular recess; located between its screw-threads and its closed inner end a sheet-metal cap applied to the open outer end of the said body, a handle secured to the said cap, and an annular packing-washer located in the said recess of the body, substantially as described.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

DENNIS B. MARTIN.

Witnesses:

FRED C. EARLE,
GEO. D. SEYMOUR.