




(No Model.)

M. F. KOENIG.

DEVICE FOR SUPPORTING COATS, VESTS, &c.

No. 528,601.

Patented Nov. 6, 1894.



Witnesses:
L. C. Mills
E. A. Bond

Inventor;
Morris F. Koenig.
by E. B. Stocking
Attorney.

UNITED STATES PATENT OFFICE.

MORRIS F. KOENIG, OF HAZLETON, PENNSYLVANIA, ASSIGNOR TO THE
BARBER-KOENIG MANUFACTURING COMPANY, OF SAME PLACE.

DEVICE FOR SUPPORTING COATS, VESTS, &c.

SPECIFICATION forming part of Letters Patent No. 528,601, dated November 6, 1894.

Application filed November 8, 1893. Serial No. 490,380. (No model.)

To all whom it may concern:

Be it known that I, MORRIS F. KOENIG, a citizen of the United States, residing at Hazleton, in the county of Luzerne, State of Pennsylvania, have invented certain new and useful Improvements in Devices for Supporting Coats, Vests, and Pantaloon, of which the following is a specification, reference being had therein to the accompanying drawings.

10 This invention relates to certain new and useful improvements in devices for supporting coats, vests and the like, of that class in which the hanger is formed of wire and comprises a bow portion and means for suspending the same.

15 It has for its object among others to provide an improved device of this character which shall be strong and durable and which shall have a novel form of construction in that the portion by which the hanger is designed to be supported is made with an offset which serves to keep the hanger proper from the wall and the parallel wires thereof serve to support a plate upon which may be placed
25 any desired advertisement, and this plate, in turn, serves to stiffen and strengthen the suspending portion. This offset therefore serves a double purpose. The hanger is preferably formed of a single piece of wire which may
30 be given the desired shape by suitable devices or mechanism which forms no part of this invention. The peculiar construction of the suspension portion affords greater elasticity. It further provides a space for the reception
35 of the collar of a coat as the latter is supported on the hanger.

Other objects and advantages of the invention will hereinafter appear and the novel features thereof will be specifically defined
40 by the appended claim.

The invention is clearly illustrated in the accompanying drawings, which, with the letters of reference marked thereon, form a part of this specification, and in which—

45 Figure 1 is a perspective view of the improved hanger. Fig. 2 is an enlarged face view of the upper portion. Fig. 3 is a vertical section through the line 3—3 of Fig. 2.

Like letters of reference indicate like parts
50 throughout the several views.

In carrying out the invention the device is preferably formed of a single piece of wire which is bent to form the yoke or arch portion *a* of double wire preferably bow-shaped

as is usual in this class of articles, and the 55 doubled wire is held firmly in the desired position by being twisted around the bow-shaped portions at points near the adjacent ends thereof or at the center as seen in Fig. 1, where the ends are shown as twisted around 60 the said bow-shaped portions. One strand or portion of each of the bows is bent at right angles as seen at *b* and thence bent horizontally to form the bar *e* and the other one is likewise bent at *d* to form the substantially 65 parallel bar *c* and these two are bent at *f* and *g* respectively to form the parallel vertical arms *h* and *i* which are bent forward at their upper ends to form the parallel arms *k* and *l* which are in the same plane as the bars *e* and 70 *c* as seen best in Fig. 3 and then they are extended upward and formed with a coil *m* which is substantially in the plane with the central portion of the arched portion as seen best in Fig. 3. 75

The two arms *h* and *i* are held rigidly at their proper distance apart by a plate *B* which has its edges bent around the said arms as shown, and upon this plate may be placed
80 any desired advertisement or other matter. This plate serves to stiffen the hanger and forms a flat bearing against the wall to prevent wobbling of the hanger when used in that position, and the offset formed by the peculiar construction of this upper portion 85 provides a space to receive the collar of a coat when supported on the arched portion.

What is claimed as new is—

A garment hanger formed of a single piece of wire bent at its center to form a suspending 90 portion from which extend vertical, parallel arms merging into horizontal arms, the adjacent, vertical arms in a different vertical plane from the suspending portion and with horizontal arms parallel with the upper horizontal arms and terminating in an arched 95 supporting portion in substantially the same vertical plane as the suspending portion and a plate secured to the vertical parallel arm between the upper and lower horizontal arms, 100 substantially as shown and described.

In testimony whereof I affix my signature in presence of two witnesses.

MORRIS F. KOENIG.

Witnesses:

R. RAYMOND JONES,
HENRY PLATT.