

(No Model.)

G. E. ADAMS.  
CLASP.

No. 537,955.

Patented Apr. 23, 1895.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.




Fig. 6.




Fig. 8.





Fig. 7.



Witnesses

J. M. Fowler Jr.  
Thomas Durant

Inventor

George E. Adams,  
By Church & Church  
his Attorneys



# UNITED STATES PATENT OFFICE.

GEORGE E. ADAMS, OF NEW BRITAIN, CONNECTICUT, ASSIGNOR TO THE  
TRAUT & HINE MANUFACTURING COMPANY, OF SAME PLACE.

## CLASP.

SPECIFICATION forming part of Letters Patent No. 537,955, dated April 23, 1895.

Application filed November 2, 1893. Serial No. 489,834. (No model.)

*To all whom it may concern:*

Be it known that I, GEORGE E. ADAMS, of New Britain, in the county of Hartford and State of Connecticut, have invented certain  
5 new and useful Improvements in Clasps; and I do hereby declare the following to be a full, clear, and exact description of the same, reference being had to the accompanying drawings, forming a part of this specification, and  
10 to the letters of reference marked thereon.

This invention relates to improvements in metallic clasps, such as are particularly but not exclusively designed for use upon garment supporters for ladies' and children's  
15 wear, and it has for its object to provide a device which shall be cheap and simple to manufacture, and one which will grasp the garment with a secure hold and at the same time, be extremely easy to fasten or release  
20 from the garment, thus overcoming in a great measure the objection to clasps of this character now in common use.

Referring to the accompanying drawings: Figure 1 is a front, Fig. 2 a side elevation, and  
25 Fig. 3 a rear view, of the preferred form of clasp. Fig. 4 is a vertical section through the same. Figs. 5, 6, and 7 are rear views in perspective, illustrating different forms of gripping jaws for the clasp. Fig. 8 is a view  
30 of the device gripping a garment.

Similar letters of reference in the several figures indicate the same parts.

In carrying this invention into practice, I preferably stamp the parts up from sheet  
35 metal, as is usual in this class of devices, and one of the parts, which I shall for convenience, term the body portion, lettered A in the drawings, is formed with laterally extending ears *a*, which are adapted to be bent around the  
40 end of the web constituting the supporter proper in order to attach the device thereto, and it is obvious that any of the ordinary well known means for securing a strong union may be employed if desired. The body portion  
45 is formed with a downwardly extending tongue B, preferably curved toward the rear somewhat, as shown best in Figs. 2 and 4 and provided at its lower end with a forwardly curved hook *b*, having its end *b'* turned well  
50 up toward the body A. In the preferred con-

struction, the end of the hook is smooth, but I may find it advantageous for some purposes as will hereinafter appear, to serrate or tooth this end, as shown for instance at *b'*, in Figs. 6 and 7.

To the front of the body portion and preferably at the base of the tongue is hinged a co-operating member consisting of a shank portion C terminating at the lower end in an inclosing ring for the end of the hook, such inclosing ring being preferably in the form of a concavo-convex cap D. At the lower end, this inclosing ring or cap is provided with a lip *d* preferably projecting upward, and in any instance, with its edge lying in position  
60 to co-operate with the extreme lower portion of the hook so as to hold said hook within the cap as illustrated in Figs. 3 to 7 or allow the same to be snapped out as in Fig. 2.

It will be observed that the front of the cap  
70 portion serves as a limiting stop for the end of the hook. The hook tongue B and portions C of the co-operating member are sufficiently elastic to allow the end of the hook to spring past the lip on the cap portion, which  
75 will thus serve as an efficient means for holding the hook in closed position when engaged with the fabric as illustrated in Fig. 8.

In engaging the device, the body portion is grasped, the hook passed beneath the fabric  
80 of the garment to be supported and the cap pressed down until the hook carrying the fabric with it, snaps past the lip on the cap, when any direct pull on the fabric will be taken up by the lip D and end of the hook *b*,  
85 there being so little tendency to cause the hook to move outward so that with a direct pull on the webbing of the supporter it is almost impossible to release the device. To insure a better grip, the edge of the lip D  
90 may, if desired, be toothed and serrated, as shown in Figs. 5, 6 and 7, and in every instance, it is preferably made with recesses *e* at each side into which the fabric may pull when drawn down.

Obviously, the hinging of the two members together may be accomplished in any well known manner, but I preferably strike up a small ear *f* from the base of the hooked tongue B and curve this ear forward around a piv-  
100



oted bar *g* formed on the upper end of the co-operating member C, usually by simply slitting the end of this member.

5 The device it will be observed is extremely simple, easily and cheaply manufactured and what is of greater importance, may be engaged with and released from the fabric of the garment with the greatest facility, and  
16 hold with a secure grip against any strains upon the garment or supporter.

Having thus described my invention, what I claim as new is—

15 As an improved article of manufacture, the clasp for garment supporters herein described, consisting of the body portion formed at the top for the attachment of the webbing and at

the bottom into the spring tongue terminating in an upwardly turned hook and the overlying member hinged at the upper end to the 20 body at a point intermediate the ends of the body said overlying member being formed at the bottom with a circular orifice adapted to surround the hook on the body, and itself having at the bottom an upwardly projecting 25 lip co-operating with the hook to form a snap catch for grasping the fabric of the garment to be supported when caught over the same; substantially as described.

GEORGE E. ADAMS.

Witnesses:

R. A. MOORE, Jr.,  
G. W. TRAUT.