




P. S. MCGEE.
VOTING MACHINE.

No. 537,990

Patented Apr. 23, 1895.



WITNESSES.

Robert J. Foster
Benjamin L. Dennis

FIG. 3 1/2

INVENTOR.
Patrick J. McGee
By Charles J. Hannigan
Atty.


(No Model.)

3 Sheets—Sheet 2.

P. S. McGEE.
VOTING MACHINE.

No. 537,990.

Patented Apr. 23, 1895.



WITNESSES.

John C. Camfield
James H. Hickey

INVENTOR.

Peter S. McGee
By Charles J. Hannigan
ATTY.

(No Model.)

3 Sheets—Sheet 3.

P. S. McGEE.
VOTING MACHINE.

No. 537,990.

Patented Apr. 23, 1895.




FIG. 9.




FIG. 8.

WITNESSES.

John C. Lamfield
James H. Hickey

INVENTOR.

Patience S. McGee
By Charles J. Hannigan
ATTY.

UNITED STATES PATENT OFFICE.

PATRICK S. MCGEE, OF DODGEVILLE, MASSACHUSETTS.

VOTING-MACHINE.

SPECIFICATION forming part of Letters Patent No. 537,990, dated April 23, 1895.

Application filed January 7, 1895. Serial No. 534,121. (No model.)

To all whom it may concern:

Be it known that I, PATRICK S. MCGEE, a resident of Dodgeville, in the county of Bristol and State of Massachusetts, have invented certain new and useful Improvements in Voting-Machines; and I do hereby declare that the following is a full, clear, and exact description thereof, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

This invention belongs to a class of machines intended to facilitate the operation of voting by simplifying the actions required, thereby shortening the time and enabling more voters to cast their ballots at one place in a given time, and it provides safeguards against the practice of "repeating," or allowing any person to vote more than once for the same candidate. It also provides for a registration of the number of votes cast for each person. It is fully explained and illustrated in this specification and the accompanying drawings.

Figure 1 shows a front elevation of the apparatus complete. Fig. 2 is a top view showing the gate and its connection with the locking bar. Fig. 3 is a top view of one of the locking bars, also showing the operating levers in their relative position as in No. 1, of Fig. 5. Fig. 3½ is a top view of a part of the locking bar when an operating lever is pulled down said movement engaging the lever with the latch lever *i*, which in turn pushes the locking bar endwise to the right and causing the lugs *o'* of the locking bar to pass under all the other operating levers and lock them up at the same time it is locked down by its own lug passing over itself. See Fig. 5. Fig. 4 shows an elevation of one, and part of another, of the divisions seen in Fig. 1, one of the division doors being open to show the operating lever and registering dials. Fig. 5 is a vertical section taken on line *x—x* of Fig. 4, showing a side view of the operating lever and the devices for registering. Figs. 6 and 7 show a side view of locking bar and the parts moved by it, in section on line *y, y*, of Fig. 5. Fig. 8 is a cross section looking down taken on line *v, v*, in Fig. 1, showing the means provided for a voter to cast his ballot

for any name not included in the party nominations. Fig. 9 is a vertical section taken on line *w, w*, in Figs. 1, and 8.

The apparatus consists of a series of compartments arranged in columns, the number of divisions in each column being the same as the number of offices to be filled, and a column is provided for each political party and another for the independent voter. All the columns are marked conspicuously at the top with a party name and each division has the name of a candidate placed on its front. All the divisions are provided with the same mechanism and the divisions of the independent voter's column to the right has additional mechanism to provide a card for the voter to write any name on he wishes to vote for. The divisions are independent of each other except in the locking arrangement by which all the divisions in each horizontal row are connected together so that the operation of one will lock all the others on that row. Each division is provided with a lever *h*, to operate its mechanism, (see Fig. 5,) and also has a registering dial and sub-dials to keep the count of the number of times the operating lever has been used in voting.

In Fig. 4 one of the divisions is shown with the door, with which they are all provided, open to show the dials.

In Fig. 5 is shown a side view of the mechanism which consists of a horizontal shaft *A*, placed at about the center of the division and having a large ratchet wheel *w*, on its back end, and at its front end a hand or pointer to indicate on the dial the number of times the ratchet wheel *w*, has been moved. A horizontal shaft *B*, is placed at right angles to the shaft *A*, in front and near the bottom of the ratchet wheel *w*. A collar *d*, is placed on the shaft *B*, and a spring hook *g*, is made fast to it, in position to have said spring hook catch in the teeth of the ratchet wheel *w*.

The operating lever *h*, is held on a stud fast in a bracket *D* attached to the inside of the case, and a small pawl *r*, is pivoted to the lower end of the lever *h*, so as to catch into a notch made into the collar *d*, and turn it over a little ways when the lever *h*, is pulled down, equal to one division on the ratchet wheel.

A recess is made in the lower side of the

collar *d*, to receive the end of the main spring *s*, which is connected by a link to one side of the recess. The lower end of the spring is made fast to the inside of the case and its
 5 object is to return the parts back to position after being moved.

It will readily be observed that when the operating lever *h*, is pulled down in the direction of the arrow the pawl *r*, at the lower end will push the collar *d*, over a short distance so that the spring hook *g*, will draw over the ratchet wheel *w*, one notch which the stationary pawl *u*, will hold, and move the pointer on the face of the dial the same.
 10 The shaft A, which carries the pointer *v*, that indicates on the large dial, *w'*, is connected by a train of wheels with the shafts that carry the pointers for the small dials *e'*, *a'*, the first of which registers the number of whole revolutions the pointer of the large dial makes,
 20 and the latter the number of revolutions the pointer on dial *e'*, makes. Thus the large dial registers the single movements of the operating lever *h*, up to one hundred and the dial *e'*, registers the hundreds up to one thousand, and if there are fifty divisions on the dial *a'* it will register the thousands up to fifty thousand or that number of votes.

A locking arrangement is provided whereby
 30 any one of the operating levers *h*, having been pulled down, the other levers in that row will be locked up, and itself locked down so they cannot be moved until the gate has been opened. This prevents all "repeating,"
 35 or voting more than once for the same candidate by one voter. The locking arrangement is shown in Figs. 2, 3, 3 $\frac{1}{2}$, 6, and 7.

In Fig. 3 the locking bar is shown as a rectangular bar *l*, with recesses *o*, made in the
 40 front of it and having projections *o'* on the side of said recess. One of these bars is placed in the lower front corner of each horizontal row of divisions so as to bring one of the recesses *o*, over each lever *h*. (See Fig. 5.)
 45 The bar *l*, is held on flanged friction rolls *n*, to make it move easily. A knee lever *i*, is placed under the locking bar *l*, a little to the left of each recess *o*, on pivots held in stands and made fast to the bottom of the division,
 50 and a notch *m*, is made in the under side of the bar *l*, over each knee lever. The operating lever *h*, is arranged to strike on one end of the knee lever *i*, and cause the other end of said knee lever to catch into the notch *m*,
 55 and move the locking bar *l*, to the right so as to keep all the other levers *h*, in that row from being pulled down again until the locking bar *l*, is drawn back, said levers *h*, being held in position by the projections *o'* until
 60 the opening of the gate to which the locking bar is connected by a chain.

In referring to Fig. 5 the No. 1 position of operating lever *h*, corresponds with Fig. 6 or as ready to be pulled downward on to the knee
 65 lever *i*, the No. 2 position of operating lever

h, corresponding with Fig. 7 or as operating lever *h*, trips the knee lever which in turn moves the locking bar a sufficient distance to prevent the remaining levers *h*, in that row
 70 from being pulled down, and the No. 3 position of operating lever *h*, as shown by the dotted lines in Fig. 5 represents when said lever *h*, is released by the hand of the voter, the main spring *s* carrying it back until it rests under the lug or projection *o'*, until the
 75 voter passes through the gate *p*, said gate having a chain *c*, fastened to it, the other end of which is attached to the locking bar *l*, which movement draws the bar to the left a short distance to allow the operating lever *h*, to go
 80 back into its recess *o*.

For an independent voter who may wish to vote for a candidate not on the lists of either of the parties, a column of divisions to the right in Fig. 1 is provided. These divisions
 85 in this column besides having all the registering and locking mechanism of the other divisions, has a crank arm *a*, made fast on the end of the shaft A, and connected at its lower end by a bar *b*, to a thin plate *j*, made to slide
 90 horizontally on the bottom of the division, and a case *k*, to hold a pile of blank cards is fastened to the inside of the division, and over the path of the plate *j*, so that when the lever *h*, is pulled down, the arm *a*, will move the
 95 plate *j*, and push the bottom card out through the slot in the front of the division on to a shelf where the voter can write any name he chooses on it and deposit it in the opening
 100 *t*, in the front of the division, which leads to a box *y*, on the inside placed to receive the cards. A bell *h'* is placed over the gate *p*, so as to be rung when the gate is opened by the voter, and another bell *d'* is placed in the
 105 upper part of each division in position to be struck every time the ratchet wheel *w*, moves a notch.

A lock is attached to the door of each division the key of which is held by the election officers and all access of the voters to any-
 110 thing but the operating lever is cut off.

This constitutes a simple and safe voting apparatus by which the voter passes in through the gate to the machine in full view of others or in private as may be preferred, and select-
 115 ing the candidates he desires to vote for, pulls down an operating lever for each and in so doing locks that lever so that he cannot pull it down again and vote twice for the same person nor can he vote for any other person for
 120 the same office because of all the other operating levers being locked up and the chains *c* leading from the locking bars to the gate being protected by covers *c'*, there is no way of releasing the operating levers but by open-
 125 ing the gate. If the name of the person he wishes to vote for does not appear on any of the divisions he can go to the column of divisions for the independent voter and by drawing down the operating lever a card will be pushed
 130

out to him upon which he can write the name he wishes and deposit the card in the receptacle provided for it.

Having thus described my improvement, I
5 claim as my invention—

In a voting apparatus, a series of divisions one for each office, a series of subdivisions one for each candidate for each office, an operating lever for each subdivision, a locking
10 device to lock all the operating levers, a connection between said locking device and a

gate to unlock the levers by the opening of said gate, a receptacle for blank cards, devices for delivering one card for each movement of the operating lever, and a receptacle 15 to receive said card from the voter, substantially as described.

PATRICK S. MCGEE.

Witnesses:

JOHN E. CAMFIELD,

JAMES H. HICKEY.