
(No Model.)

J. A. WHITE.
MUSIC LEAF TURNER.

No. 547,310.

Patented Oct. 1, 1895.



S. Solliatt.

Joseph A. White INVENTOR


--- By Miller Attorney

(No Model.)

J. A. WHITE. MUSIC LEAF TURNER.

No. 547,310.

Patented Oct. 1, 1895.



S. S. Olliatt.

M. S. Olliatt.

Josephel. White
INVENTOR

Attorney

United States Patent Office.

JOSEPH A. WHITE, OF AUGUSTA, MONTANA.

MUSIC-LEAF TURNER.

SPECIFICATION forming part of Letters Patent No. 547,310, dated October 1, 1895.

Application filed June 6, 1895. Serial No. 551,862. (No model.)

To all whom it may concern:

Be it known that I, Joseph A. White, a citizen of the United States of America, residing at Augusta, in the county of Lewis and 5 Clarke and State of Montana, have invented certain new and useful Improvements in Music-Leaf Turners; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will ento able others skilled in the art to which it appertains to make and use the same, reference being had to the accompanying drawings, and to letters of reference marked thereon, which form a part of this specification.

The object of this invention is to provide a simple and inexpensive music-leaf turner, which can be readily applied to pianos, organs, and similar instruments for holding sheet-music and turning the leaves thereof

20 successively or collectively.

The invention consists in the construction after fully set forth, and particularly pointed out in the claims.

In the accompanying drawings, forming part of this specification, Figure 1 is a perspective view of a music-leaf turner constructed in accordance with my invention, showing but a single leaf holder and turner 30 upon the supporting-rod; and Fig. 2 is a front elevation of the device, showing a number of leaf holders and turners upon the rod.

A designates the support or ledge with which pianos and organs are usually provided, 35 and to this ledge my improved music-leaf holder and turner is adapted to be applied.

B designates a box or suitable fixture, the upper and lower portions extending beyond the sides at the rear, so as to lie above and 40 below the ledge A and position the box immediately in front of the same. The upper part of the box may be provided with suitable clamping-screws for holding the same securely in place. Through the front portion 45 of the box or fixture B passes a rod C, which is supported in a vertical position with respect to said box, and immediately in rear of this rod is located a spring-bar D. Passing into or through the front portion of the box 50 or fixture B are wires E, which extend from the sides of the box and are bent upwardly,

then outwardly, where they are bent upon themselves and have connecting portions, a similar arrangement of bends being in the upper part, where they are formed into eyes 55 or loops e, which encircle the rod C near its upper end. It will be observed that the wires E extend on both sides of the rod C.

So much of the device as has been described is adapted to hold in place a single sheet of 60 music, the same being placed between the rod C and spring-bar D and the edges of the leaves placed between the bent portions of the wires E. The wires E may be made of a single piece or two pieces, each having eyes 65 at their upper ends, while their lower ends enter the box or fixture and are suitably retained therein.

F designates the leaf holders and turners, which are each made up of two sections or 70 wire loops connected to each other at their upper and lower ends, where they are formed and combination of the parts, as will be herein- | into eyes which encircle the rod C, the several leaf holders and turners being separated by washers or collars, as shown in Fig. 2. By 75 reference to Fig. 1, it will be noted that the leaf holders and turners are each made up of a single lenghth of wire, starting at an intermediate portion of the lower member of one loop, passing back to form the lower eye, then 80 bent to form the other loop, twisted to form the upper eye, and finally bent to form the major portion of the first-mentioned loop, the ends being twisted upon themselves to form a handle or lever f, which is bent, as shown, 85 to engage the lower part of the rod C, from which it extends to provide a grasping portion, the handles being of different lengths and are connected to their loops in such manner as to position the grasping portions side 90 by side on a horizontal line. In use the music-leaves may be placed between the sections of the leaf holder and turner, and when it is desired to turn a leaf the holder in which it is placed can be moved to the other side of 95 the rod or support C by turning its operating handle or lever.

> In order to more securely hold the leaf in connection with its holder, I solder or otherwise attach to the handle f, adjacent to its 100 loop, a spring clamp or clasp G, so that the jaws thereof will be positioned between the

two sections or loops, and by this arrangement when the jaws are opened the sections will be

separated to receive the music-leaf.

This device can be very cheaply manufactured, is light and effective in turning leaves, either successively or collectively, and may be used not only for sheet-music, but also for turning the leaves of books, in which case the wires E will support the backs of the books.

I am aware that prior to my invention it has been proposed to provide a music-leaf turner with a series of arms which engage with leaves, said arms having handles for operating the same, and I do not therefore

claim such invention broadly; but

What I claim as new, and desire to secure

by Letters Patent, is-

1. A leaf holder and turner, comprising a suitable box or fixture serving as a support for a central rod C, leaf holders or cover supports E connected to the rod and to the box or fixture, each support consisting of a loop bent back upon itself at its outer end as shown, and a leaf holder and turner pivoted at its upper and lower ends upon the rod and made up of a double loop, an operating handle formed on one of the loops, and an interposed spring clamp the jaws of which lie between the loops, substantially as shown and for the purpose set forth.

2. In a leaf holder and turner, the combi-

nation, of a suitable box or fixture B supporting a rod C, leaf holders or cover supports E connected to the rod and to the box 35 or fixture; together with leaf holders and turners F pivoted at their upper and lower ends upon the rod, each leaf holder and turner consisting of a single length of wire bent to form eyes which encircle the rod and two loops 40 which normally lie together, the ends of the wire being twisted one upon the other to form an operating lever or handle, and spring clamps secured to the levers or handles so that the jaws thereof will extend between 45 the loops, substantially as shown and for the purpose set forth.

3. A leaf holder and turner comprising a suitable support or fixture which carries a rod C and rear of said rod a spring bar, as D, 50 wires E rigidly attached to the fixture and to the upper ends of the rod C said wires having portions bent upon themselves as shown, one or more leaf holders made up of wire in the form of a loop which is connected at its 55 ends to the rod C, the wire being twisted at an intermediate point so as to form a handle which is also connected to the rod C.

In testimony whereof I affix my signature

in presence of two witnesses.

JOSEPH A. WHITE.

Witnesses:
RAYMOND J. Goss,
T. G. Woods.