

(No Model.)

J. C. BURGESS.
BOLT CLIPPER.

No. 547,328.

Patented Oct. 1, 1895.




Fig. 1.




Fig. 2.

Fig. 3.

WITNESSES:
F. L. Ourand.
J. M. Stone.

INVENTOR.
James C. Burgess,
by Louis Bagge & Co.
Attorneys.

UNITED STATES PATENT OFFICE.

JAMES C. BURGESS, OF YOUNTSVILLE, INDIANA, ASSIGNOR TO JOHN F. HAYWORTH, OF SAME PLACE.

BOLT-CLIPPER.

SPECIFICATION forming part of Letters Patent No. 547,328, dated October 1, 1895.

Application filed May 31, 1895. Serial No. 551,110. (No model.)

To all whom it may concern:

Be it known that I, JAMES C. BURGESS, a citizen of the United States, and a resident of Yountsville, in the county of Montgomery and State of Indiana, have invented certain new and useful Improvements in Bolt-Clip-
5 pers; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it appertains to make and use
10 the same, reference being had to the accompanying drawings, which form a part of this specification.

My invention relates to bolt-clippers; and
15 its object is to provide an improved tool for such purpose which shall possess superior advantages with respect to efficiency in operation.

The invention consists in the novel construction and combination of parts hereinafter fully described and claimed.

In the accompanying drawings, Figure 1 is a side elevation of a bolt-clipper constructed in accordance with my invention. Fig. 2 is
25 a similar view looking from the under side. Fig. 3 is a longitudinal sectional view.

In the said drawings the numeral 1 designates a metal bar formed at one end with a curved stationary jaw 2, having its extremity
30 or end beveled to form a cutting-edge. Intermediate its ends this bar has riveted or otherwise secured to it a bracket 3, through which and the bar passes a bolt 4, to which is pivoted a link 5. The other end of this
35 link, which is rounded, fits in a curved recess 7 in the cam-head 6 of a lever 8 and is pivoted to a link 9. At the opposite side the said head is formed with a similar recess 10, in which is seated the rounded end of a movable
40 bar 12, which end is pivoted to the outer end of said link 9. This bar passes through and works in guides 13, secured to bar 1, and its outer end is beveled to form a cutting-edge.

The manner of using the device will be
45 readily understood. A bolt to be clipped is placed between the cutting-edges of the jaw 2 and of the movable rod, and the lever is then pressed inward, and through the medium
50 of the recessed cam-head and rounded ends of the bar 12 and link 5 great pressure is exerted upon the bolt, so that it will be readily clipped. It will be seen that the lever is not pivoted or otherwise secured to any of the
55 parts, being held in place by the rounded ends of clip 5 and bar 12, the link 9, pivoted to said bar and link, holding it in place.

The numeral 14 designates a stop secured to the bar 1 for limiting the movement of the lever and preventing the cutting-edges of the
60 jaw and movable bar from coming in contact with each other.

Having thus fully described my invention, what I claim is—

In a bolt clipper, the combination with the
65 bar having a curved cutting jaw, the bracket secured to said jaw, the bolt, the link pivoted at one end to said bar, and having its other end rounded, the movable bar having its
70 outer end provided with a cutting edge and its opposite end rounded, and the guides in which said movable bar works, of the cam lever having opposite curved recesses in
75 which the rounded end of said link and the inner end of the movable bar engage, forming knuckle joints, and the link pivoted to said first mentioned link and to the movable bar, substantially as described.

In testimony that I claim the foregoing as my own I have hereunto affixed my signature
80 in presence of two witnesses.

JAMES C. BURGESS.

Witnesses:

EARL L. HURLEY,
A. T. HORNBAKER.