




(No Model.)

J. L. YATES.

DESK ATTACHMENT FOR RAILWAY CAR SEATS.

No. 547,830.

Patented Oct. 15, 1895.



Attest:

Jacob Marx.
L. Lee.

Inventor.

John L. Yates
By
William H. Lambrogh
Attorney

UNITED STATES PATENT OFFICE.

JOHN L. YATES, OF LITTLE FALLS, NEW YORK.

DESK ATTACHMENT FOR RAILWAY-CAR SEATS.

SPECIFICATION forming part of Letters Patent No. 547,830, dated October 15, 1895.

Application filed February 7, 1895. Serial No. 537,624. (No model.)

To all whom it may concern:

Be it known that I, JOHN L. YATES, a citizen of the United States, residing at Little Falls, Herkimer county, State of New York, have
5 invented certain new and useful Improvements in Desk Attachments for Railway-Car Seats, of which the following is a specification.

My invention has for its object to furnish a collapsible desk attachment provided with
10 a flexible top covering, which, with the supporting-frame, may be readily folded into a small compass to facilitate transportation. The attachment constitutes a new article of manufacture, the parts of which are so ar-
15 ranged that it may be quickly unfolded and adjusted to a car-seat, and then makes a convenient writing desk or shelf for railway travelers.

The invention will be understood by reference to the annexed drawings, in which—

Figure 1 is a perspective view taken from the upper side of the desk or attachment expanded in readiness for use and hung upon the back of a car-seat, the upper part of which
25 is also indicated in the drawings. Fig. 2 is a perspective view taken from the lower side of the device expanded, but detached from the car-seat. Fig. 3 is a perspective view taken from the lower side, like Fig. 2, with
30 the device in a partly-folded condition.

The construction belongs to that class in which the desk-top is hinged to back-stay bars, which latter are provided with hooks to engage the top of the car-seat, the desk-top
35 itself having a frame which is provided with transverse brace-bars hinged in such manner as to permit the folding of the device in a small compass. The top frame is rectangular and the transverse brace-bars are attached
40 close to its ends. The desk-top 1 is made of some flexible material, as rubber-faced cloth or oil-cloth, or may be made of light wooden strips secured to a flexible fabric, so as to be rolled with entire facility. This top 1 is fast-
45 ened, as represented in the drawings, by the aid of clamping-strips 2 to the opposite side bars 3 3 of the top frame. These side bars are jointed by hinges 4 4 to the outer ends of pairs of brace-bars 5 5, the inner ends of
50 each pair of which are coupled together by hinge 6. These two two-part bars 5 5 form

braces, which may be folded inward on the hinges 4 6, as hereinafter explained.

The back-stay bars 8 8 are provided at their upper ends with hinges 7, by which they are
55 jointed to the inner ends of the top frame-bars 3 3, and an inclined brace 10 is pivoted upon each of the stay-bars to sustain the top when in use. The lower end of each brace is pivoted to the stay-bar 8 at a point 9 below
60 the hinge 7, and the other end of the brace is provided with a slot 11, forming a hook adapted to engage the shank of a headed stud or screw 12, which is fastened in the
65 outer side of the adjacent bar 3. The upper end of each stay-bar is provided with a hook 14, adapted to support the attachment upon the back of a car-seat, which in Fig. 1 is designated 13.

The device is fitted for transportation by
70 unhooking the inclined braces 10 from the studs 12 and turning them downwardly upon the sides of the stay-bars 8 and then folding the stay-bars upon the under side of the frame-bars 3, as is shown in Fig. 3. The top
75 frame is then collapsed, so as to bring the side bars and stay-bars in proximity with one another by pressing inwardly the transverse braces 5 5, which, being jointed at the middle by the hinges 6 and attached by the hinges 7
80 to the inner side of the frame-bars, are adapted to pack closely between the same when wholly bent, as illustrated in Fig. 3.

The flexible top permits the approximation of the side bars 3 when thus collapsed and may
85 be folded around the same, as is partially indicated in Fig. 3.

When required for use, the top frame is distended by drawing apart the side bars 3. The transverse braces 5 are then straightened
90 to act as toggles to stretch the flexible top 1 flat and tightly over and across said frame. The back-stays 8 are then unfolded on their hinges 7 and the slots 11 of the pivoted braces 10 are engaged with the top frame-studs 12,
95 thus securing the device in the braced condition shown in Fig. 2 of the drawings. The hook-clamps 4 are then adapted to slip over the top of the car-seat back, as shown in Fig. 1, which wholly adjusts the device for use.
100

When desired, the device may be collapsed and repacked in the manner already described

and then occupies but a small amount of space.

I am aware that it is common to construct a desk with a top having hinged stay-bars 5 and braces, and I do not, therefore, claim such a combination as my own invention; but,

Having set forth the constructive features of my new article of manufacture, I claim the same, as follows:

10 As a new article of manufacture, the desk attachment comprising the rigid bars 3, 3, with the flexible top 1 fastened thereto and having the studs 12 upon their outer sides,

the two-part bars 5, 5, coupled by hinges 6 and connected to bars 3 by hinges 4, the back- 15 stays 8 connected at the top by hinges 7 to the rear ends of the bars 3 and provided with the hooks 14, and the braces 10 pivoted to the stays 8 below the hinges 7 and formed at their ends with slots 11 adapted to engage the studs 20 12, the whole arranged and operated substantially as herein set forth.

JOHN L. YATES.

Witnesses:

JACOB MARX,

M. H. UNDERWOOD.