



(No Model.)

E. L. COLE.
STOVE LEG.

No. 553,152.

Patented Jan. 14, 1896.



Inventor

Edwin L. Cole.

Witnesses

Thos. W. Riley.
J. F. Riley

By His Attorneys,

C. A. Snow & Co.

UNITED STATES PATENT OFFICE.

EDWIN L. COLE, OF PERU, OHIO.

STOVE-LEG.

SPECIFICATION forming part of Letters Patent No. 553,152, dated January 14, 1896.

Application filed October 2, 1895. Serial No. 564,391. (No model.)

To all whom it may concern:

Be it known that I, EDWIN L. COLE, a citizen of the United States, residing at Peru, in the county of Huron and State of Ohio, have
5 invented a new and useful Stove-Leg, of which the following is a specification.

The invention relates to improvements in stove-legs.

The object of the present invention is to improve the construction of that class of stove-legs which are supplied with casters and to enable the casters to be readily brought into operation when it is desired to move the stove from one point to another and to raise the
10 casters above the floor or other supporting-surface when it is desired to support the stove firmly in position for use or the like.

The invention consists in the construction and novel combination and arrangement of
20 parts hereinafter fully described, illustrated in the accompanying drawings, and pointed out in the claim hereto appended.

In the drawings, Figure 1 is a vertical sectional view of a stove-leg constructed in accordance with this invention. Fig. 2 is a detail perspective view of the lower portion of the caster. Fig. 3 is a similar view of the upper portion thereof.

Like numerals of reference indicate corresponding parts in all the figures of the drawings.

1 designates a stove-leg provided at its inner side with a pair of perforated horizontal ears or flanges 2 and 3, which are arranged
35 parallel and have located between them a nut 4, and the latter engages a threaded stem 5, which passes loosely through the perforations of the flanges, and which carries at its lower end a swiveled caster 6. The nut is adapted
40 to be engaged by a wrench, which is inserted in the space between the upper and lower horizontal flanges 2 and 3. The flanges are adapted to form a support and guide for the wrench and to facilitate its ready engagement
45 with the nut, and by rotating the latter the stem may be raised or lowered, according to the direction in which the nut is rotated, to cause the roller of the caster to project below the lower end of the leg to rest upon the floor
50 or other supporting-surface to enable the stove

to be readily moved over the same and also to raise the caster above the floor to cause the leg to rest thereon to prevent any accidental movement or shifting of the stove.

The caster comprises an upper portion, 7, 55 and a lower portion, 8, and the upper portion consists of a disk and a central tubular portion, which forms a journal for the lower portion or bracket. The lower end of the stem is secured within the tubular portion and the
60 bracket or lower portion is provided with a pair of rollers 9 adapted to run on the floor, and it has at its top an antifriction-roller 10 bearing against the lower face of the disk of the upper portion. The parts of the caster
65 are secured together by a screw 11, which enters a threaded opening of the tubular portion and which secures a washer 12 to the same of greater diameter than the opening
70 which is provided in the lower portion or bracket for the reception of the said tubular portion.

It will be seen that the stove-leg is simple and inexpensive in construction, that it is strong and durable, and that the caster may
75 be readily raised and lowered to enable the stove to which it is applied to be readily moved or to rest firmly on its legs.

Changes in the form, proportion, and minor details of construction may be resorted to
80 without departing from the principle or sacrificing any of the advantages of the invention.

What I claim is—

The combination of a stove leg provided at its inner side with a pair of parallel horizontal perforated flanges or ears, a nut arranged
85 in the space between the flanges or ears, a threaded stem passing through the perforations of the flanges or ears and engaged by said nut, and a swiveled caster mounted on
90 the lower end of the stem and adapted to be raised and lowered by rotating the nut, substantially as described.

In testimony that I claim the foregoing as my own I have hereto affixed my signature in
95 the presence of two witnesses.

EDWIN L. COLE.

Witnesses:

E. G. BOUGHTON,
LENA M. BOUGHTON.