


(No Model.)

C. H. SNIVELY & J. HIRSCH.  
PLACKET FASTENER.

No. 556,070.

Patented Mar. 10, 1896.



WITNESSES:

M. B. Harris  
C. Smith

INVENTORS  
Charles H. Snively  
Jacob Hirsch  
BY  
Edgar Tate & Co  
ATTORNEYS

# UNITED STATES PATENT OFFICE.

CHARLES H. SNIVELY AND JACOB HIRSCH, OF NEW YORK, N. Y.

## PLACKET-FASTENER.

SPECIFICATION forming part of Letters Patent No. 556,070, dated March 10, 1896.

Application filed November 19, 1895. Serial No. 569,407. (No model.)

*To all whom it may concern:*

Be it known that we, CHARLES H. SNIVELY and JACOB HIRSCH, citizens of the United States, and residents of New York, in the  
5 county of New York and State of New York, have invented certain new and useful Improvements in Fastening Devices for Garments or other Articles, of which the following is a specification, reference being had to the  
10 accompanying drawings, forming a part thereof, in which similar letters of reference indicate corresponding parts.

This invention relates to fastening devices, and particularly to that class thereof which  
15 are adapted for use in closing the placket-opening of a skirt, although, as will hereinafter appear, our improved fastening device may be used for other and similar purposes.

The invention is fully disclosed in the following specification, of which the accompanying  
20 drawings form a part, in which—

Figure 1 is a view of our improved fastening device, showing the separate parts separated and in full lines, and also showing the  
25 same united in dotted lines; Fig. 2, a central transverse section of the fastening devices proper or the heads thereof, showing the method by which said parts are united; and Fig. 3, a perspective view of a cover of tape,  
30 cloth, or other material which we employ.

In the practice of our invention we provide two similar coupling heads or pieces A and B, each of which is composed of a metal plate folded in the middle, as shown at *b* and *a* in  
35 Fig. 2, and formed in the adjacent sides of said plates or heads are tongues or projections *b'* and *a'*, respectively, which are cut from the material of the plates or heads, one end and the sides thereof being cut out and  
40 the body portion being bent outwardly, as shown in Fig. 2, by which means slots or recesses *b<sup>2</sup>* and *a<sup>2</sup>* are formed, over which the tongues or projections *a'* and *b'* project.

Each of the heads or fastening devices A  
45 and B is provided with an arm D, the free ends of which are pivotally connected at G, and connected with said arms at G is a piece of tape or similar material H.

In practice we provide a cover for one of the  
50 heads or fastening devices composed of a piece

of tape, cloth, or other and similar material K, which is folded in the middle, as shown in Fig. 3, and the central portion of which is cut out, forming a longitudinal slot *k*, and, as shown in the drawings, this cover is secured  
55 to the head or fastening device B by being folded thereover and stitched thereto around the edges thereof.

The operation will be readily understood from the foregoing description, when taken in  
60 connection with the accompanying drawings.

The fastening device is secured to the skirt by means of the tape H, said tape being stitched within the skirt at the bottom of the placket-opening, or in any other desired man-  
65 ner, and the heads or fastening devices A and B are secured to the belt at the upper end of said placket-opening and at each side thereof, or they may be secured to the adjacent sides of the skirt below the belt, and when thus se-  
70 cured in position all that is necessary to lock the same together and securely close said opening is to draw the heads or fastening devices together and slightly past each other, so that the tongues or projections *a'* and *b'*  
75 may interlock, as shown in Fig. 2, and in this position the heads or fastening devices will be securely held until they are again separated by reversing the operation by which they were united.  
80

It is evident that our improved fastening device may be employed in connection with other garments or parts thereof, and our invention is not limited to the exact form, construction, and arrangement of parts herein  
85 shown and described, and we therefore reserve the right to make all such alterations therein and modifications thereof as fairly come within the scope of the invention.

Having fully described our invention, we  
90 claim and desire to secure by Letters Patent—

A placket-fastening for a skirt, comprising two separate heads, each of which is provided with an arm, the free ends of which are piv-  
95 otally connected, said heads being also provided in their corresponding sides with projections or tongues, and corresponding slots or recesses adapted to engage with each other, said heads or fastening devices being each  
100



composed of a plate of metal which is folded  
in the middle, one of said heads being pro-  
vided with a covering of tape, cloth or other  
material, having a longitudinal central slot  
5 formed therein, substantially as shown and  
described.

In testimony that we claim the foregoing as  
our invention we have signed our names, in

presence of the subscribing witnesses, this  
15th day of November, 1895.

CHARLES H. SNIVELY.  
JACOB HIRSCH.

Witnesses:

C. GERST,  
C. V. KIRCHHOFF.