




(No Model.)

J. R. PATTERSON.
COT OR BED FRAME.

No. 556,833.

Patented Mar. 24, 1896.



WITNESSES:

S. M. Holden.
C. G. Gresh.

INVENTOR

John R. Patterson
BY
Edgar S. Bates & Co.
ATTORNEYS

UNITED STATES PATENT OFFICE.

JOHN ROBERT PATTERSON, OF MOSCA, COLORADO.

COT OR BED FRAME.

SPECIFICATION forming part of Letters Patent No. 556,833, dated March 24, 1896.

Application filed December 27, 1895. Serial No. 573,554. (No model.)

To all whom it may concern:

Be it known that I, JOHN ROBERT PATTERSON, a citizen of the United States, and a resident of Mosca, in the county of Costilla and State of Colorado, have invented certain new and useful Improvements in Cot or Bed Frames, of which the following is a specification, reference being had to the accompanying drawings, forming a part thereof, in which
10 similar letters of reference indicate corresponding parts.

This invention relates to folding cots or beds, and the object thereof is to provide an improvement in this class of devices, which
15 consists of a cot or bed frame so constructed as to be entirely, quickly, and easily taken apart and the separate parts thereof folded and packed together, and which may be as quickly and as easily placed in proper form
20 for use; and with this and other objects in view the invention consists in the construction, combination and arrangement of parts hereinafter described and claimed.

The invention is fully disclosed in the following specification, of which the accompanying drawings form a part, in which—

Figure 1 is a side view of my improved cot or bed frame. Figs. 2 and 3 are perspective views of details of the construction; and Fig.
30 4 a perspective view of one end of the frame, showing the parts detached, but arranged in order to be put together.

In the practice of my invention I provide a cot or bed frame comprising sectional side
35 bars, which are preferably composed of three separate parts, A, B, and A, the parts A and A being precisely the same, and the part B constituting the central portion of the side bar of the bed-frame. The inner ends of the
40 parts A are adapted to receive the ends of the part B, and said parts may be adjustable, so as to make the bed of any desired length, and in practice I prefer to form these side bars of angle-iron, as shown in Fig. 2, the parts A be-
45 ing provided with inwardly-directed flanges a , by means of which the inner portion, B, is held in place while being free to slide within the end portions, A; and I also provide a spring a^2 , on one end of which is formed a
50 pin a^3 , which is adapted to enter a hole or opening a^4 formed in the parts A and B, so as to securely lock them together. Said hole or

opening a^4 is shown in Fig. 1, and the spring and pin are shown in Fig. 2, and also the hole or opening in dotted lines, and it will be un-
55 derstood that as many of these holes or openings as may be desired may be placed in the part B.

The outer end of each of the parts A is provided with a tubular inwardly-directed head
60 C, which is adapted to receive the end bar D, two of which are employed, and which constitute the end of the bed or cot frame, and these end bars are preferably made of tubular iron, and connected with the end of each
65 is a chain E, and I also employ end posts G, which are provided at their upper ends with eyes or rings g , through which the ends of the end bars D are adapted to be passed, and the lower ends of the end posts G are provided
70 with flattened heads g^2 , which are pivotally connected with side braces g^3 , which extend upwardly and are connected with a head g^4 of angle-iron, which is adapted to be connected with the end pieces A of the side bars
75 by means of a spring H, having a pin h at the end thereof, which passes through a hole in said head g^4 and a corresponding hole in the adjacent end piece A of the side bar.

It will be understood that the spring H is
80 secured to the part A and that the head g^4 may be detached from said part whenever desired. In coupling the end bars D and the side bars together the end of the former is passed through the ring or eye G of the corner post or posts and then into the tubular
85 head C, and the chain E is then carried around and secured to a lug or projection L; and the object of this chain is to keep said parts together when detached or not set up for use
90 as a cot or bed frame, and the end bars D are also provided with springs d^2 having pins d^3 at their outer ends which are adapted to enter holes d^4 , formed in the tubular head C, whereby said parts may be securely locked
95 together.

The body portion of the cot or bed consists of a strip or strips M of canvas or any preferred material which may be laced together
100 at m and the entire device may be taken apart and folded together or in connection with the end bars D or one of said end bars, and I also provide straps O by which when said parts are thus packed or folded together they may

be secured in such position, and in this operation the separate sections of the side bars are disconnected. The end posts are also disconnected from the side bars and the end bars and all of said parts are placed together and then the canvas or other material M is wrapped around the same and the straps O are applied thereto. It will thus be seen that I accomplish the object of my invention by means of a device which is simple in construction and which is also comparatively inexpensive and which may be folded into a compact or convenient form and which is thus capable of being easily transported from one point to another without great expense or inconvenience.

My invention is not limited to the exact form, construction and arrangement of parts herein described; and I therefore reserve the right to make all such alterations therein and modifications thereof as fairly come within the scope of the invention.

Having fully described my invention, its construction and operation, I claim as new and desire to secure by Letters Patent—

1. The herein-described bed or cot frame, which comprises side bars which are composed of sections and are adapted to be folded together, the end sections being provided with tubular heads, and end bars which are adapted to be inserted into said tubular heads, said frame being also provided with vertical legs or corner-supports, the upper ends of which are provided with rings or eyes through which the end bars are adapted to be inserted, and the bases of said supports or legs being provided with braces which are pivotally connected therewith, and which are also connected with the side bars, said parts being constructed, combined and arranged, substantially as shown and described.

2. The herein-described bed or cot frame, which comprises side bars which are composed of sections and are adapted to be folded together, the end sections being provided with tubular heads, and end bars which are adapted to be inserted into said tubular heads, said frame being also provided with vertical legs or corner-supports, the upper ends of which are provided with rings or eyes through which the end bars are adapted to be inserted, and the bases of said supports or legs being provided with braces which are pivotally connected therewith, and which are also connected with the side bars, by means of angular heads provided with holes or openings which correspond with similar holes or openings formed in the ends of the side bars, and springs connected with said side bars or the ends

thereof, and provided with pins which are adapted to enter said holes or openings, substantially as shown and described.

3. The herein-described bed or cot frame, which comprises side bars which are composed of sections and are adapted to be folded together, the end sections being provided with tubular heads, and end bars which are adapted to be inserted into said tubular heads, said frame being also provided with vertical legs or corner-supports, the upper ends of which are provided with rings or eyes through which the end bars are adapted to be inserted, and the bases of said supports or legs being provided with braces which are pivotally connected therewith, and which are also connected with the side bars, by means of angular heads provided with holes or openings which correspond with similar holes or openings formed in the ends of the side bars, and springs connected with said side bars or the ends thereof, and provided with pins which are adapted to enter said holes or openings, and the separate sections of the side bars being composed of angle-iron, and said sections being also held together by springs provided with pins which are adapted to enter holes or openings formed in the separate sections, substantially as shown and described.

4. The herein-described cot or bed frame which comprises side bars which are composed of sections which are detachably connected and adapted to be longitudinally adjusted, said side bars being composed of angle-iron, and the ends of the end sections being provided with transverse tubular heads which are adapted to receive the end bars of the frame which are tubular in form, said end bars being also provided with chains which are adapted to be passed through said transverse tubular heads, and said frame being also provided with corner legs or supports, the upper ends of which are provided with rings or eyes through which the end bars are adapted to be inserted, and the lower ends of said corner posts or supports being provided with braces which are pivoted thereto, and the other ends of which are adapted to be detachably connected with the side bars of the frame, substantially as shown and described.

In testimony that I claim the foregoing as my invention I have signed my name, in presence of the subscribing witnesses, this 19th day of December, 1895.

JOHN ROBERT PATTERSON.

Witnesses:

C. W. MORGAN,
PORTER S. GRAY.