
## G. WILLIAMS. PLANT PROTECTOR.



## United States Patent Office.

GEORGE WILLIAMS, OF ROYAL OAK, MICHIGAN.

## PLANT-PROTECTOR.

SPECIFICATION forming part of Letters Patent No. 563,532, dated July 7, 1896.

Application filed June 10, 1895. Serial No. 552,277. (No model.)

To all whom it may concern:

Be it known that I, GEORGE WILLIAMS, a citizen of the United States, residing at Royal Oak, in the county of Oakland and State of 5 Michigan, have invented certain new and useful Improvements in Plant-Protectors, of which the following is a specification, reference being had therein to the accompanying drawings.

It is the special object of my invention to provide a means for protecting young and tender plants from frosts or sudden changes of temperature in the spring of the year; and the invention consists in the peculiar con-15 struction of a protecting frame or box composed of separated side sections adapted to be quickly placed together around the plant and as readily removed when no longer needed.

Myinvention further consists in the means 20 employed for holding the ends of the box together and for securing a protecting-covering thereto, and, further, in the peculiar construction of parts whereby the device when not in use may be stored in the smallest possible 25 space, all as more fully hereinafter described.

In the drawings, Figure 1 is a perspective view of the protector-box and the securinghoop therefor. Fig. 2 is a cross-section through the device in use. Fig. 3 is an ele-30 vation of the parts in knockdown position as arranged for storing. Fig. 4 is a perspective view of one of the side sections. Fig. 5 is a section through the corner of a modified form of box. Fig. 6 is an elevation of a pro-35 tector provided with an additional upper section.

My protector consists in a box A, composed of similarly-formed side sections B, preferably four in number. Each side section is 40 formed with parallel top and bottom edges C C', and the ends D D' inclined inwardly from bottom to top.

E is an angle-groove formed at the end D, 45 otherwise secured to the side of the section and projecting beyond the end thereof.

G is an angle-groove formed at the end D', preferably by the cleat H, secured to the opposite side of the section at a distance from 50 the end D' equal to the thickness of the section. The cleats F and H serve to hold the section from warping and as they are of uni- | ceive the end of an adjacent section, and a

form thickness the sections may be conveniently piled together when not in use, as shown in Fig. 3.

The sections B may be placed around the plant to be protected, to form a box, as shown in Figs. 1 and 2, the groove E receiving the end D' and the groove G receiving the end D of the adjacent sections. The inclined ends 60 of the sections will throw their top edges in far enough to render it unnecessary under ordinary circumstances to secure the sections together, especially so if the gardener presses the bottom edge of each section into the soft 65 soil, which will hold it in position. In case, however, a strong wind is blowing, it may be necessary to lock the sections together, and this may be done by providing each with a securing device, such as a button or hook 70 and eye, but preferably by means of a hoop I, adapted to be dropped over the top of the box. This hoop I is preferably formed of jointed sections J, each provided with a hook K at one end and an eye L at the other end. 75 When not in use, the sections may be detached and thus more conveniently stored.

In Fig. 6 I have shown a box provided with an upper extension formed of sections M similar to the sections B but shorter, the lower 80 edge being equal in length to the upper edge of the section B. This may be used when the plant is taller than the width of a single box.

When it is desired to protect the plant from frost, a piece of cloth or other suitable cov- 85 ering may be placed across the top of the box and secured by the hoop I, as shown in Fig. 2. The box may also be used as a hot-bed by laying a piece of glass across the top.

Although I prefer to form the side section 90 as described the cleats E and H may be omitted and a rabbet N formed in one end of the sections, as shown in Fig. 5 of the drawings.

My protector-box may be made of any number of side sections, and thus by enlarging 95 preferably by means of the cleat F, nailed or | the angle of the grooves E and G a large bed may be surrounded with sections and thereby be protected.

What I claim as my invention is—

1. A plant-protector consisting of a box roc formed of separate side sections adapted to be placed together, each section having an angle-groove formed at its end adapted to resecuring-hoop formed of detachable jointed sections corresponding to the side sections of the box, substantially as described.

2. A plant-protector consisting of a box 5 formed of separate side sections adapted to be placed together around the plant, each section having its ends inclined inwardly from bottom to top, an angle-groove formed at the end of one section adapted to receive the end of the adjacent section and a securing-hoop

formed of detachable, jointed sections corresponding to the side sections of the box, substantially as described.

In testimony whereof I affix my signature

in presence of two witnesses.

GEORGE WILLIAMS.

Witnesses:

M. B. O'DOGHERTY, O. F. BARTHEL.