
(No Model.)

W. B. BOLTON. WASHTUB.

No. 563,908.

Patented July 14, 1896.



Statest Dates maedson 1: L. Modulm

Milliam B. Bolton by Sur Man Alter

United States Patent Office.

WILLIAM B. BOLTON, OF SHARPSVILLE, PENNSYLVANIA.

WASHTUB.

SPECIFICATION forming part of Letters Patent No. 563,908, dated July 14, 1896.

Application filed September 9, 1895. Serial No. 561,943. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM B. BOLTON a citizen of the United States, residing at Sharpsville, in the county of Mercer and State of Pennsylvania, have invented certain new and useful Improvements in Washtubs, of which the following is a specification, reference being had therein to the accompanying drawings.

My invention relates to legs for supporting washtubs, and it includes a set of removable legs, with means for adjusting the same, to permit of the raising of the tubs to various positions in order that persons of different heights may use the same with equal advantage by adjusting the legs, as will be hereinafter described.

The invention also includes the details of construction, as will be hereinafter described, and particularly pointed out in the claim.

The invention is illustrated in the accom-

panying drawings, in which—

Figure 1 is an elevation; Fig. 2, a detached sectional view of one of the legs with the attaching-plate therefor. Fig. 3 is a detail sectional view on line xx of Fig. 2. Fig. 4 is a detail view of the wedge-plate. Fig. 5 is a detail view.

A tub of ordinary construction is shown at 30 1 in the drawings, to the side of which is secured a series of plates 3, having tapered sockets formed therein. Any desirable num-

ber of these plates may be used, but in the present instance I have used but three, these being the minimum number that are neces- 35 sary. In the sockets formed in these plates 2 a wedge-shaped plate 4 is adapted to be removably held, said plate 4 carrying the socket 5 for the reception of the legs 6, which are adjustable within the same, being held 40 in adjusted position by means of the thumbscrew 7. The plates 4 may also be held within the socket of the plate 2, and prevented from falling out when the tub is lifted, by a thumbscrew 8. It will be understood that said socket 45 is tapered sufficiently to prevent the plate 4 from slipping out of the same when it is inserted therein, and that the screws 8 are not absolutely necessary, as the wedge would ordinarily be held by the frictional contact 50 between the same and the sides of the ribs 4.

Having now described my invention, what I claim is—

The combination with a washtub, of the plate secured thereto, having a tapered socket, 55 the wedge-shaped plate removably fitted thereto and carrying a second socket and the leg held therein, substantially as described.

In testimony whereof I affix my signature

in presence of two witnesses.

WILLIAM B. BOLTON.

Witnesses:

A. W. WILLIAMS, FRED SERVICE.