

(No Model.)

2 Sheets—Sheet 1.

J. T. WHITMORE.  
BOOK HOLDER.

No. 571,254.

Patented Nov. 10, 1896.





Fig. 2.



Witnessed:  
E. B. Gilchrist  
Ella E. Tilden

Inventor:  
James T. Whitmore  
By Sykes, Dore, & Ormally  
his Attorneys


(No Model.)

2 Sheets—Sheet 2.

J. T. WHITMORE.  
BOOK HOLDER.

No. 571,254.

Patented Nov. 10, 1896.



Witnesses,  
E. B. Gilchrist  
Ella E. Tilden

Inventor,  
James T. Whitmore  
By  
Sydney D. Jones & Son  
Attorneys



# UNITED STATES PATENT OFFICE.

JAMES T. WHITMORE, OF CLEVELAND, OHIO.

## BOOK-HOLDER.

SPECIFICATION forming part of Letters Patent No. 571,254, dated November 10, 1896.

Application filed April 6, 1896. Serial No. 586,326. (No model.)

*To all whom it may concern:*

Be it known that I, JAMES T. WHITMORE, of Cleveland, Cuyahoga county, Ohio, have invented certain new and useful Improvements in Book-Holders; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it pertains to make and use the same.

My invention relates to improvements in book-holders; and it consists in certain features of construction and combinations of parts hereinafter described, and pointed out in the claims.

In the accompanying drawings, Figure 1 is a view in perspective of a magazine or book to which my improved book-holder is applied. Fig. 2 is an end plan showing the lower edge of the book and the book-holder from below. Fig. 3 is a front or top side elevation of my improved book-holder. Fig. 4 is a right-hand side elevation relative to Fig. 3. Fig. 5 is rear side elevation of the device. Fig. 6 is a transverse section on line 6-6, Figs. 3 and 4, looking upwardly. Fig. 7 is a transverse section on line 7-7, Figs. 3 and 4, looking upwardly.

My improved book-holder is composed, preferably, of metallic pieces. A wire bent to form two parallel members A A, that are located a suitable distance apart, has its central portion *a* forming the lower end or handle of the book-holder. Two cross-bars B and B' connect together and are suitably secured to members A A. Cross-bar B' is located, preferably, a short distance above the handle, and cross-bar B is located, preferably, near the upper ends of members A A. Each cross-bar B and B', at its central portion and forward side, has two forwardly-converging shoulders *b b'*, that are adapted to form a bearing for the back of the book held by the holder, and shoulders *b* or shoulders *b'* form the back-bearing for the book, according as the latter turns or swings laterally in the one direction or the other. Members A A and cross-bars B B' therefore constitute a frame having bearings for the book's back. Another bar or member D, arranged centrally between and parallel with members A A, extends centrally through and is rigidly secured to cross-bars B B'. Member D is composed,

preferably, of a piece of wire that extends a suitable distance below the lower cross-bar B' and is long enough to render it capable of being bent upwardly at a point below said cross-bar, and thereby form a spring-hook or spring-jaw *d*, adapted to enter the book to be held by the device and press the book against the back-bearing-forming members of the book-holder.

A cylindrical tubular member E, arranged parallel with members D and A A, is soldered or otherwise rigidly secured to the rear side of said member D and the lower cross-bar B'. Within tube E is journaled an oscillating leaf-holder that is composed, preferably, of a piece of wire G, having bearing in said tube E and extending below said tube and bent upwardly below the tube to form a spring-jaw *g*, adapted to enter between adjacent leaves of a book and hold said leaves in place and provided at its upper end with two arms *g' g'*, projecting laterally in opposite directions, respectively, and adapted to engage and hold apart said leaves.

The leaf-holder G is movable endwise of the tube E, in which it is journaled, and is lowered to free the engaged leaves preparatory to turning one of said leaves, and is again elevated after the leaf has been turned to hold said leaf in place. The capability of the leaf-holder to oscillate accommodates the swinging of the book laterally from shoulders or bearings *b* to bearings *b'*, or vice versa.

What I claim is—

1. A book-holder comprising a frame provided with bearings for the back of a book, and terminating, at its lower end, in a handle, and provided, furthermore, with a spring-hook or spring-jaw at the forward side and at or near its lower end, substantially as and for the purpose set forth.

2. A book-holder comprising two parallel members A A forming a handle at the lower end of the device, two cross-bars B B' connecting together, and rigidly secured to, said parallel members and arranged a suitable distance apart above the handle and provided, on their forward sides, with bearings for the back of the book, and a suitably-formed spring-hook or spring-jaw at the forward side of the device above the handle, substantially as and for the purpose set forth.



3. A book-holder comprising two parallel members A A forming a handle at the lower end of the device, two cross-bars B B' connecting together and rigidly secured to said parallel members and arranged a suitable distance apart above the handle and provided, on their forward sides and centrally, with two forwardly-converging bearings *b b'* for the back of the book, and a suitably-formed spring-hook or spring-jaw at the forward side of the device above the handle, substantially as set forth.

4. A book-holder consisting of a wire bent to form the two parallel members A A and the handle *a*; the cross-bars B B' connecting together, and rigidly secured to, said parallel members, and provided, upon their forward sides, with bearings for the back of the book, and another wire extending centrally through said cross-bars and bent to form the spring-hook or spring-jaw *d*, all arranged and operating substantially as shown, for the purpose specified.

5. A book-holder comprising a frame pro-

vided with bearings for the back of a book, and terminating, at its lower end, in a handle, and provided, furthermore, with a jaw at or near its lower end and forward side, a cylindrical tube rigid with and arranged longitudinally of said frame, and the oscillating leaf-holder comprising a member having bearing in, and movable endwise of, said tube, substantially as and for the purpose set forth.

6. A book-holder comprising a cylindrical stationary tube arranged longitudinally of the device, an oscillating wire journaled in and movable endwise of said tube, and bent at a point below said tube to form the spring-jaw *g*, and the arms *g' g'* projecting laterally from opposite sides, respectively, of said jaw, substantially as and for the purpose set forth.

In testimony whereof I sign this specification, in the presence of two witnesses, this 2d day of April, 1896.

JAMES T. WHITMORE.

Witnesses:

C. H. DORET,  
ELLA E. TILDEN.