

(No Model.)

P. E. GUÉRARD.
HOSE COUPLING.

No. 571,361.

Patented Nov. 17, 1896.

FIG. 1.




FIG. 2.





FIG. 3.



Witnesses

F. Laberge

J. Patenaude

Pierre Etienne Guérard, Inventor

By Attorney

J. A. Marion

UNITED STATES PATENT OFFICE.

PIERRE ETIENNE GUÉRARD, OF MONTREAL, CANADA, ASSIGNOR OF ONE-HALF TO NAPOLEON MATHIEU, OF SAME PLACE.

HOSE-COUPLING.

SPECIFICATION forming part of Letters Patent No. 571,361, dated November 17, 1896.

Application filed May 21, 1896. Serial No. 592,377. (No model.)

To all whom it may concern:

Be it known that I, PIERRE ETIENNE GUÉRARD, a citizen of the Dominion of Canada, residing at Montreal, in the district of Montreal and Province of Quebec, Canada, have invented certain new and useful Improvements in Hose-Couplings; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

This invention relates to hose-couplings; and it consists in the novel construction and combination of the parts hereinafter fully described and claimed.

In the drawings, Figure 1 is a longitudinal section through the hose-coupling with the guard-pipe broken away to show the spring-fingers. Fig. 2 is a cross-section taken on the line *xx* in Fig. 1. Fig. 3 is a longitudinal section through one half of the coupling between the spring-fingers, showing the guard-pipe in position.

A is the outer half of the coupling, which is provided with a cylindrical end portion *a'*, having a shoulder for the end of one section of the hose-pipe to engage with. The front end of the part A has an internal shoulder B, a conical ring B' of india-rubber or other soft material, and an annular groove *b* between the said ring and shoulder. The ring B' is secured in the part A in any approved manner.

C is the inner half of the coupling provided with a shoulder for the other section of the hose-pipe to engage with in the usual manner. The front end of the part C is provided with a conical portion *c'* for bearing against the ring B' when the parts A and C are pressed together. The part C has a series of longitudinal slots D, and *d* is a series of spring-fingers having their rear ends secured to the rear end of the part C in any approved manner.

The fingers *d* each have two inclined projections *e* and *e'*, which project through the slots D, and *f* is a notch between the said projections. The outer surfaces of the projections are inclined in opposite directions, and the projections have their high ends next to the notch between them.

G is a ring which is slidable on the part C of the coupling behind the projections *e'*. When the parts of the coupling are pressed together, the projections *e* spring into the groove *b* and hold the two parts of the coupling securely connected together. When the sections of the hose-pipe are to be separated, the ring G is slid upon the projections *e'*, so that the projections *e* are pressed inward until clear of the shoulder B. This permits the halves of the coupling to be separated.

A guard-pipe *g* is secured inside the part C to prevent water from passing out of the slots D.

What I claim is—

1. In a hose-coupling, the combination, with one half of the coupling provided with a shoulder at its front end and an annular groove behind the said shoulder; of the other half of the coupling provided with a series of longitudinal slots, a series of spring-fingers each having two inclined projections extending through the slots, and notches between the said projections; and a slidable ring for pressing inward the said spring-fingers, substantially as set forth.

2. In a hose-coupling, the combination, with one half of the coupling provided with a conical ring of soft material, a shoulder at its front end, and an annular groove between the said shoulder and ring; of the other half of the coupling provided with a conical front end for bearing against the said ring, a series of longitudinal slots, a series of spring-fingers each having two inclined projections extending through the said slots, and notches between the said projections; and a slidable ring for pressing inward the said spring-fingers simultaneously and releasing the halves of the coupling, substantially as set forth.

In testimony whereof I affix my signature in presence of two witnesses.

PIERRE ETIENNE GUÉRARD.

Witnesses:

F. C. LABERGE,
T. J. PATENAUDE.