


(No Model.)

C. A. & W. E. METZGER.
AWNING.

No. 572,434.

Patented Dec. 1, 1896.



WITNESSES:

Henry T. Hensch.
J. H. Hensch.

INVENTORS
C. A. Metzger.
W. E. Metzger.
BY
Munn & Co.
ATTORNEYS.

UNITED STATES PATENT OFFICE.

CHARLES A. METZGER AND WILLIAM E. METZGER, OF RUTLAND,
VERMONT.

AWNING.

SPECIFICATION forming part of Letters Patent No. 572,434, dated December 1, 1896.

Application filed February 18, 1896. Serial No. 579,739. (No model.)

To all whom it may concern:

Be it known that we, CHARLES A. METZGER and WILLIAM E. METZGER, of Rutland, in the county of Rutland and State of Vermont, have
5 invented a new and useful Improvement in Awnings, of which the following is a full, clear, and exact description.

Our invention relates to an improvement in awnings; and the object of the invention
10 is to provide a means for hanging the awning which will be simple, durable, and economic and whereby the hanging devices attached to the awning need not be removed from the awning when said awning is disconnected
15 from its support, and whereby, further, the said hanging devices will be securely and fixedly attached to said awning.

A further object of the invention is to provide an awning with a device whereby when
20 it is drawn upward the folds of the awning will not interfere with the pulley through which the draw-rope passes or with the rope itself, and to so attach such a device to the awning that it will not detract from its ap-
25 pearance.

Another object of the invention is to construct hangers adapted to receive the hanging devices attached to the awning, the said hangers being especially adapted for attach-
30 ment to an iron rod or a rigid rod of any material adapted as a support for the awning, the hangers being so made that they may be attached or fixed at any point on the rod or conveniently and expeditiously removed from
35 said rod and disconnected from the hanging devices of the awning.

The invention consists in the novel construction and combination of the several parts, as will be hereinafter fully set forth,
40 and pointed out in the claims.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar characters of reference indicate corresponding parts in all the figures.

45 Figure 1 is a front elevation of a portion of an awning, illustrating the application of the improvement. Fig. 2 is a section taken substantially on the line 2 2 of Fig. 1. Fig. 3 is a detail perspective view of one of the im-
50 proved hangers, and Fig. 4 is a detail perspective view of the upper marginal portion

of the awning and a hanging device secured at that point.

In carrying out the invention the awning A may be of any desired shape or material, and
55 it is provided with the usual hem B at its top, through which hem a rope or cord 10 is made to pass. The hanging devices for the awning consist of loops 11, preferably made of metal, the extremities of the members of which are
60 passed through the awning at the hem and around the rope or cord 10, as shown in Fig. 4, being bent over the hem portion of the awning in such manner that they will be
65 clamped or firmly secured thereto.

The hangers for the awning are adapted particularly for engagement with a rod C, made of metal or a like material. Each hanger consists of a yoke 12, preferably made
70 of strap metal, having at the lower end of one of its members a pin 13, either attached to or formed integral with the yoke, and the opposite member of the yoke is made sufficiently long to admit of an opening 14 being
75 made therein, adapted to receive the pin 13. The members of the yoke are drawn together, so that the pin will connect the two members, by means of a bolt 15, secured preferably in
80 the member carrying the pin and passing loosely through the member having the opening 14 made therein, and the said bolt at its free end is provided with a nut 16, preferably
85 of the wing character, as illustrated. When the nut is loosened, the yoke-body of the hanger may be passed over the hanging or supporting rod C, and when the nut is tight-
90 ened the members of the yoke-body of the hanger will be firmly clamped to the rod, the hanger thereby remaining in the position in which it was placed.

The pins 13 of the hanger are adapted to be
passed through the loops or staples 11, at-
tached to the awning, and by this means the
awning is suspended from the said hangers
in a convenient manner, and upon loosening
95 the nut 16, admitting of the members of the hanger separating and thereby withdrawing the pin 13 from the opening 14, the loops or staples 11 may be readily withdrawn from
100 the hanger with which they were connected.

A pulley 17 is provided, as is ordinary, to accommodate the draw rope or cord 18, par-

particularly adapted for raising the awning or carrying it to its folded position. The pulley 17 is provided with an eye, through which a pin 13 of one of the hangers is passed, and the draw-rope is carried downward through the usual guide-rings 19.

An outwardly-curved spring 20, usually of a general rectangular contour, is secured to the awning by means of a cover strip or flap 21, as shown in Fig. 1, at that portion of the awning which is adjacent to the pulley 17 and the pull rope or cord 18 adjacent to the pulley, as is best shown in Fig. 2. The said spring 20 usually consists of a wire of suitable resiliency, which is bent upon itself to form a skeleton frame, being curved in an outwardly direction.

Under this construction it is obvious that when the rope or cord 18 is operated to draw the awning upward or fold the same the material of the awning adjacent to the pulley will be held out of engagement therewith, and consequently the awning cannot interfere with the action of the pulley or the rope or cord 18, permitting the awning being raised with much less expenditure of strength than heretofore and to a greater height and a more compact folding.

Having thus described our invention, we claim as new and desire to secure by Letters Patent—

1. An awning provided with an expansion-spring opposite the pulley through which the draw-rope of the awning is passed, the said spring acting to hold the awning free from the said pulley, as and for the purpose specified.

2. The combination, with a rod-support, of a hanger of substantially yoke formation, one member of the hanger being provided with a

pin and the other member with an opening to receive the pin, and a device for drawing the members together, as and for the purpose specified.

3. The combination, with a supporting-rod, of a hanger comprising a yoke-like body of a spring material, having a pin near one extremity of one member, extending in direction of the opposite member, the said opposite member being provided with an opening to receive the said pin, a bolt secured in the pin-carrying member of the hanger, loosely passed through the opposing member, and a nut located upon the free end of the said bolt, adapted for engagement with the apertured member of the yoke-body of the hanger, as and for the purpose specified.

4. The combination, with a support, a yoke-like hanger provided with a pin attached to one member, and a keeper upon its opposite member, receiving the said pin, and a tension device adapted to contract the members of the hanger, or admit of the expansion of the same, of an awning, and a staple secured to the marginal portion of the said awning, through which staple the pin of the hanger is adapted to be passed, as and for the purpose specified.

5. An awning-hanger, consisting of a yoke provided with a pin projecting from one member and an opening in the other member to receive the pin, and a bolt for drawing the members of the yoke together, substantially as described.

CHARLES A. METZGER.
WILLIAM E. METZGER.

Witnesses:

WALTER G. OTIS,
HORACE A. BATCHELDER.