

(No Model.)

R. F. SPENCER.
HARNESS.

No. 573,306.

Patented Dec. 15, 1896.

FIG. 1.




FIG. 2.





FIG. 3.



Witnesses:

Chas. R. Cross.
John H. Hurley.

Inventor:

Inventor:
Ripley F. Spencer
By his Attorneys
Winkler Henders Smith Portsmouth

UNITED STATES PATENT OFFICE.

RIPLEY F. SPENCER, OF ASHLAND, WISCONSIN.

HARNESS.

SPECIFICATION forming part of Letters Patent No. 573,306, dated December 15, 1896.

Application filed March 18, 1896. Serial No. 583,801. (No model.)

To all whom it may concern:

Be it known that I, RIPLEY F. SPENCER, of Ashland, in the county of Ashland and State of Wisconsin, have invented certain new and useful Improvements in Harness; and I do hereby declare that the following is a full, clear, and exact description of the invention, which will enable others skilled in the art to which it pertains to make and use the same, reference being had to the accompanying drawings, and to the letters of reference marked thereon, which form a part of this specification.

My improvements relate to that class of harness which are designed particularly for use with light vehicles, such as gigs and sul- kies, and comprising, in connection with a saddle and girth; draft and holdback straps attached to the saddle and extending rear- wardly and forwardly therefrom in place of the usual breast-collar, traces, and breeching.

The main objects of my invention are to encumber the animal with as little weight and as few straps as possible, and thus allow perfect freedom of movement, to insure the proper support of the vehicle-shafts and thus prevent accidents, and to admit of the use of any suitable harness-saddle not specially made for the purpose, whereby an old saddle that has been broken to the animal may be utilized for the purpose.

It consists of certain novel features in the construction and arrangement of component parts of the harness, as hereinafter particu- larly described, and pointed out in the claims.

In the accompanying drawings like letters designate the same parts in the several fig- ures.

Figure 1 is a general perspective view of a harness embodying my improvements as ap- plied in practice. Fig. 2 is a front elevation, on an enlarged scale, of a harness-saddle to which my improvements are applied; and Fig. 3 is a side elevation of the same.

A designates an ordinary harness-saddle of the kind commonly employed in light harness. It is provided with the belly-band or girth B and with terrets *g g* and check-hook *h* in the usual way.

a is a safety-strap constituting a part of my improvements. It extends over the saddle and is secured thereto by the terrets *g g*, which

are first removed from the saddle and then screwed into it through holes made therefor in said strap.

d d are metal pieces riveted or otherwise se- curely attached to the safety-strap *a* on each side of the saddle below the terrets *g g*. They are formed at the sides with loops or openings for the attachment of the draft and holdback straps, as hereinafter explained, and with one or more loops or openings for the passage of the saddle-bearers when the saddle is pro- vided with these appendages.

The safety-strap *a* is preferably extended in width where the metal pieces *d d* are at- tached thereto, so as to form a suitable base or bearing therefor, as shown in Fig. 3.

b b are straps, usually called by harness- makers "saddle-bearers," with which har- ness-saddles of this class are usually provided. They are secured at their upper ends to the saddle usually by inserting them through transverse slits in the backs of the saddle- pads and passing the terrets through them. In connection with my improvements these saddle-bearers are passed outwardly through openings in the safety-strap *a* and through openings or loops in the upper parts of the metal pieces *d d*, thence inwardly through loops or openings in the lower parts of said metal pieces, so that their lower ends lie over and parallel with the corresponding ends of the safety-strap *a*, as shown in Fig. 2.

C C are shaft loops or tugs adjustably se- cured by buckles *c c* to the lower ends of both the safety-strap *a* and the saddle-bearers *b b*.

For the purpose of lightness and to prevent corrosion the metal pieces *d d* may be made of aluminium. The upper loop or opening therein may be omitted and the metal pieces themselves may be altogether dispensed with, the draft and holdback straps being attached to the safety-strap by any other suitable means. I prefer, however, to use the metal pieces for this purpose, as they afford a strong fastening and a neat and attractive finish.

e and *f* are holdback and draft straps, re- spectively, such as are employed in this style of speeding-harness in place of the ordinary breast-collar, traces, breeching, and hold- backs. They are secured in the side loops or openings of the metal pieces *d d* and extend forwardly and rearwardly therefrom for at-

tachment to the front and rear ends of the vehicle-shafts. The holdback-straps *e* are preferably provided in the usual manner with sockets, as shown in Fig. 1, to pass over the front ends of the shafts, and the draft-straps *f* may be fastened at their rear ends to a whiffletree or directly to the shafts or cross-bar.

By means of the safety-strap *a* I am enabled to readily apply my improvements to any suitable saddle not specially constructed for the purpose. This is not only a matter of economy, but enables me to utilize saddles which have been used, broken, or fitted and are therefore generally preferred to new saddles, which are stiff and uncomfortable. It also insures against accidents by holding the vehicle-shafts up in place in case the ordinary saddle or parts thereof break, which is very liable to occur, particularly with old harness, preferably employed for speeding purposes on account of its flexibility and ease.

I do not wish to be understood as limiting myself to exact details of construction herein shown and described, as they may be modified within the intended scope of my invention.

I claim—

1. In harness the combination with a saddle, of a safety-strap extending over and se-

cured to the saddle, saddle-bearers attached to the saddle and passing outwardly through openings in said safety-strap, shaft tugs or loops attached to said safety-strap and saddle-bearers, and draft and holdback straps attached to said safety-strap above the shaft-tugs, substantially as and for the purposes set forth.

2. In harness the combination with a saddle, of a safety-strap extending over and secured to said saddle, metal pieces attached to said safety-straps and formed with loops or openings, saddle-bearers attached at their upper ends to the saddle and passing through said safety-strap and openings or loops in said metal pieces, shaft tugs or loops attached to the ends of said safety-strap and saddle-bearers and draft and holdback straps attached to the side loops of said metal pieces, substantially as and for the purposes set forth.

In testimony that I claim the foregoing as my own I affix my signature in presence of two witnesses.

RIPLEY F. SPENCER.

Witnesses:

B. E. WEBB,

J. WHIT POTTER.