

(No Model.)

P. J. LEONARD & W. HEAD.
LOCK.

No. 574,250.

Patented Dec. 29, 1896.





Fig. 2.



WITNESSES:

Edward Thorpe
J. H. Sappington

INVENTORS

INVENTORS
C. J. Leonard
W. Head

BY

Murray
ATTORNEYS.

UNITED STATES PATENT OFFICE.

PATRICK J. LEONARD AND WILLIAM HEAD, OF NEW YORK, N. Y.

LOCK.

SPECIFICATION forming part of Letters Patent No. 574,250, dated December 29, 1896.

Application filed May 11, 1896. Serial No. 591,076. (No model.)

To all whom it may concern:

Be it known that we, PATRICK J. LEONARD and WILLIAM HEAD, of New York city, in the county and State of New York, have invented 5 new and useful Improvements in Locks, of which the following is a full, clear, and exact description.

This invention relates to certain improvements in locks, and has for its object to provide a lock of a simple and inexpensive construction which shall be especially adapted for use on milk-cans and similar receptacles to hold the cover or lid of the can against accidental or unauthorized removal.

15 The invention consists in a lock comprising two parts, one adapted to be inserted in the other and provided with tongues, and a bolt having a conical thread to screw in the inner part of the lock and arranged to expand said 20 tongues against the inside of the outer part of the lock to hold the two parts against separation.

The invention also contemplates certain novel features of the construction, combination, and arrangement of the various parts of the improved lock, whereby certain important advantages are attained, and the device is made simpler, cheaper, and otherwise better adapted and more convenient for use than 30 similar devices heretofore employed, all as will be hereinafter more fully set forth. The novel features of the invention will be carefully defined in the claims.

Reference is to be had to the accompanying 35 drawings, forming a part of this specification, in which similar characters of reference indicate corresponding parts in both the views.

Figure 1 is a fragmentary sectional view taken through the upper part of a milk-can, 40 showing the cover or lid secured in place thereon by means of a lock constructed in accordance with our invention; and Fig. 2 is a fragmentary view showing an under side plan, the cover or lid having an inner section 45 or part of the lock secured thereto.

In the views, 1 indicates the body portion of a milk-can, which may be of the ordinary or any preferred construction, having a neck 2 at its upper end, with an expanded lip 3, 50 and 4 indicates the cover or lid of the can, having a central cylinder 5 projecting from

its under side and adapted to fit snugly within the neck 2 of the can.

The lower section or part of the lock is provided with a plate or head 6, adapted to be 55 riveted to the under side of the lip 3 of the milk-can, and on said plate is formed an upwardly-projecting tubular portion 7, extending through an opening formed in the lip 3 and having its opposite ends open. The lower 60 end 8 of the tubular portion 7 of the lower section or part of the lock opens at the under side of the rim or lip 3 of the can, and since the plate 6 is arranged to stand at an angle to the part 7, so as to fit against the under 65 side of the inclined lip, said lower end 8 is made somewhat enlarged, so as to permit the ready insertion of a key for opening or closing the lock.

In the hollow of the lower portion 7 of the 70 lock is arranged to fit the body portion 9 of the upper part or section, said upper part or section being formed at its upper end with an elongated plate 10, riveted, as indicated at 11 in Fig. 2, to the upper surface of the 75 milk-can cover or lid 4. The body portion 9 of said upper section or member is made hollow at its lower end and is provided with interior screw-threads, as clearly shown in Fig. 1. 80

The lower end of the body portion 9 of the upper section or part of the lock is provided with longitudinal slits 12, extending through the screw-threaded portion, and in the lower 85 end of said body portion 9 is arranged to screw the bolt 13, having conical screw-threads on its surface, and provided at its lower end with a square or head 14, adapted to be engaged by a wrench or tool inserted at the lower open 90 end 8 of the lower section or part of the lock, whereby the lock may be opened or closed.

In operation, when the cover or lid 4 of the can is put in place, the body portion 9 of the upper section of the lock is inserted in the hollow of the part 7 of the lower section in 95 the position indicated in Fig. 1, after which a key or wrench of any desired kind is inserted at the open lower end 8 of the lower section in position to engage the square 14 on the lower end of the bolt 13, so that said bolt may 100 be turned or screwed into the hollow of the body portion 9 of the upper section.

The body portion 9 of the upper section being longitudinally slitted and the screw-threaded portion of the bolt 13 being made conical, it will be evident that the bolt will
5 serve to expand the slitted or tongued lower end of the upper section, so as to hold the same securely locked with the lower section, whereby the removal of the cover or lid 4 will be prevented until after the bolt 13 has been
10 unscrewed.

From the above description it will be seen that the improved lock is of an extremely simple and inexpensive nature, and is especially well adapted for the purposes for which it is
15 designed, and it will also be readily understood that the invention is susceptible of some modification without material departure from its principles and spirit, and that it may be employed for various purposes other than
20 holding the lids or covers of milk-cans in place. For this reason we do not wish to be understood as limiting ourselves to the exact form and arrangement of the various parts herein set forth.

25 Having thus described our invention, we claim as new and desire to secure by Letters Patent—

1. The combination with a can, of a lock comprising a tubular part attached to a portion of the can, an expanding part secured to
30 another portion of the can and adapted to en-

ter the tubular part and a screw-plug for expanding the expanding part, substantially as specified.

2. The combination with a milk-can comprising a body portion and cover, of a lock consisting of a tubular section secured to the body portion of the can, a hollow section secured to the cover of the can and adapted to enter the tubular section, the said hollow section being longitudinally split and provided with an interior screw-thread, and a bolt having a conical screw-threaded portion to engage the thread of the hollow section and expand the same, substantially as specified. 45

3. The combination of a milk-can having a body portion and a cover, an outwardly-extended lip on the neck of the body portion, a tubular lock-section having its lower end expanded in an opening in said neck, a hollow section attached to the cover, and adapted to enter the tubular section, the body portion of the hollow section being longitudinally split and having an interior screw-thread and an expanding-bolt for engaging said screw-
55 thread, substantially as specified.

PATRICK J. LEONARD.
WILLIAM HEAD.

Witnesses:

JOHN WALLACE,
WILLIAM ALLEN.