

(No Model.)

P. MULLANE.  
HOSE SUPPORTER.

No. 581,868.

Patented May 4, 1897.




Fig. 4.




Fig. 2.




Fig. 5.





Fig. 3.



Witnesses  
Norris A. Clark.  
John R. Taylor.

Inventor  
Patrick Mullane  
By his Attorneys  
Dyer & Driscoll

# UNITED STATES PATENT OFFICE.

PATRICK MULLANE, OF MOLINE, ILLINOIS.

## HOSE-SUPPORTER.

SPECIFICATION forming part of Letters Patent No. 581,868, dated May 4, 1897.

Application filed May 28, 1896. Serial No. 593,381. (No model.)

*To all whom it may concern:*

Be it known that I, PATRICK MULLANE, a citizen of the United States, residing at Moline, in the county of Rock Island and State of Illinois, have invented a certain new and useful Improvement in Hose-Supporters, of which the following is a specification.

My invention relates to improvements in hose-supporters where, by the addition of a simple but very effective device to a well-known form, a hose-supporter is produced which is far more convenient to attach to the hose and which cannot become detached accidentally, while being as little liable to tear the fabric as any of the old forms.

In the old form it is necessary to use the thumb and finger of one hand to pull the fabric through the broader part of the opening and then to slip the fabric into the slit by pulling up upon the supporter with the other hand. If hurriedly done, the fabric is apt not to crowd into the slit sufficiently to stay, but works out, detaching the supporter.

By means of my improvement the hose-supporter may be attached to the stocking with the use of one hand only, the fabric being automatically lifted as it is drawn into the slit, where it is held without the possibility of becoming detached.

My supporter has another feature to recommend it. The pin which is used to catch up the fabric has its point completely guarded when in normal position from sticking into or tearing anything which may brush against it. The pin in my supporter is unlike the pins in somewhat similar forms in not being used to support the stocking, the slit in the main body of the supporter performing that function when the supporter is attached. The pin simply guides the fabric into position to be gripped by the sides of the slit, and when the fabric is so gripped the pin supports little or none of the strain. Thus while keeping the fabric from slipping through and becoming detached from the garter the tearing of the fabric is avoided, which always results when a sudden strain is put upon the stocking held by any supporters bearing the strain upon pins or roughened edges.

In the drawings accompanying this descrip-

tion, wherein like letters of reference indicate similar parts, Figure 1 shows a view of the under side of the hose-supporter. Fig. 2 shows a section of the supporter cut through the line 2 2, Fig. 1. Fig. 3 shows a section of the supporter cut through the line 3 3, Fig. 1; and Figs. 4 and 5 show sections, like Fig. 3, of modified forms of my supporter.

The body of the supporter is well known in form, being a plate A, of appropriate shape, in which is an opening B, broad at the top and narrowing into a slit C at the bottom A' of the plate. The top A<sup>2</sup> of the plate forms a bar, to which the web of the elastic or other material which supports the stocking is attached. A pin D is attached to the plate A just below the end of the slit C and extends upward over the slit to the broad portion of the opening B, where it is bent down into the opening and has its point directly beneath the bar A<sup>2</sup> and pointing toward it. The bar A<sup>2</sup>, with its attached web, forms an efficient guard for the point of the pin when in normal position. This, together with the sides of the opening B, absolutely prevents it from accidentally catching in or tearing any material near it.

The operation of my improved supporter is as follows: Instead of drawing the fabric with the thumb and finger through the broad opening B, as one must do in the ordinary supporter when it is desired to fasten it to the stocking, the point of the pin is depressed below the face of the supporter and the supporter is drawn up. The pin engages with the fabric of the stocking until sufficient has been taken upon its point, when it is released and springs back into position. The upward movement of the garter forces the fabric along the pin, and as it reaches the bent portion of the pin the fabric is raised above the level of the garter, slipping easily over the slight curves in the pin. The fabric is now ready to be engaged by the slit and as it travels along the pin it is crowded down into the slit, the sides of which grip it and take any additional strain which may be put upon the supporter. Consequently it will be seen that the pin does nothing more than engage the fabric and automatically raise it into position to be fastened in the slit as it travels along the pin toward the slit. To release the stocking, it is



merely necessary to push down the garter, when the fabric will slip along the pin and off its point.

The modifications of my supporter shown in Figs. 4 and 5 are fastened and detached in the same manner as above described. In Fig. 4 the pin D is straight, but in order to guard its point the plate A is bent so as to bring the bar A<sup>2</sup> over such point. The relation of the pin D to the slit C is the same in all modifications, thus retaining the feature which distinguishes it from other pin-supporters and serves to make it so much less destructive to the fabric. In Fig. 5 the point of the pin is in the same position and is guarded as in Fig. 4, but the pin has a hump E, which lies just over the place where the part B of the aperture narrows down into the slit C. This hump serves three purposes—first, to make a raised point for the finger to press upon when it is desired to insert the point of the pin in the fabric; second, to prevent more effectively the accidental detaching of the supporter when the fabric is once caught in the slit, and, third, to raise the fabric just as it enters the slot and is gripped by the sides thereof. This hump thus serves to take all the strain off the pin after the fabric has passed over it.

What I claim is—

1. In a hose-supporter, the combination with a frame provided with a wide opening for entering the fabric, said opening terminating in a narrow slit for supporting and holding the fabric of a guide-pin extending over said slit and into the wide opening, its point being in substantially the same plane with the inner edges of the wide opening of the frame, whereby the fabric may be readily caught, substantially as set forth.

2. In a hose-supporter, the combination with a flat frame provided with a wide opening for entering the fabric, said opening terminating in a narrow slit for supporting and holding the fabric of a guide-pin extending from the rear end of said narrow slit over said slit and forward toward the wide opening and being bent down so as to be in substantially the same plane with the edges of the frame, whereby the pin-point is protected and the fabric may be readily caught, substantially as set forth.

This specification signed and witnessed this 25th day of May, 1896.

PATRICK MULLANE.

Witnesses:

C. CHRISTOPHER,  
CHAS. J. DUNN.