




(No Model.)

J. ZIEGLER.  
NECK YOKK.

No. 589,325.

Patented Aug. 31, 1897.



Inventor  
*Jacob Ziegler*

Witnesses

E. A. Monroe

By *his* Attorneys,

*W. S. Shepard.*

Cashover.



# UNITED STATES PATENT OFFICE.

JACOB ZIEGLER, OF ARLINGTON, NEBRASKA.

## NECK-YOKE.

SPECIFICATION forming part of Letters Patent No. 589,325, dated August 31, 1897.

Application filed January 12, 1897. Serial No. 618,996. (No model.)

*To all whom it may concern:*

Be it known that I, JACOB ZIEGLER, a citizen of the United States, residing at Arlington, in the county of Washington and State of Nebraska, have invented a new and useful Neck-Yoke, of which the following is a specification.

My invention relates to neck-yokes, particularly to the coupling-rings thereof, by which the neck-yoke is secured to the wagon-tongue.

My object is to provide a neck-yoke coupling that will interlock with the cap or tip on the tongue, that will tend to keep the neck-yoke in proper vertical position, and that is adjustable to different sizes of neck-yokes.

Accordingly my invention consists of the details and combinations of parts, as hereinafter described and claimed.

In the accompanying drawings, Figure 1 is a perspective view of a neck-yoke with my improved coupling. Fig. 2 is a cross-section thereof. Fig. 3 is a rear elevation of the coupling.

Similar numerals of reference designate corresponding parts in the several figures of the drawings.

Reference-numeral 1 designates the ordinary neck-yoke. Secured to the middle of said yoke is a pair of pivot-plates 2, one on the upper side and one on the under side, diametrically opposite to each other. These plates are curved on their under surface to correspond to the oval of the neck-yoke, to which they are secured by screws or bolts at either end, and are flat at their outer middle portion 3 to provide a bearing-surface for the inside of ring 4, which is centrally perforated at 5 5 through the enlarged portions 6 6 to receive the stub-pivots 7 7 of plates 2.

Ring 4 is preferably elliptical in shape, so as to accommodate neck-yokes of different widths, and at its lower outer portion carries a tongue-collar 8. This collar 8 is preferably formed in one piece with ring 4, connected thereto by a strong neck portion 9, and projects forward transversely thereto in a plane oblique to the ring-pivots 7. This collar 8 is perforated at 10, in line with the wagon-

tongue, so as to form a skew collar projecting normally back from the bottom of the tongue to the top. At its bottom edge collar 8 is thickened and provided with a rearwardly-extended hook 12, whose upturned end 13 is adapted to normally engage with the retaining-lip formed ordinarily on the under side of the wagon-tongue tip or cap.

In use my neck-yoke coupling is secured, as shown, on a neck-yoke at its middle portion. The neck-yoke is then turned vertically and collar 8 is sleeved over the end of the tongue till the hook 12 comes opposite the under lip-of the tongue, when the neck-yoke is turned over horizontally on top of the tongue. This movement engages the upturned end 13 of the hook behind the said lip and secures the neck-yoke against accidental disengagement from the tongue. The fact that collar 8 is not in line with the pivots of the ring 4, but slants outwardly therefrom and is secured thereto at the lower front end thereof, prevents the neck-yoke from rolling over out of its proper vertical position by the pull of the horses.

I believe myself to be the first to devise a neck-yoke coupling consisting of two parts or members rigidly connected together, one part embracing and detachably engaging the tongue and the other made in the form of a ring to encircle the neck-yoke and provide a bearing therefor.

Changes in the form, proportion, and minor details of construction may be resorted to without departing from the spirit or sacrificing any of the advantages of this invention.

What I claim as my invention, and desire to secure by Letters Patent, is—

A neck-yoke coupling comprising a collar designed to encircle a tongue, disposed at a backward inclination and provided at its bottom with a hook extending rearward and adapted to interlock detachably with the tip of the tongue, the rearwardly-inclined neck extending upward from the top of the collar and rigid with the same, and the rearwardly-extending longitudinally-disposed ring arranged horizontal and formed integral with the neck and being rigid with the inclined

collar to prevent the neck-yoke from rolling  
over out of its proper vertical position by the  
pull of the horses, said neck-yoke being piv-  
oted within the ring at a point in rear of the  
5 collar and having its pivot disposed verti-  
cally, substantially as described.

In testimony that I claim the foregoing as

my own I have hereto affixed my signature in  
the presence of two witnesses.

JACOB ZIEGLER.

Witnesses:

H. W. SCHOETTGER,  
THOS. FINNELL.