
W. H. KNIGHT.
FLUID PRESSURE MOTOR.



United States Patent Office.

WALTER H. KNIGHT, OF NEW BRIGHTON, NEW YORK.

FLUID-PRESSURE MOTOR.

SPECIFICATION forming part of Letters Patent No. 589,355, dated August 31,1897.

Application filed May 7, 1896. Serial No. 590,612. (No model.)

To all whom it may concern:

Be it known that I, WALTER H. KNIGHT, a citizen of the United States, residing at New Brighton, in the county of Richmond and 5 State of New York, have invented certain new and useful Improvements in Fluid-Pressure Motors, of which the following is a specification.

My invention is particularly applicable to to fluid-pressure engines in which the main valve and cut-off valves are operated by fluidpressure, but my improvements may be applied to other forms of fluid-pressure engines.

My invention consists in arranging the ex-15 haust-ports at such points and of such size that they will be opened by the piston to allow the exhaust of the expanding working fluid at or just before the completion of each stroke of the piston and before the com-20 mencement of the return stroke. By this means the rapidity of action and efficiency of the engine are greatly increased for the reason that the surplus in pressure of the working fluid behind the piston is relieved and re-25 duced to atmospheric pressure before the piston begins its return stroke.

I will describe my improvements more particularly in connection with the accompanying drawing, which represents a plan view of 30 a fluid-pressure engine embodying my invention, part being in section to show the internal arrangement of the valves and ports.

A A are the cylinders, and B B are the pistons.

C C are the main-valve chambers, communicating with the cylinders A A through fluid-supply ports D D', located adjacent to the ends of the cylinders.

E is the main valve, comprising the cylin-40 drical heads e e', working in the casing C and

united by a rod.

F is the fluid-pressure chest, communicating through ports G G' with the cut-off-valve casings H H' and adapted to receive fluid under pressure through the throttle-valve I. The cut-off-valve casings H H' communicate with the ends of the cylinders through ports KK', and with the main-valve casing through ports L L'.

50 JJ' are the cylindrical cut-off valves, working in casings H H' and having differential pressure-faces, the larger face in each case | following is what I desire to claim:

being presented toward the port N or N', presently to be referred to. The ends of the mainvalve casings C also communicate with the 55 ports K K' through ports Q Q'. The casings C C communicate with exhaust-ports M M', through which the cylinders exhaust.

N N' are ports leading from the cylinders A to the casings HH' on the opposite sides 65

of the cut-off valves from ports K K'.

O O' are exhaust-ports leading from the cylinders to the main-valve casings C C. The exhaust-ports are formed with depressions or recesses P P', extending inwardly toward 65 the center of the cylinder from the exhaustports and becoming gradually smaller or tapering toward the center of the cylinder.

The operation may be briefly described as follows: At the left-hand side of the sheet the 70 parts are shown in the position they assume just as the piston B is starting on its return stroke, the cylinder A taking compressed air or other fluid through the main supply-ports G, D, and K from the chest F. The piston 75 moves to the right under the action of the live air or other fluid until it passes the port N, when the live air will pass through port N to valve-casing H and shift the cut-off valve J, which cuts off the supply of fluid to the cyl- 80 inder. The piston then continues its stroke under the action of the expansion of the fluid which is confined in the cylinder, the cylinder exhausting in front of the piston during the stroke through the exhaust-port O', casing C, 85 and exhaust M. When the piston passes the exhaust-port O', the air confined between the piston and the end of the cylinder will be compressed for acting, through port K', upon the main-valve head e' and cut-off valve J' for 90 shifting them. Before the compression has gone far enough to effect the shifting of the valves, however, the piston will pass over and uncover the depression or recess P' and allow the expanding working fluid behind the pis- 95 ton to bleed out or exhaust into the exhaustport O' and escape through pipe M. Just as soon as this has been accomplished the compression in the end of the cylinder will have increased sufficiently to actuate the valves, 100 when the operations will be repeated at the other end of the cylinder.

Having thus described my invention, the

1. A fluid-pressure engine having supply and exhaust ports, and main and cut-off valves, with depressions or extensions forming continuations of the exhaust-ports in the 5 cylinder for bleeding the expanding working fluid from the cylinder into the exhaust when uncovered by the piston at or near the end of

its stroke, as set forth.

2. In a fluid-pressure engine, the combinato tion of the cylinder having supply and exhaust ports adjacent to its opposite ends, depressions or recesses extending from the exhaust-ports toward the center of the cylinder and the piston adapted to uncover the de-15 pressions or recesses just before or at the completion of each stroke for the purpose of bleeding the expanding working fluid from

behind the piston before it starts on its return stroke, as set forth.

3. In a fluid-pressure engine, the combina- 20 tion of the cylinder having supply and exhaust ports adjacent to its opposite ends, tapering depressions or recesses extending from the exhaust-ports and tapering toward the center of the cylinder, and the piston 25 adapted to uncover the depressions or recesses just before or at the completion of each stroke for the purpose of bleeding the expanding working fluid from behind the piston before it starts on its return stroke, as set forth. 30 WALTER H. KNIGHT.

Witnesses:

HARRY E. KNIGHT, M. V. BIDGOOD.