(No Model.)

K. SCHIEK.
DOOR OPENER.

No. 590,169.

Patented Sept. 14, 1897.

Fig. 1.






Fig.4

Fig. 2.





THE NORRIS PETERS CO., PHOTO-LITHO., WASHINGTON, D. C

## United States Patent Office.

KARL SCHIEK, OF STUTTGART, GERMANY.

## DOOR-OPENER.

SPECIFICATION forming part of Letters Patent No. 590,169, dated September 14, 1897.

Application filed December 29, 1896. Serial No. 617,405. (No model.)

To all whom it may concern:

Be it known that I, KARL SCHIEK, of Stuttgart, Kingdom of Würtemberg, Germany, have invented certain new and useful Improvements in Door-Openers, of which the following is a specification.

This invention relates to a device for opening a door by means of the foot; and it consists in the construction hereinafter set forth

10 and claimed.

In the accompanying drawings, Figure 1 shows the arrangement attached to a door in elevation. Fig. 2 shows a partial view on a larger scale. Fig. 3 shows a plan view from

15 above, and Fig. 4 shows a detail.

A bar b passes through a longitudinal slot a', provided underneath in the door a. The said bar bears the step-plates c c', one on each side of the door. The one plate c is connected to a lever d, which is attached at d' revolubly to the door. The plate c is, moreover, articulated by means of a rod e to the handle f. The connection of the rod e to the handle f may be effected in any suitable manner. As shown in Fig. 4, this may be done by hooking the rod to the handle.

If the user treads with the foot upon the one or the other of the plates cc' on the bar b, working in the slot a', the handle or bolt of the door will open. In order that the door may be still further pressed upon—that is to say, may open farther by itself—there is a plate g, fastened either at the top to the door or side-

wise to the same, which bears a spring h, pressing against the door-post.

By means of the plates c c' I am enabled to

open the door from either side.

What I claim, and desire to secure by Let-

ters Patent, is—

1. A door-opener consisting of a bar b extending through a slot in the lower part of the door, foot-plates cc' on said bar at either side of the door, a lever d to carry said bar and foot-plates said lever being pivotally attached to the door means for connecting the 45 free end of said lever to the handle-lever of the door-lock and means for pushing the door open when the said foot-plates are depressed substantially as described.

2. The combination of a bar b extending 50 through a slot in the lower part of the door, foot-plates c c' at either side of the door attached to said bar, a lever d to carry said bar and foot-plates, said lever being pivotally attached to the door, means for connecting the 55 free end of said lever to the handle-lever of the door-lock and a spring attached to the said door and adapted to press against the door-frame in the manner and for the purpose substantially as described.

In witness whereof I have hereunto set my hand in presence of two witnesses.

KARL SCHIEK.

Witnesses:

KARL BOSCH, CHRISTIAN BAUER.