

(No Model.)

A. J. LYON.  
KEY GUARD.

No. 592,300.

Patented Oct. 26, 1897.

FIG. 6.




FIG. 1.




FIG. 2.




FIG. 3.




FIG. 4.





FIG. 5.



WITNESSES:

*H. Kelly.*  
*Wm. A. Kelly.*

INVENTOR  
*A. J. Lyon.*

BY

*Mumford*  
ATTORNEYS.



# UNITED STATES PATENT OFFICE.

ADDISON J. LYON, OF MOUNT VERNON, NEW YORK.

## KEY-GUARD.

SPECIFICATION forming part of Letters Patent No. 592,300, dated October 26, 1897.

Application filed October 30, 1896. Serial No. 610,587. (No model.)

*To all whom it may concern:*

Be it known that I, ADDISON J. LYON, of Mount Vernon, in the county of Westchester and State of New York, have invented a new and Improved Key-Guard, of which the following is a full, clear, and exact description.

The object of my invention is to provide a key-guard capable of being readily applied to any form of a lock, the guard being furthermore so constructed that when applied to a mortised lock the door will not be mutilated, and whereby also the device itself will be entirely concealed by the escutcheon.

Another object of the invention is to provide a key-guard which will be exceedingly simple, durable, and economic and which may be applied to a lock in a convenient and in an expeditious manner.

The invention consists in the novel construction and combination of the several parts, as will be hereinafter fully set forth, and pointed out in the claims.

Reference is to be had to the accompanying drawings, forming a part of this specification, in which similar characters of reference indicate corresponding parts in all the figures.

Figure 1 is a perspective view of the improved guard removed from the lock and viewed from the front. Fig. 2 is a rear elevation of the improved guard. Fig. 3 is a vertical section through a portion of a door, illustrating the application of the device, which is also in section, to a mortise-lock, the said section being taken substantially on the line 3 3 of Fig. 4. Fig. 4 is a front view of a portion of a door to which a mortise-lock is applied, illustrating the escutcheon and the guard as located between the lock and the escutcheon. Fig. 5 is a horizontal section through the guard and through the escutcheon attached thereto; and Fig. 6 is a perspective view of a rim-lock, illustrating the application of the improvement thereto.

A flange 10 is secured to the back of a face-plate 11, the said face-plate being provided with a longitudinal opening 12 therein, around which opening the flange 10 is arranged. The flange may be attached to the face-plate or may constitute an integral portion of the same. A vertical flange 13 extends within the opening 12 in the face-plate at one side of the opening, and this flange 13

is preferably formed by striking up the metal from the face-plate adjacent to the opening and bending the metal over the opening, as is clearly shown in Figs. 1 and 2, thereby leaving an opening 14 in the face-plate, but the front flange 13, which is actually a stop-flange, may be otherwise formed if found necessary.

At the opposite side of the opening 12 in the face-plate an upper transverse rib 15 is formed on the inner face of the flange 10, and at the bottom of the opening 12 on the same side a parallel rib 16 is formed, while between these two ribs 15 and 16 the knuckles of a stop plate or block 17 are entered, and the stop plate or block is hinged to the face-plate and its flange 10 by passing a spindle 18 through the knuckles of the stop plate or block and into the upper and lower ribs 15 and 16, as is most clearly illustrated in Fig. 2.

The stop block or plate at its free end is normally held in engagement with the inner face of the stop-flange 13 by coiling a spring 19 around the spindle 18, causing one end of the spring to have bearing against the block or plate and the other end against the face-plate or its flange 10. The outer face of the stop plate or block 17 is practically flush with the outer surface of the face-plate 11, as shown in Fig. 5.

A handle 20, preferably in the form of a crank-arm, is employed to open the stop plate or block or carry the same inward within the flanged portion 10 of the face-plate. This handle or arm usually consists of a vertical member which revolves freely in the central portion of the stop block or plate, being introduced through the bottom thereof, and a horizontal member which is curved and extends outward from the bottom of the stop block or plate in direction of one side of the face-plate. The object of revolvably mounting the handle or arm in the stop-block is to enable it to readily adjust itself to the opening in thick or thin escutcheons. Thus by pushing inward the outer portion of the handle 20 the stop block or plate will be carried inward, as shown in dotted lines, Fig. 5, admitting of the key previously introduced in the lock being taken out or removed from the lock in connection with which the guard is employed. The stop-block is in no manner



a barrier to the introduction of a key in the lock, as the block moves backward or within the flanged portion 10 of the face-plate as the key is advanced; but after the key has passed the block the spring 19 will return the block to its normal position across the keyhole, effectually preventing the withdrawal of the key or the key dropping from the lock by reason of the door being violently closed or receiving a shock from another source. The key can be withdrawn only after the stop-block has been carried inward by the manipulation of the arm or handle 20, as above stated.

The face-plate 11 may or may not be secured to the escutcheon 21 when the device is used in connection with a mortise-lock or is applied to a door at that side opposite which the lock is located, it simply being necessary in applying the device to insert it in an opening in the door of sufficient size to receive the flange 10, and the flange fitting snugly in the opening protects the sides of the opening, while the material of the door serves to strengthen the device, and when the escutcheon is secured to the door, as shown in Fig. 4, the device will be perfectly concealed, since it will be securely held between the escutcheon and the opposing surface of the door, a portion of the stop plate or block only being visible as it crosses the keyhole, together with the horizontal portion of the handle 20, which is carried out through the bottom portion of the keyhole in the escutcheon.

In Fig. 6 I have illustrated the key-guard as applied to a rim-lock. In this instance the flange 10<sup>a</sup> of the face-plate 11<sup>a</sup> is formed on the front of the face-plate instead of the back, and the hinged stop 17<sup>a</sup> is located in the lower portion of the flange, at the forward edge thereof, instead of between the walls of the opening in the face-plate. By this means the face-plate may be secured directly to the lock by rivets or their equivalents.

Having thus described my invention, I claim as new and desire to secure by Letters Patent—

1. The combination with a lock, and its casing, of a spring-controlled stop carried by a support on one side of the keyhole and normally extending across said keyhole, said

stop being movable in a plane which is at right angles to the casing to swing away from the keyhole and admit of the insertion of a key, the spring returning said stop to its normal position after the key has been inserted, as set forth.

2. In a lock, a stop hinged at one end to a support and located within the casing of the lock and extending across the keyhole of the same, a flange against which the free end of the stop has bearing, a spring normally holding the stop in engagement with the said flange, and means for carrying the stop inward against the tension of the said spring, substantially as shown and described.

3. A key-guard consisting of a face-plate, a stop hinged in an opening in the said face-plate, spring-controlled in one direction, means for limiting the outward movement of the stop, and an arm mounted to turn in the block and adapted for carrying the stop inward against the tension of its spring, as and for the purpose specified.

4. A key-guard consisting of a face-plate having an opening therein adapted to register with the keyhole of the lock, and a spring-controlled stop hinged to the face-plate within the said opening, a flange surrounding the said opening of the face-plate, and devices, substantially as described, for limiting the outward movement of the stop and carrying the said stop inward, as and for the purpose specified.

5. A key-guard, the same consisting of a face-plate having an opening therein, and a flange surrounding the said opening at one side of the face-plate, a stop having a spring-controlled hinged connection with the face-plate at a point within the opening of the same, a flange limiting the movement of the stop in one direction, and a handle extending beyond the face-plate and arranged for carrying the stop inward to permit the withdrawal of the key, as and for the purpose set forth.

ADDISON J. LYON.

Witnesses:

J. FRED. ACKER,  
JNO. S. WILLIAMS.