


(No Model.)

J. L. ELSASS.
BOTTLE PROTECTOR.

No. 598,596.

Patented Feb. 8, 1898.



WITNESSES
G. F. Downing
S. B. Nottingham

INVENTOR
J. L. Elsass
By N. A. Seymour
Attorney

UNITED STATES PATENT OFFICE.

JOHN LOUIS ELSASS, OF CHILLICOTHE, OHIO.

BOTTLE-PROTECTOR.

SPECIFICATION forming part of Letters Patent No. 598,596, dated February 8, 1898.

Application filed October 16, 1897. Serial No. 655,411. (No model.)

To all whom it may concern:

Be it known that I, JOHN LOUIS ELSASS, a resident of Chillicothe, in the county of Ross and State of Ohio, have invented certain new and useful Improvements in Bottle-Protectors; and I do hereby declare the following to be a full, clear, and exact description of the invention, such as will enable others skilled in the art to which it appertains to make and use the same.

My invention relates to an improvement in bottle-protectors, and more particularly to protectors for nursing-bottles and the like, the object of the invention being to provide a cheap and neat-appearing device that will preclude all liability of breaking a nursing-bottle when same is dropped.

With this object in view the invention consists in certain novel features of construction and combinations and arrangements of parts, as will be more fully hereinafter set forth, and pointed out in the claims.

In the accompanying drawings, Figure 1 is a view showing my improved device placed upon a nursing-bottle. Fig. 2 is a view of same detached. Fig. 3 is a detail, and Fig. 4 is a horizontal section.

A represents my improved protector, which consists of a frame composed of spring-wire and provided with a base 1, composed of a piece of spring-wire 2, bent into elliptical shape and provided with two cross-pieces 3 3. To the base 1 four (more or less) upright wires 4 are secured, said upright wires being bent or indented, as at 5, to form bearing-points for the device against the nursing-bottle B. The uprights are bent or curved outwardly at their upper ends to form hooks or catches 5^a for the reception of a ring 6, approximately similar in diameter to the diameter of the neck of the bottle. An elliptical-shaped reinforcement 7 is provided about midway between the ends of the upright wires 4 and secured thereto. Said reinforcement is bent or indented, as at 8, to form bearing-points for the intermediate portion of the frame against the bottle. Where the upright wires join the reinforcement I prefer to employ a device or coupling, such as shown in Fig. 3. This consists of a single piece of metal bent to form two collars 9 9, both

adapted to be secured on the same wire, and an intermediate portion 10, bent to receive the other wire and secure same at right angles to the first-mentioned wire. Solder may be placed in this fastening device to more securely hold same in place.

It is to be understood that I do not limit myself to the precise form of locking device, but consider myself at liberty to employ any approved means for securing the wires together.

When it is desired to place my improved safety device or protector upon a bottle, it is simply necessary to remove the ring 6, when the upright wires 4 will spring outward and allow the bottle to be placed therein. The ring can then be passed over the neck of the bottle and secured around the hook-shaped ends 5^a of the upright wires 4. When the bottle is thus protected by the frame, it will be practically impossible for the bottle to break should it fall upon the ground or floor, as the spring-wires of the frame will prevent contact of the bottle with the floor and will also take up most of the jar which would otherwise result.

Various slight changes might be made in the general form and arrangement of parts herein shown and described without departing from the spirit and scope thereof, and hence I would have it understood that I do not limit myself to the precise details herein shown and described; but,

Having fully described my invention, what I claim as new, and desire to secure by Letters Patent, is—

1. As an article of manufacture, a bottle cage or protector constructed to receive the bottle from its top and envelop and guard it upon all sides, said cage or protector having an arched wire bottom upon the crest of which the bottle rests.

2. As an article of manufacture, a bottle cage or protector composed of wire, the bottom of which is composed of a wire ring, and upwardly-bowed or arched cross-pieces extending diagonally from opposite points of the ring.

3. As an article of manufacture, a bottle cage or protector composed of wire, the upper ends springing normally outward and

furnished with outwardly-extending projections, and a removable ring adapted to encircle said spring ends whereby to retain them in a normally-closed position.

- 5 4. As an article of manufacture, a bottle cage or protector composed of wire bottom and sides, said sides having inwardly-extending indentations adapted to bear upon the bottle, free upper ends and a removable ring for
10 retaining said upper ends together around the

bottle after it has been dropped into the cage or protector.

In testimony whereof I have signed this specification in the presence of two subscribing witnesses.

JOHN LOUIS ELSASS.

Witnesses:

JACOB R. GALBRAITH,
D. H. COLLETT.