

(No Model.)


L. SKAIFE. CONDUIT.


No. 600,935.

Patented Mar. 22, 1898.









Witnesses
RACNignber
Fall State
334

Lilvis Skaife

Ottorney

Ottorney

Moh Muan

## UNITED STATES PATENT OFFICE.

## LEWIS SKAIFE, OF MONTREAL, CANADA.

## CONDUIT

SPECIFICATION forming part of Letters Patent No. 600,935, dated March 22, 1898.

Application filed June 5, 1897. Serial No. 639,614. (No model.)

To all whom it may concern:

Be it known that I, Lewis Skaife, of the city of Montreal, in the district of Montreal and Province of Quebec, Canada, have invented certain new and useful Improvements in Conduits; and I do hereby declare that the following is a full, clear, and exact description of the same.

My invention has for its object to produce as a new article of manufacture a conduit length or section which from its peculiar nature may be laid in line with others to form a single conduit or be placed side by side in the building of large sewers.

The conduit-section is wedge-shaped in cross-section, or, in other words, has two sides of such angles as make them radial from a given center, and is preferably made of tile material, although other materials—such as cement, earthenware, &c.—suitable for carrying electric wires may be used.

For full comprehension, however, of the invention reference must be had to the annexed drawings, forming a part of this specification, in which like symbols indicate cor-

responding parts, and wherein—Figure 1 is a perspective view

Figure 1 is a perspective view of a single conduit length; Fig. 2, a longitudinal section of a modified form of same; Fig. 3, a view 30 showing several lengths laid in line to form a conduit; Fig. 4, a view showing the crown portion of a large sewer built of my improved conduit lengths, and Fig. 5 an enlarged end elevation of a single conduit length.

35 My improved conduit length or section is of oblong form and practically wedge-shaped in cross-section, with parallel top and bottom a b, inclined sides c d, and a central longitudinal passage e, the inclined sides c d being at such angles as to make them radial from a given center—such as, for instance, the center 2 of the sewer shown in Fig. 4.

As shown by the drawings, the especial form of the conduit length allows it to be used either in line with others to form a single conduit or to be used in building sewers of large dimensions. It is preferably manufactured from tile material suitably baked and glazed, although I do not wish to be confined to such material.

In the modified form shown in Fig. 2 the ends of the conduit length are respectively recessed and tenoned to effect a more perfect union, when desired.

The conduit lengths can be made in a simi- 55 lar manner to the manufacture of drain tile pipes, &c.

What I claim is as follows:

1. As a new article of manufacture a tile conduit length of oblong form having paral- 60 lel flat top and bottom, inclined sides, and a centrally-located longitudinal circular passage, the sides being at such angles as to make them radial from a given center, substantially as and for the purpose set forth.

2. As a new article of manufacture, a tile conduit length of oblong form having a centrally-located longitudinal circular passage therethrough, parallel flat top and bottom and inclined sides, the latter at such angles 70 as to make them radial from a given center, substantially as and for the purpose set forth.

3. As a new article of manufacture, a tile conduit length of oblong form having a centrally-located longitudinal circular passage 75 therethrough, parallel flat top and bottom, inclined sides at such angles as to make them radial from a given center, and the ends respectively recessed and tenoned, substantially as described and for the purposes set forth. 80 LEWIS SKAIFE.

Witnesses:

F. W. McFeat, Fred. J. Sears.