

(No Model.)

C. N. SMITH.
COFFIN LID FASTENER.

No. 604,848.

Patented May 31, 1898.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 6a.




Fig. 6.





Fig. 7.



WITNESSES:

Edwin L. Bradford
R. H. Pherson

INVENTOR

Chris N. Smith

BY

Fred J. Dietrich
ATTORNEYS

UNITED STATES PATENT OFFICE.

CHRIS N. SMITH, OF ELGIN, ILLINOIS, ASSIGNOR OF ONE-HALF TO G. A. ROWE, OF SAME PLACE.

COFFIN-LID FASTENER.

SPECIFICATION forming part of Letters Patent No. 604,848, dated May 31, 1898.

Application filed May 12, 1897. Serial No. 636,185. (No model.)

To all whom it may concern:

Be it known that I, CHRIS N. SMITH, residing at Elgin, in the county of Kane and State of Illinois, have invented certain new and useful Improvements in Coffin-Lid Fasteners, of which the following is a specification.

My invention relates to an improved fastening device more especially adapted for securing coffin-lids; and it primarily has for its object to provide devices of this character which will automatically lock the lid to the coffin-body and hold it thereon practically airtight.

My invention also seeks to provide a device of this kind so constructed and arranged that the same can be manipulated to instantly remove the lid.

Furthermore, my invention has for its object to provide a fastener and lock means for the purposes stated of a very simple and inexpensive construction which can be easily applied to the ordinary coffin-bodies and lids and which are entirely concealed from view by the overlapping edge of the lid or cover.

With other objects in view, which will be hereinafter referred to, my invention consists in a lid-fastening means embodying the peculiar combination and novel arrangement of parts, as will be first described in detail, and then be specifically pointed out in the appended claim, reference being had to the accompanying drawings, in which—

Figure 1 is a perspective view of a coffin with my improvement applied. Fig. 2 is a top plan view of the coffin-body and the lid, said lid being shown inverted. Fig. 3 is a detail longitudinal section taken on the lines 3 3 of Fig. 2, the lid being held locked on the body. Fig. 4 is a perspective view of one of the wedge lock-plates. Fig. 5 is a similar view of one of the T-head lock-plates. Fig. 6 is a perspective view of the combined wedge-lock and latch-plate. Fig. 6^a is a section on the line 6 6 of Fig. 2. Fig. 7 is a transverse section taken on the line 7 7 of Fig. 2, the lid being locked on the body.

In practical application of my invention the fastener members are so applied to the body and the lid that by simply placing the lid on the coffin-body and sliding it forward causes the said fastener members to engage with each

other, and thereby secure the lid in place, the construction of the fasteners being such that the forward sliding motion of the lid will serve to draw it tightly down on the coffin, and thereby make practically an air-tight fit.

Referring now to the accompanying drawings, in which like numerals indicate like parts in all of the figures, 1 indicates the coffin-body, which may be of any approved form, and 2 the lid, the edges of which lap the coffin sides in the usual manner. The upper edges of the sides of the coffin have a series of sockets 3 3, the upper edges of which terminate at transverse seats 3^a 3^a, which may extend entirely across the said edges, as shown, but need not necessarily do so.

5 indicates a series of wedge lock-plates, each of which consists of a smooth top plate 6 of a width and length to fit flush in the seats 3^a 3^a and which have keyhole-slots 7, the head portion 7^a of which is made, preferably, square, and at the point where it merges with the shank portion 7^b it has beveled edges 7^c for a purpose presently described.

The plate 5 at the sides of the head portions 7^a of the slot has pendent lugs 8, which snugly fit against the sides of the sockets 3, and at the sides of the shank portion 7^b of such slot it has pendent wedge members 9, the heel of which is adjacent the rear end of the slot 7^b, while the point terminates at the lugs 8, which have their ends adjacent the wedges 9 beveled, as at 8^a. The outer edges of the wedges 9 also form lateral bearings to engage the sides of the pockets, as clearly shown in Fig. 7.

The several plates 5 are secured to the coffin-body by screws 5^b 5^b.

The lid 2 has a series of seats 10, which coincide with the pockets in the coffin-body, in which the plates 11 are held flush with the lower face by the screws 11^a 11^a. The plates 11 have centrally-disposed pendent T-headed lock-lugs 12. One of the plates 11 has an extension 11^c, provided with an opening 11^b, through which passes a lock-stud 14, secured to a spring-plate 14^a, in turn secured to the extension 11^c, which moves freely in a socket 15 in the lid under such extension 11^c, which socket is also extended at right angles toward the edge of the lid, as at 15^a, to permit a free

movement of the catch member 16, secured to the lock-stud and having a finger portion 16^a, projected below the edge of the lid, as clearly shown in Fig. 1.

5 To close a coffin having my improved fasteners, the lid is placed on the body with the T-lugs passed down into the head portions of the keyhole-slots in the plates 5, the operator at this time holding the lock-catch pulled up
10 into the sockets 15 15^a. As the lid is slid forward the shank of the lugs 12 will pass into the shank portions 7^b of the slots, such movement being facilitated by the beveled edges 7^c, while the heads will pass under and en-
15 gage the wedges 9, and thereby, as the lid is slid forward, gradually draw the said lid tightly down on the body. It will be noticed by reference to the drawings that the rela-
20 tion of the lock-lugs, the wedges, the key-slots, and the lock-opening in the end and the lock-plate is such that after the lid has been slid forward until it has been drawn
25 down tight the spring-lock stud will be in position to pass down into the head end of the slot in the said end lock-plate, and thereby hold the lid locked to the coffin-body.

To remove the lid, the operator by finger manipulation raises the lock-stud out of en-
30 gagement with the end lock-plate and pulls the lid back, which causes the lock-lugs to enter the head portion of the slot, the heads being guided into a proper position into such slots by the beveled edges of the lugs 8.

35 While I have described in detail but one lock device, it is obvious that in practice the lid will have a pair of such locks, one at each side, as shown in the drawings.

Instead of making the lock-lugs and the wedges integral with their securing-plates they may be detachably connected with such
40 plates, if desired.

From the foregoing description, taken in connection with the accompanying drawings, it is thought the advantages and complete
45 operation of my invention will be readily understood. The same is of an exceedingly simple nature and capable of such manipulation that the lid can be quickly attached to or removed from the coffin-body without the
50 use of a screw-driver or other implement.

While I have shown my improvement as applied to a coffin, it is manifest its use is ap-
plied to any box having a removable lid.

Having thus described my invention, what I claim, and desire to secure by Letters Pat-
55 ent, is—

The combination with the coffin-body, hav-
ing a series of pockets in the upper edge of its sides, each having a lock-plate having a
60 keyhole-slot having beveled portions 7^c pendent wedges 9 having the beginning-point of
incline at the said beveled portions, and hav-
ing pendent lugs 8 at such point of begin-
ning, said lugs having beveled edges 8^a, of a
65 lid having a series of lock-plates having T- heads, all being arranged substantially as
shown and described, whereby the shank of the lock-plate will be guided by the edges 7^c,
and the head by the beveled edges 8^a, when
70 the parts are joined as hereinbefore described.

CHRIS N. SMITH.

Witnesses:

A. G. WAITE,
MAY E. HOUSTON.