

(No Model.)

T. E. SAYRE.
BOX FASTENER.

No. 605,919.

Patented June 21, 1898.

Fig. 1.




Fig. 2.




Fig. 3.




Fig. 4.




Fig. 5.





Fig. 6.



Witnesses

R. A. Shepard
J. H. Riley

By *his* Attorneys,

Chas. Snow & Co.

Inventor

Thomas E. Sayre.

UNITED STATES PATENT OFFICE.

THOMAS E. SAYRE, OF JANESVILLE, WISCONSIN.

BOX-FASTENER.

SPECIFICATION forming part of Letters Patent No. 605,919, dated June 21, 1898.

Application filed May 25, 1897. Serial No. 638,133. (No model.)

To all whom it may concern:

Be it known that I, THOMAS E. SAYRE, a citizen of the United States, residing at Janesville, in the county of Rock and State of Wisconsin, have invented a new and useful Box-Fastener, of which the following is a specification.

The invention relates to improvements in box-fasteners.

10 The object of the present invention is to improve the construction of box-fasteners and to provide a simple, inexpensive, and efficient device adapted to be readily applied to box-covers and capable of securely fastening the
15 same to the bodies of boxes and of preventing their removal without a key.

The invention consists in the construction and novel combination and arrangement of parts, as hereinafter fully described, illustrated in the accompanying drawings, and
20 pointed out in the claims hereto appended.

In the drawings, Figure 1 is a perspective view of a box-cover provided with a fastener constructed in accordance with this invention. Fig. 2 is a vertical sectional view of
25 the upper portion of a box, showing the invention applied. Fig. 3 is an enlarged detail sectional view of the central portion of the box-fastener, the key being in position. Fig. 4 is a detail perspective view of the rotary hub. Figs. 5 and 6 are detail views of
30 the casing.

Like numerals of reference designate corresponding parts in all the figures of the drawings.
35

1 designates a cover designed especially for beer-boxes, but adapted for any analogous receptacle, and provided on its lower face with a depending flange 2, preferably formed by
40 cleats or strips and fitting within the body 3 of the box, as illustrated in Fig. 2 of the accompanying drawings. The cover is provided with a central circular opening 4, in which is arranged an annular flange or sleeve
45 5 of a hub 6, which consists of a plate or disk arranged on the inner face of the cover and the said sleeve or flange, which extends into the circular opening and forms a journal.

The sleeve or flange of the hub has its upper edge located slightly below the plane of
50 the upper face of the cover, and the hub is

provided with a central opening or socket 7, adapted to be engaged by a key 8 and receiving a central stud 9 of a casing 10.

The casing 10 is provided with substantially L-shaped feet 11, which are perforated
55 for the reception of screws or other suitable fastening devices and which offset the body portion of the casing from the cover. The body portion of the casing is circular and the
60 feet, which are arranged at intervals, form openings through which extend the inner portions of sliding bolts 11^a.

The sliding bolts 11^a, which consist of rods, have their outer ends 12, which are pointed,
65 guided in perforations 13 of the flange of the cover, and the inner ends of the bolts are bent upward at right angles and are engaged with perforations 14 of the hub, whereby when the
70 latter is partially rotated the bolts are simultaneously reciprocated. The pointed ends of the bolts are adapted to engage the sides and ends of a box which does not have to be provided with any particular form of keeper,
75 and when the inner ends of the bolts are brought in alinement with their outer ends and are arranged directly opposite each other they are positively held against accidental inward movement.

It will be seen that the box-fastener is exceedingly simple and inexpensive in construction, that the casing secures the hub to
80 the cover and supports and forms a bearing for the same, and that the bolts cannot be operated without a key. It will also be apparent that the box-fastener is quickly operated to lock or release a cover and that a
85 keeper is unnecessary; the pointed ends of the bolts being adapted to embed themselves in any ordinary wooden box.
90

What I claim is—

1. In a box-fastener, the combination with a cover having a central opening, of a rotary hub provided with a central opening and having an annular flange or sleeve fitting in the
95 opening of the cover, said hub being adapted to be engaged by a key, a casing secured to the cover, receiving the hub and provided with a stud fitting in the central opening of the same and forming a pivot said casing being provided with a series of openings, and
100 sliding bolts guided on the cover and having

their inner portions extended through the openings of the casing and connected with the hub, substantially as described.

2. In a box-fastener, the combination with
5 a cover provided with a depending flange having perforations, a casing provided with a central vertical pivot-stud and having feet forming openings and secured to the cover, a hub provided with an annular sleeve or
10 flange and having a central opening to receive the pivot-stud and provided with perforations, said hub being journaled on the stud

and in an opening of the cover, and pointed rods guided in the perforations of said flange and having upturned inner ends arranged in the perforations of the hub, substantially as described. 15

In testimony that I claim the foregoing as my own I have hereto affixed my signature in the presence of two witnesses.

THOMAS E. SAYRE.

Witnesses:

CLAUDE J. HENDRICKS,
HOMER S. NOLAN.