

No. 618,703.

Patented Jan. 31, 1899.




H. S. MAXIM.

APPARATUS FOR MANUFACTURING FILAMENTS FOR ELECTRIC LAMPS.

(Application filed Nov. 8, 1898.)

(No Model.)

2 Sheets—Sheet 1.



Witnesses.  
Hillary C. Messimer  
Benjamin Miller,

Inventor.  
Hiram S. Maxim.  
by Kew, Page & Cooper  
Att'ys.



H. S. MAXIM.

APPARATUS FOR MANUFACTURING FILAMENTS FOR ELECTRIC LAMPS.

(Application filed Nov. 8, 1898.)

(No Model.)

2 Sheets—Sheet 2.



Witnesses.  
 Hillary C. Messimer  
 Benjamin Miller.

Inventor.  
 Hiram S. Maxim.  
 by Kerr, Page & Cooper  
 Attys.

# UNITED STATES PATENT OFFICE.

HIRAM STEVENS MAXIM, OF LONDON, ENGLAND.

APPARATUS FOR MANUFACTURING FILAMENTS FOR ELECTRIC LAMPS.

SPECIFICATION forming part of Letters Patent No. 618,703, dated January 31, 1899.

Application filed November 8, 1898. Serial No. 695,833. (No model.)

*To all whom it may concern:*

Be it known that I, HIRAM STEVENS MAXIM, chevalier of the Legion of Honor, civil and mechanical engineer, a citizen of the United States, residing at 18 Queen's Gate Place, London, in the county of Middlesex, England, have invented certain new and useful Improved Apparatus for Manufacturing Filaments for Electric Lamps, of which the following is a specification.

My invention relates to an apparatus for manufacturing filaments for incandescent electric lamps.

The tendency at the present time in electric lighting is to use very high voltage, and in order to meet the new requirements arising from this tendency it is necessary to increase the resistance of the lamp-filaments as much as possible. This can only be done by making them extremely fine and long or by adding to the carbon of which they are composed some highly-refractory non-conducting material. When such materials as carbid of silicon and carbid of boron are employed with the carbon, they are liable to be volatilized by the electric current when the lamp is in use and to form a thin opalescent film on the inside of the glass globe of the lamp. Now diamond-powder is not subject to this objection, as it will endure a very high temperature without being volatilized. Natural diamond-powder—*i. e.*, natural diamonds reduced to powder—is, however, too expensive to be used for this purpose even if made from the cheapest kind of stones that can be obtained; but according to my invention I am able to manufacture a species of carbon which, while closely if not completely resembling the diamond, will be less expensive than natural diamonds. For this purpose it is necessary to employ an extremely great pressure and a high temperature, and an important feature of my invention has reference to the manner in which such great pressure and high temperature are obtained.

It is well known that carbonic acid or carbon dioxid ( $\text{CO}_2$ ) may be retained in the liquid condition at a pressure of about from five hundred to six hundred pounds per square inch at ordinary temperatures, but that if it be converted into carbon monoxid the pressure required to confine it is very

much greater. I take advantage of this fact to obtain the high pressure and temperature I require by placing in a strong tightly-closed vessel carbonic acid in the liquid or solid condition, together with carbon, preferably a hydrocarbon, such as gasolene. The carbonic acid and the hydrocarbon are then decomposed by subjecting them to the voltaic arc, the oxygen of the carbonic acid being thus caused to take up another measure of carbon and to be thereby converted from carbon dioxid into carbon monoxid. This decomposition, together with the rise in temperature, will produce the necessary pressure, the temperature of the carbon being at the same time raised so extremely high that the carbon in immediate contact with or contiguous to the electric conductors, between which the voltaic arc is produced, will be converted into a species of diamond-scales which will scratch glass, while all the carbon will be very much modified.

In some instances it may be necessary to continue the high temperature for a very long time in order to allow the carbon to crystallize out of the carbonaceous gases. Of course if the carbon or hydrocarbon be heated in carbonic acid alone very little effect would take place, as no very high pressure would be reached, whereas if a too large quantity of hydrocarbon be employed a loose, smutty, and soft deposit would be formed; but by having only a small excess of carbon—*i. e.*, just sufficient to convert all the carbonic acid present into carbon monoxid with a little free hydrocarbon remaining—then the crystallization may take place from the residuum of gases, and if the process be continued long enough diamond-crystals or a species of diamond-carbon may be formed. The diamond-carbon instead of being of a very low resistance, which is peculiar to carbon whose temperature has been raised very high, will have imparted to it a high quality of electrical resistance. In fact, it may be so perfectly crystallized as to altogether prevent the passage of an electric current through it. This of course depends upon the length of time that the aforesaid treatment is continued and the temperature employed during such treatment.

In some instances all the ingredients used

for forming lamp-filaments may be mixed and subjected to the high temperature and pressure or the said ingredients may be treated singly. It will thus be possible to so change  
 5 the constitution of the carbon or other ingredients as to render them highly advantageous for the filaments of electric lamps. In any case the temperature to which they are subjected is higher than that to which they will  
 10 be subjected in the lamp itself.

The carbon obtained or the ingredients treated by my method are afterward reduced to extremely fine powder, mixed with suitable vehicles—such as tar, pitch, or sugar—  
 15 and then molded into filaments, which are “retorted” and “flashed” in the usual manner. It will be obvious from what has already been stated that the electrical resistance of the filaments will be in proportion to  
 20 the quantity of the diamond-carbon employed in their manufacture.

In the accompanying drawings, Figure 1 is a side elevation, Fig. 2 a vertical section, and Fig. 3 a plan, of one form of the apparatus for use in obtaining a high pressure and  
 25 temperature according to my invention. Fig. 4 is a vertical section, and Fig. 5 a sectional plan, of a modified construction of the said apparatus.

30 Referring more particularly to Figs. 1 to 3, A is a strong vessel of approximately cylindrical shape, furnished with trunnions A' A', by which it is pivotally supported in a frame A<sup>2</sup>. This vessel is preferably made of steel  
 35 lined with suitable refractory material, such as bricks of compressed silica or compressed magnesia, to protect it from the heat to which it is subjected internally when in use. The ends of the said vessel are provided with strong  
 40 detachable screw-covers or screw-stoppers A<sup>3</sup> A<sup>4</sup>, each of which has a lever-handle A<sup>5</sup> to enable it to be conveniently unscrewed when either of the said covers is required to be removed for the purpose of obtaining access to  
 45 the interior of the vessel.

B B' are carbon pencils or electrodes mounted in metallic holders b b', forming part of hollow stems b<sup>2</sup>, that extend through the aforesaid covers A<sup>3</sup> A<sup>4</sup>. The carbon pencils  
 50 are arranged coaxial with the vessel A, one of them being capable of longitudinal movement with respect to the other, so that the distance between their adjacent ends can be varied according to requirements. For this  
 55 purpose the stem b<sup>2</sup> of the holder b passes through a stuffing-box a, forming part of the plug-piece a'. This stem b<sup>2</sup> is connected at its outer end with another stem b<sup>3</sup>, which is screw-threaded and passes through a nut b<sup>4</sup>.  
 60 The said nut is mounted in a cross-piece b<sup>5</sup>, so as to be capable of revolving without sliding, the cross-piece b<sup>5</sup> being connected by bolts b<sup>6</sup> to a disk or bar a<sup>2</sup>, which is screwed to the aforesaid plug-piece a' and secures the  
 65 latter to the cover A<sup>3</sup>. The nut b<sup>4</sup> is furnished with lever-handles b<sup>7</sup> to permit of its being revolved, while the stems b<sup>2</sup> b<sup>3</sup> are prevented

from revolving by a feather b<sup>8</sup> on the carbon-holder engaging with a longitudinal groove  
 a<sup>3</sup> in the plug-piece. This plug-piece is insulated from the surrounding metal by suitable  
 70 insulating material a<sup>4</sup>. The other carbon pencil B' is carried by the stationary holder b', the stem b<sup>2</sup> of which passes through the screw-plug A<sup>4</sup> and is insulated therefrom by insulating material b<sup>9</sup>, such as mica or asbestos.  
 75 In order to keep the carbon-holders cool, I make the said stem b<sup>2</sup> b<sup>3</sup> of the movable holder b and also the stem b<sup>2</sup> of the fixed holder b' hollow and arrange within them a central pipe  
 80 or tube b<sup>10</sup> with an annular space b<sup>11</sup> around it. The extremities of the stems are provided with inlet and outlet nozzles b<sup>12</sup> b<sup>13</sup>, one of which communicates with the pipe b<sup>10</sup> and the other with the annular space b<sup>11</sup>. Cold water  
 85 can thus be allowed to circulate through the carbon-holders and the parts directly connected therewith.

The apparatus illustrated by Figs. 4 and 5 is provided with a lining A<sup>6</sup>, upon which the  
 90 vessel A is shrunk, the said lining having a spiral watercourse A<sup>7</sup> around it for the circulation of cold water, which enters at A<sup>8</sup> and escapes at A<sup>9</sup>. The plug-piece a' is likewise  
 95 formed with a hollow head a<sup>5</sup>, communicating with longitudinal passages a<sup>6</sup> and with inlet and outlet nozzles a<sup>7</sup> a<sup>8</sup> for enabling cold water to circulate through said plug-piece and keep it cool. The screw-stopper A<sup>3</sup> is in  
 100 this example provided with an obturator A<sup>8</sup>, composed of asbestos and plumbago with a slight admixture of paraffin-wax for assisting in rendering the vessel A gas-tight. It is also  
 105 provided with a toothed segmental portion A<sup>10</sup>, adapted to gear with a worm A<sup>11</sup>, mounted on an axle furnished with a crank-handle A<sup>12</sup> for revolving it. The said upper stopper A<sup>3</sup>  
 is formed with interrupted screw-threads, so that by giving approximately a quarter-turn  
 110 thereto it will be released from engagement with the corresponding interrupted screw-threads on the vessel A. To permit of  
 it then being readily removed from the vessel, the said worm and the crank-handle are  
 115 adapted to be disconnected by forming the worm with a longitudinal central hole of rectangular shape to receive the axle, which is also of rectangular shape at the part where  
 the worm fits it. The end A<sup>13</sup> of the said axle and the portion A<sup>14</sup> are made cylindrical to  
 120 fit the bearings A<sup>15</sup>. When the axle has been revolved a sufficient number of times to turn and release the stopper, as aforesaid, the said axle can be withdrawn longitudinally from  
 the bearings A<sup>15</sup> and also from the worm,  
 125 whereby both these parts are at one operation detached from the vessel A.

In using the apparatus the carbon or hydrocarbon is placed within the vessel A, together  
 with a quantity of carbonic acid, preferably  
 130 in its solid or snow-like condition. The vessel is then hermetically sealed by tightly screwing on the screw-stoppers, and the electric current is then allowed to pass between

the carbon pencils. As the temperature rises by the heat generated by the electric current the solid carbonic acid in the presence of the carbon will be converted into carbon monoxid and a great pressure be thereby generated within the vessel, as aforesaid. The continuance of such high temperature and great pressure will convert the carbon into a very hard and crystalline condition, which after its removal from the vessel is crushed into fine powder for use with the carbon employed in the manufacture of the filaments, as already explained above.

I do not confine myself to the use of the said apparatus for obtaining carbon in a hard and crystalline condition, as above stated, as the said apparatus may be used for treating other substances requiring to be subjected to high temperature and pressure. For instance, ordinary lamp-filaments after being retorted in the usual manner may be treated in the apparatus so as to heat them to a much higher temperature than is possible when they are heated at atmospheric pressure. In this case I prefer to employ a hollow carbon conductor to contain the filaments.

I do not claim herein the method described of manufacturing filaments for electric lamps, the same having been made the subject-matter of an application filed by me January 5, 1899, as a division hereof and bearing Serial No. 701,226.

What I claim is—

1. Apparatus consisting of a vessel provided with trunnion-bearings to permit of its moving in a vertical plane, of a screw-cover for hermetically closing said vessel of an electrically-insulated plug therein, of a hollow head to said plug communicating with inlet and outlet nozzles through which water enters

and leaves the hollow head to keep the latter cool, of electrodes mounted in holders located at opposite ends of said vessel, of stems on said holders extending to the exterior of the said vessel and formed with passages communicating with the holders and with inlet and outlet nozzles through which water enters and leaves said holders to keep them cool, of a nut carried in a frame and engaging with screw-threads on one of the stems of the electrode-holders, of handles on said nut for turning it and thereby shifting the holder so as to adjust the distance between the electrodes, of a lining for said vessel such lining having a spiral watercourse for the entrance and exit of cold water, and of a source of electricity for supplying electric current to the electrodes, substantially as and for the purpose specified.

2. In an apparatus consisting of a vessel capable of being hermetically closed by an interrupted screw-cover and having electrodes mounted in adjustable holders to which electricity is supplied from a suitable source; the combination with the said vessel of a toothed segment on said cover, of a crank-spindle having a rectangular portion, of a worm adapted to loosely fit said rectangular portion and engage with the teeth of the said toothed segment on the cover, and of brackets to temporarily receive said crank-spindle when the cover is operated substantially as and for the purpose described.

In testimony whereof I have hereunto set my hand, in presence of two subscribing witnesses, this 7th day of November, 1898.

HIRAM STEVENS MAXIM.

Witnesses:

PARKER W. PAGE,  
HILLARY C. MESSIMER.