

No. 619,519.

Patented Feb. 14, 1899.


H. VAN HOEVENBERGH.  
ELECTRIC BRANDING DEVICE.

(Application filed Aug. 2, 1894.)

(No Model.)

2 Sheets—Sheet 1.

*Fig. 1.*



Witnesses  
*C. E. Ashley*  
*J. W. Lloyd*

Inventor  
*Henry Van Hoevenberg*  
By his Attorneys  
*Robert L. Lloyd*

No. 619,519.

Patented Feb. 14, 1899.

H. VAN HOEVENBERGH.  
ELECTRIC BRANDING DEVICE.

(Application filed Aug. 2, 1894.)

(No Model.)

2 Sheets—Sheet 2.

Fig. 2,




Fig. 3,




Fig. 4,




Fig. 5,





Fig. 6,



Witnesses  
C. E. Ashley  
14 W. Lloyd.

Inventor  
Henry Van Hovenbergh  
By his Attorneys  
Proctor & Knapp



# UNITED STATES PATENT OFFICE.

HENRY VAN HOEVENBERGH, OF NEW YORK, N. Y., ASSIGNOR TO HENRIETTA LONSDALE FELLOWES, OF SAME PLACE.

## ELECTRIC BRANDING DEVICE.

SPECIFICATION forming part of Letters Patent No. 619,519, dated February 14, 1899.

Application filed August 2, 1894. Serial No. 519,255. (No model.)

*To all whom it may concern:*

Be it known that I, HENRY VAN HOEVENBERGH, a citizen of the United States, residing in the city, county, and State of New York, have invented certain new and useful Improvements in Electric Branding Devices, of which the following is a specification.

This invention relates to electric branding devices.

10 The object of the invention is to permit the burning into or upon the surface or through the substance of a fabric a group of characters, which may be varied according to the ultimate design which is desired.

15 The invention is especially designed to permit the recording of a series of numbers upon a check, draft, or other obligation to pay money, so that the amount for which the paper is drawn will be rendered unalterable.

20 In another application for Letters Patent filed by me and Birney Fellowes contemporaneously herewith we have described an apparatus having similar objects in view, in which an organization is described comprising a series of disks independently adjustable. The present invention is designed to simplify the apparatus by permitting the object to be obtained by a single disk.

25 In carrying out my invention I provide a pivoted frame carrying a rotatable disk, upon the periphery of which are arranged a series of characters formed of a thin strip of metal, one end of which is embedded in the disk and the other end of which projects therefrom, and provide means by which the apparatus will be shifted laterally after each character is burned or imprinted, so that a succession of characters may be recorded side by side upon the fabric.

30 The several features of novelty of the invention will be more particularly hereinafter described and will be definitely indicated in the claims appended to this specification.

35 In the accompanying drawings, which illustrate the invention, Figure 1 is a perspective view of an apparatus embodying my improvements. Fig. 2 is a transverse sectional view, partially in elevation. Fig. 3 is a side elevation looking to the left of Fig. 2. Fig. 4 is a top plan view. Fig. 5 is a partial sectional

view on the plane indicated by the line 5 5, Fig. 4; and Fig. 6 is a detail view of the disk upon which the branding characters are mounted.

1 represents a base-plate provided with a slot at 2, by which the line of branding may be accurately determined. The base-plate is provided with vertical uprights or lugs 3 3<sup>a</sup>, in which is journaled a curved arm 4, provided with a projection 5 near its pivotal point coöperating with a leaf-spring 6, mounted on the base-plate, by which the arm 4 is normally maintained in a raised position, so as to carry the branding-disk 7 above the plane of the base-plate. The arm 4 is provided with a shoulder 8 and a projecting pin 9, upon which is journaled a handle 10, carrying the disk 7. A set-screw mounted at the outer end of the handle or any other suitable device may be provided by which the parts are kept in working relation. Upon the periphery of the disk 7 is mounted a series of branding characters 11, embedded in the periphery of the disk. The disk is preferably made of an insulating fireproof composition, such as artificial stone, which may be molded to the desired shape and in which the branding characters 11 may be fixed during the molding operation. Each branding character is formed of a thin strip of German silver bent to the shape required to form the character and provided at its terminals with current-leading conductors 12 13. One of these conductors, as 12, terminates on the inner face of the disk 7 in a stud or pin 14, (see Fig. 6,) the several studs 14 corresponding to the several characters being arranged concentrically with the axis of the disk and coöperating with a contact-spring 15, mounted on the shoulder 8, and insulated therefrom and electrically connected with a binding-post 16, by which connection may be made with an electric circuit. The conductors 13, leading to the other extremity of the several branding characters, are connected with a metallic ring 17, mounted in the face of the disk, against which bears a conducting-pin pressed inwardly by a spring 18, mounted upon the arm 4 and electrically connected with an insulated contact 24, coöperating with a contact-spring 25,



secured to binding-post 19. When the handle is depressed, contact is made at 24 25. Current will then flow through the character whose stud engages the spring 15.

5 The base-plate is provided with a series of rollers 20 20<sup>a</sup> 20<sup>b</sup>, mounted in uprights on its upper face, the rollers projecting slightly below the bottom of the base-plate. One of the rollers, as 20<sup>b</sup>, which is mounted centrally  
10 with respect to the sides of the base-plate and the rollers 20 20<sup>a</sup> is provided with a milled edge, so as to permit it to firmly engage the surface of the fabric and carries upon its shaft or axis a ratchet-wheel 21, coöperating  
15 with a spring-pressed pawl 22, so arranged that when the handle 10 has been depressed the pawl will engage a new tooth of the ratchet-wheel 21 and when the handle is  
20 lifted away by reaction of spring 6 the pawl will shift the ratchet-wheel 21 circumferentially and roll the apparatus laterally a distance sufficient to present to the branding-disk when again depressed a clean branding-surface. Thus when the disk is repeatedly  
25 depressed a series of characters will be branded side by side upon the fabric.

Upon the front face of the disk 7 is printed, embossed, or otherwise indicated a series of characters, as shown in Fig. 3, corresponding to the branding characters mounted upon  
30 the periphery of the disk, but placed on the opposite side of the axis, and an indicator 23 is placed in such position that when any character is brought in line with it, looking  
35 at the face of the disk, that character will be in branding position—that is to say, facing the surface upon which the base-plate 1 rests. Upon the side of the base-plate opposite the handle 10 is mounted a thumb-piece 26, by  
40 which the apparatus may be steadied during its manipulation.

The operation of the apparatus will now be understood. The instrument is placed upon the surface to be branded and the thumb-piece 26 grasped by one hand, while the handle 10 is turned until the character desired—say the dollar-mark—is brought in line with the indicator 23. The branding character corresponding to the dollar-mark is then in  
50 line to engage the surface of the fabric when the handle 10 is depressed. The handle 10 is then depressed, thereby closing the circuit. The resistance offered by the thin sheet metal forming the character brings it under action  
55 of the current to a branding temperature,

which may be regulated, as desired, to produce a scorching heat or a heat which will burn through the substance of the fabric. The handle is then permitted to rise under the pressure of spring 6 and the circuit is  
60 broken. Simultaneously the pawl shifts the roller 20<sup>b</sup>, pushing the apparatus laterally a distance sufficient to bring it in position to brand another character. The handle 10 is then turned to bring the next desired character in line with the indicator, when it may be branded. The operation may be repeated as often as desired until the required series of characters have been burned into the fabric.

It will of course be understood that the apparatus is not limited to branding a series of letters or numbers, but may be employed with a series of characters having any desired configuration, and may be employed for stenciling, canceling, pinking, or other uses wherein  
75 a design is required to be recorded upon the surface of a combustible or fusible material or fabric.

Having thus described my invention, what I claim as new, and desire to secure by Letters  
80 Patent, is—

1. An electric branding device provided with a rotatable disk carrying a series of circularly-arranged branding characters, a supporting-frame, means for holding the characters normally out of engagement with the surface upon which the frame rests, a guide-roller mounted on the frame and bearing upon the contact-surface, and means for turning the roller axially so as to shift the apparatus when the handle is operated, whereby a repeated operation of the handle will burn upon the fabric a series of characters side by side.

2. An electric branding device provided with a rotatable disk carrying a series of branding characters, said disk being mounted upon a spring-controlled pivoted arm, a pawl attached to the arm, and a guide-roller controlled by said pawl, said roller projecting slightly below the bottom of the base of the device, whereby the device is shifted after each act of branding.

In testimony whereof I have hereunto subscribed my name this 26th day of July, A. D. 1894.

HENRY VAN HOEVENBERGH.

Witnesses:

G. G. WHITE,  
H. A. FISHER.