




No. 626,658.

Patented June 6, 1899.

A. C. LEIGH.
CLOTHES POUNDER.

(Application filed Apr. 1, 1899.)

(No Model.)



Witnesses:
J. M. Birdsall
G. H. Purnum

Inventor:
Arthur C. Leigh.

UNITED STATES PATENT OFFICE.

ARTHUR C. LEIGH, OF DOWS, IOWA.

CLOTHES-POUNDER.

SPECIFICATION forming part of Letters Patent No. 626,658, dated June 6, 1899.

Application filed April 1, 1899. Serial No. 711,391. (No model.)

To all whom it may concern:

Be it known that I, ARTHUR C. LEIGH, a citizen of the United States of America, residing at Dows, in the county of Franklin and State of Iowa, have invented a Clothes-Pounder, of which the following is a specification.

My object is to provide a simple, strong, and durable device adapted to be advantageously operated by hand in a tub for forcing air and water through the meshes of articles of clothing and all kinds of woven fabrics to remove dirt therefrom.

My invention consists in the implement constructed and adapted to be operated as hereinafter set forth, pointed out in my claim, and illustrated in the accompanying drawings, in which—

Figure 1 is a sectional view of the device, showing transverse bracing-partitions and open-ended tubes supporting the partitions. Fig. 2 is a bottom view of the device. Fig. 3 is a modification of Fig. 1, showing a check-valve at a point below the bottom of a solid wooden handle.

The letter A designates the central body portion of the device in the form of a sheet-metal cylinder, and B the top portion in the shape of a cone that terminates in a screw-threaded socket C for a handle.

D is a hollow frustum fixed to the bottom of the cylinder A.

F is a partition fixed at the junction of cylinder A and top B, and F² is a corresponding partition fixed at the junction of the bottom of the cylinder and the top of the frustum.

Fixed vertical partitions H divide the hollow frustum into four distinct open-bottomed chambers, and each chamber communicates with the chamber in the top B by means of an open-topped tube J, fixed in the partitions F and F² in such a manner that air can pass down through the tubes in the chambers in the frustum.

K is a wooden handle fitted in the socket C, to be detachably connected with the top of the device, and is provided with a bore *m* and a valve *m'* at the bottom of the bore to admit air into the hollow top B.

In Fig. 3 a solid handle is used and a valve attached inside of the wall of the part B and over a vent in the wall.

In the practical use of my invention thus constructed when clothing is placed in a tub to be washed in hot soapsuds to submerge the articles I simply press and pound the goods by seizing the handle and moving the complete device up and down and about in the tub, so that the bottom edges of the walls of the four distinct chambers in the frustum will at each downward motion engage and press the flexible fabrics to be washed, and air and water will be forced through the meshes of the articles. At each upward motion air will be admitted into the hollow top portion of the device, and at each downward motion the check-valve will close and the confined air will be compressed and a portion thereof forced down through each tube into a chamber in the frustum to press upon the water that has risen into the chambers, so that air and water will be simultaneously forced through the textile fabrics that are thus successively pressed, as required, to loosen and remove dirt therefrom.

Having thus described my invention, its operation and utility will be readily understood by persons familiar with the art to which it pertains, and

What I therefore claim as new, and desire to secure by Letters Patent therefor, is—

A clothes-pounder, comprising a cylinder, a hollow cone at the top of the cylinder terminating in a socket for a handle, a wooden handle fitted in the socket and provided with a bore to admit air, and a check-valve to prevent air passing upward through the bore, a frustum fixed to the bottom of the cylinder and divided into distinct open-bottomed chambers, a transverse partition at the junction of the cylinder and hollow cone-shaped top, a partition at the junction of the cylinder and the frustum and open-ended tubes fixed in the said transverse partitions, all arranged and combined as shown and described to operate in the manner set forth for the purposes stated.

ARTHUR C. LEIGH.

Witnesses:

R. W. BIRDSALL,
U. H. RUMMEL.