
No. 632,321.

## J. P. OLNEY. EXHIBITION JAR.

(Application filed May 6, 1899.)

(No Model.)



## United States Patent Office.

JAMES P. OLNEY, OF ROME, NEW YORK.

## EXHIBITION-JAR.

SPECIFICATION forming part of Letters Patent No. 632,321, dated September 5, 1899.

Application filed May 6, 1899. Serial No. 715,799. (No model.)

To all whom it may concern:

Be it known that I, JAMES P. OLNEY, a citizen of the United States of America, and a resident of Rome, Oneida county, New York, 5 have invented certain new and useful Improvements in Exhibition-Jars, of which the following is a specification.

My invention relates to an improvement in exhibition-jars; and it consists in the arrange-10 ment of the parts, as hereinafter more par-

ticularly pointed out and claimed.

In the drawings, Figure 1 represents a side view of my exhibition-jars and jar-stand arranged on the plan hereinafter pointed out. 15 Fig. 2 is a vertical central section of a jar, its attachment, and the jar-stand on which the same is located. Fig. 3 is a perspective view of the sectional clamping-ring. Fig. 4 is a bottom view of the sectional clamping-20 ring. Figs. 5 and 6 are sections of the clamping-ring, showing the arrangement of the springs, catches, and parts.

corresponding parts in the several views.

25 On the upper face of the stand I provide circular holes or openings, which in this instance are shown to be dovetailed in shape, as illustrated at numeral 2 in Fig. 2, for the receipt of the neck of the jar. The jar 3 is 30 made of glass, with the upper end rounded and the neck provided with flange 4, Fig. 2, and into this jar I insert the requisite canned goods which are to be illustrated and exhibited and then insert cork 5 in the neck of 35 the jar and place it in the inverted position, (shown in Figs. 1 and 2,) the reck being inserted in recess 2. The neck of the jar properly corked is inverted and inserted in opening 2 in the jar-stand. Around this neck I 40 pour plaster-of-paris cast or other equivalent packing material 6, so as to hold the neck of the jar rigidly in a vertical position, as illustrated in Figs. 1 and 2. I employ on the jarstand, in such form and configuration as I de-45 sire, the requisite number of exhibition-jars required to properly illustrate the exhibit presented.

I place around the neck of the inverted jar what I term a "sectional" clamping-ring 50 7, formed in sections 7° and 7°, preferably formed of metal, and in this instance the ring I their vertical position. It should also be

has a corrugated surface in cross-section. Other forms of rings may be used. To one section of ring 7—viz., 7°—are attached springcatches 8, and the other section 7b is pro- 55 vided near the ends thereof with openings 10 to receive said catches at their free ends with catches 9 9, the catches fitting into slots 10 10 on section 7<sup>b</sup>, Fig. 5, so that when the two halves of the clamping-ring are brought 60 together the catches 9 9 on the ends of the four springs slip into slots 10 10 on the other half of the ring and form a close connection. The two sections of the ring when brought together have an annular opening 11 (best 65 illustrated in Figs. 3 and 4) and so made as to fit closely against the neck of the jar at 12 12, Fig. 2, and rest on the upper surface

of the jar-stand 1 at 13 13, Fig. 2.

For the purpose of still further steadying 70 the jars in their inverted position I provide three or more lips 14 14, (best illustrated in Fig. 4,) which are cut from the metal where In the drawings similar numerals refer to | the neck is cut away and turned downward and inward, as best illustrated in Fig. 2. 75 These lips can be placed substantially in a vertical line, so as to rest vertically against the neck of the inverted jar; but in this instance they are shown deflected away from the vertical line of the neck. It is obvious 80 that these features may be omitted, if it is thought desirable; but my preference is to have these lips arranged so as to engage and support the neck of the inverted jar held steadily in its position to prevent accidents 85 in handling the same.

The purpose of my invention is to furnish a compactly-arranged neat method of exhibiting in glass jars canned fruits and vegetables to be used as exhibits in stores and other 90 places where such exhibits are desired. By the arrangement of the parts as herein illustrated each jar is hermetically sealed, and the jar being transparent the fruit or vegetables contained in the jar are exposed to the 95 view of purchasers and those interested in the subject.

It should also be borne in mind that the sectional clamping-ring can be screwed or tacked to the jar-stand for giving additional 100 security in supporting the inverted jars in

noted that another feature of the jars consists in having the top portion rounded not only for beauty, but for convenience.

What I claim as new, and desire to secure

5 by Letters Patent, is—

1. The combination of the jar-stand having a recess, an inverted glass jar secured at its neck in the recess in the stand, and a sectional ring surrounding the neck of the jar 10 resting against the surface of the stand, with mechanism for securing the sectional ring in contact with the neck of the jar, for the pur-

poses stated.

2. A jar-stand provided with a dovetailed 15 recess in the stand, in combination with a glass jar having a neck at one end and a rounded portion at the opposite end inverted and placed in the opening in the jar-stand and suitable packing surrounding the neck 20 of the jar, and a sectional clamping-ring engaging the neck of the jar and the surface of the jar-stand, for the purposes stated.

3. A jar-stand and the inverted jars placed on the stand in combination with sectional 25 base-rings surrounding the necks of the jars and engaging the same and also engaging the jar-stand, and means for holding the sectional rings to the stand and to the neck of the inverted jars, for the purposes stated.

4. A jar-stand provided with inverted jars, in combination with a sectional metallic basering surrounding the neck of each jar with means for holding the sections of the ring together and each section of the rings provided with a lip turned downward into contact with 35 the neck of the jars, for the purposes stated.

5. A jar-stand and an inverted jar supported thereon in combination with a sectional clamping-ring arranged to engage the neck of the inverted jar and the surface of 40 the jar-stand, one section of the ring being provided with springs having catches at their ends and one section of the ring being provided with slotted catch-engaging openings for holding the parts of the ring together, for 45 the purposes stated.

6. A jar-stand, in combination with a transparent inverted jar, the inverted end of the jar resting on the stand, and a ring surrounding and engaging the neck of the jar secured 50 to the stand, substantially as set forth.

7. A jar-stand having a recess, in combination with a transparent inverted jar, the neck of which fits into the recess on the stand, packing surrounding the neck of the jar on 55 the recess for the purposes stated.

Signed by me at Rome, New York, this 14th

day of April, 1899.

JAMES P. OLNEY.

Witnesses:

J. S. BAKER,

D. L. Greenfield.