
## H. H. CONDIT. COMBINATION UNDERGARMENT.

(Application filed Sept. 7, 1899.)



## United States Patent Office.

## HARRY H. CONDIT, OF INDIANAPOLIS, INDIANA.

## COMBINATION UNDERGARMENT.

SPECIFICATION forming part of Letters Patent No. 637,708, dated November 21, 1899.

Application filed September 7, 1899. Serial No. 729,755. (No model.)

To all whom it may concern:

Be it known that I, HARRY H. CONDIT, a citizen of the United States, residing at Indianapolis, in the county of Marion and State of Indiana, have invented new and useful Improvements in Combination Undergarments, of which the following is a specification.

My invention relates to certain new and useful improvements in combination undergarments; and it has for its prime object to provide such a garment or suit wherein the use or employment of buttons is entirely dispensed with and a close and neat-fitting buttonless union garment provided.

Combination or union undergarments as now generally made are provided with numerous button-fastenings at the neck-opening, and it is the salient feature of the present invention to entirely obviate the use of such button-fastenings and to employ in lieu thereof a simple form of fastening means comprising draw and tying tapes or cords attached to opposite sides of the garment at the neck-opening in such position as to enable the free ends to be readily grasped and tied and wherein a neat and close fit may be secured.

The invention has for its objects other features of construction and arrangement of parts in the general formation and make-up of the garment, all of which will be hereinafter clearly set forth, and illustrated in the accompanying drawings, forming a part of this specification, wherein—

Figure 1 is a front view of the garment with one of the shoulder-flaps partly broken away to show the manner of attaching the tapes. Fig. 2 is a similar view of the upper portion of the garment, showing the shoulder-flaps thrown back.

Referring to the drawings, the referencenumeral 1 designates the body or shirt portion of the garment, having the usual sleeves
2 and drawers or leg portions 3, all of which
45 are preferably made of Jersey knitted fabric.
The back 4 of the shirt is provided with two
separate shoulder-flaps 5, which are cut or
rounded out at their upper edges 6 to provide a neck-opening, and each flap is provided
50 at its free end or point 7 with a tape or cord
opening 8, the said free ends of the flaps being preferably made to abut, so that the tape-

openings will lie close together in order to secure a neat and close fit of the garment, as will hereinafter appear. Each shoulder-flap 55 5 extends from the neck-opening outward to the armpits and is stitched along its extreme outer edge 9 to the sleeve portions of the garment, as will be seen. By preference I make the said shoulder-flaps of considerable length, 60 so that they will overlap the upper edge of the front of the garment and extend downward thereover for a considerable distance.

The front portion 10 of the garment extends upward nearly to the shoulder-line 11 65 and is secured only at its opposite side edges, thereby leaving the garment open at the top throughout its entire width. The upper edge 12 of the said front portion is folded over and stitched to provide a pocket throughout its 70 entire width for the reception of draw tapes or cords 13, said tapes or cords being secured at their upper ends to reinforcing-strips 14, sewed to the garment adjacent to the shoulder-line and preferably near the point of con- 75 nection between the sleeve and stitched outer edge 9 of the shoulder-flap, these parts being all stitched together at this point. The said upper edge 12 at the front of the garment is provided at a central point with a single open-80 ing 15, out through which the free ends of said draw tapes or cords pass, as will be seen from an inspection of the drawings. While I have herein shown and described the drawtapes as being secured near the shoulder-85 line, I wish it to be understood that I may attach them at other points without departing from the spirit of my invention. It is, however, of considerable advantage to secure the ends of the tapes at the particular points 90 herein indicated, since by drawing them somewhat tight a close and neat fit of the garment is secured, as the pull is directly upon the shoulder-line and sleeves.

In securing or fastening the garment upon 95 the body of the wearer it is simply necessary to pass the free ends of the tapes through the openings in the shoulder-flaps—one tape through one flap and the opposite tape through the other flap—and then draw upon the tapes 100 until a close and comfortable fit is secured, whereupon the tapes are tied as desired.

By the construction herein set forth it will be seen that I provide a novel and simple

form of combination or union garment wherein but a single fastening is required and where no buttons whatever are employed, thus enabling the garment to be easily and quickly 5 adjusted to position with a neat and close fit.

It will be obvious that instead of incasing the tapes or cords in a pocket at the upper free edge of the front of the garment I may run the said cords or tapes through said free 10 edge in any other suitable manner without departing from the spirit of my invention.

While I have herein shown and described my invention as being applied to combination or union garments, I do not wish to be under-15 stood as limiting myself to this form of garment specifically, for it will be obvious that the fastening means described may be employed in connection with other forms of wearing-apparel, such as ladies' undervests 20 and the like.

Having thus described my invention, what I claim is—

1. An undergarment provided with a pair of shoulder-flaps attached to the back por-25 tion of the garment and extending over upon the front thereof to provide a central neckopening, and a pair of fastening tapes or cords each secured at one end to opposite sides of the garment adjacent to the sleeves and trav-30 ersing the upper free edge of the front to a central point therein where the ends of said tapes hang free in a position to engage suitable openings in the adjacent free ends of the said shoulder-flaps.

2. An undergarment provided with a pair of shoulder-flaps secured at their outer edges to the front of the garment adjacent to the armpits, and draw-tapes secured to opposite sides of the garment near the sleeves and traversing the upper free edge of the front to 40 a central point therein where the ends of said tapes hang free in a position to enter suitable openings in the adjacent free ends of the said

shoulder-flaps.

3. A union undergarment comprising con- 45 nected body, leg, and arm portions, a pair of shoulder-flaps formed with the back portion of the garment extending over upon the front thereof and having their outer edges secured to said front and to the arm portions, and 50 fastening-tapes each attached at one end to the front of the garment at the neck and having their free ends arranged to enter suitable openings in the adjacent ends of the said shoulder-flaps.

4. A union undergarment comprising integral body, leg, and arm portions, a pair of shoulder-flaps formed with the back portion of the garment extending over upon the front thereof and secured at their outer edges to 60 the extreme sides of the front, said flaps being cut out at their upper edges to provide a neck-opening, the front of said garment being extended upward to a point near the shoulder-line and having its free edge provided 65 with a pocket, and draw-tapes secured to opposite sides of the garment adjacent to the sleeves and located within said pocket, the free ends of said tapes leaving the pocket at a central point in position to enter suitable 70 openings in the free ends of the shoulder-flaps.

In testimony whereof I have hereunto set my hand in the presence of two subscribing

witnesses.

HARRY H. CONDIT.

Witnesses:

ALBERT ASCHE. CHARLES ALCON.